

---

# **Sanic Documentation**

*Release 19.9.0*

**Sanic contributors**

**Oct 15, 2019**



# CONTENTS

<b>1</b>	<b>Sanic aspires to be simple</b>	<b>3</b>
<b>2</b>	<b>Guides</b>	<b>5</b>
2.1	Getting Started . . . . .	5
2.2	Configuration . . . . .	6
2.3	Logging . . . . .	10
2.4	Request Data . . . . .	12
2.5	Response . . . . .	16
2.6	Cookies . . . . .	18
2.7	Routing . . . . .	19
2.8	Blueprints . . . . .	27
2.9	Static Files . . . . .	31
2.10	Versioning . . . . .	33
2.11	Exceptions . . . . .	34
2.12	Middleware And Listeners . . . . .	35
2.13	WebSocket . . . . .	38
2.14	Handler Decorators . . . . .	39
2.15	Streaming . . . . .	40
2.16	Class-Based Views . . . . .	42
2.17	Custom Protocols . . . . .	45
2.18	Sockets . . . . .	46
2.19	SSL Example . . . . .	47
2.20	Debug Mode . . . . .	48
2.21	Testing . . . . .	49
2.22	Deploying . . . . .	51
2.23	Extensions . . . . .	54
2.24	Examples . . . . .	54
2.25	Changelog . . . . .	71
2.26	Contributing . . . . .	78
2.27	API Reference . . . . .	82
2.28	Python 3.7 AsyncIO examples . . . . .	129
<b>3</b>	<b>Module Documentation</b>	<b>131</b>
	<b>Python Module Index</b>	<b>133</b>
	<b>Index</b>	<b>135</b>



Sanic is a Python 3.6+ web server and web framework that's written to go fast. It allows the usage of the `async/await` syntax added in Python 3.5, which makes your code non-blocking and speedy.

The goal of the project is to provide a simple way to get up and running a highly performant HTTP server that is easy to build, to expand, and ultimately to scale.

Sanic is developed on [GitHub](#). Contributions are welcome!



## SANIC ASPIRES TO BE SIMPLE

```
from sanic import Sanic
from sanic.response import json

app = Sanic()

@app.route("/")
async def test(request):
    return json({"hello": "world"})

if __name__ == "__main__":
    app.run(host="0.0.0.0", port=8000)
```

---

**Note:** Sanic does not support Python 3.5 from version 19.6 and forward. However, version 18.12LTS is supported thru December 2020. Official Python support for version 3.5 is set to expire in September 2020.

---





## 2.1 Getting Started

Make sure you have both `pip` and at least version 3.6 of Python before starting. Sanic uses the new `async/await` syntax, so earlier versions of python won't work.

### 2.1.1 1. Install Sanic

If you are running on a clean install of Fedora 28 or above, please make sure you have the `redhat-rpm-config` package installed in case if you want to use `sanic` with `ujson` dependency.

```
pip3 install sanic
```

To install `sanic` without `uvloop` or `ujson` using `bash`, you can provide either or both of these environmental variables using any truthy string like `'y'`, `'yes'`, `'t'`, `'true'`, `'on'`, `'1'` and setting the `SANIC_NO_X` (`X = UVLOOP/UJSON`) to `true` will stop that features installation.

```
SANIC_NO_UVLOOP=true SANIC_NO_UJSON=true pip3 install sanic
```

You can also install Sanic from `conda-forge`

```
conda config --add channels conda-forge
conda install sanic
```

### 2.1.2 2. Create a file called `main.py`

```
from sanic import Sanic
from sanic.response import json

app = Sanic()

@app.route("/")
async def test(request):
    return json({"hello": "world"})

if __name__ == "__main__":
    app.run(host="0.0.0.0", port=8000)
```

### 2.1.3 3. Run the server

```
python3 main.py
```

### 2.1.4 4. Check your browser

Open the address `http://0.0.0.0:8000` in your web browser. You should see the message *Hello world!*.

You now have a working Sanic server!

## 2.2 Configuration

Any reasonably complex application will need configuration that is not baked into the actual code. Settings might be different for different environments or installations.

### 2.2.1 Basics

Sanic holds the configuration in the `config` attribute of the application object. The configuration object is merely an object that can be modified either using dot-notation or like a dictionary:

```
app = Sanic('myapp')
app.config.DB_NAME = 'appdb'
app.config.DB_USER = 'appuser'
```

Since the config object actually is a dictionary, you can use its `update` method in order to set several values at once:

```
db_settings = {
    'DB_HOST': 'localhost',
    'DB_NAME': 'appdb',
    'DB_USER': 'appuser'
}
app.config.update(db_settings)
```

In general the convention is to only have UPPERCASE configuration parameters. The methods described below for loading configuration only look for such uppercase parameters.

### 2.2.2 Loading Configuration

There are several ways how to load configuration.

#### From Environment Variables

Any variables defined with the `SANIC_` prefix will be applied to the sanic config. For example, setting `SANIC_REQUEST_TIMEOUT` will be loaded by the application automatically and fed into the `REQUEST_TIMEOUT` config variable. You can pass a different prefix to Sanic:

```
app = Sanic(load_env='MYAPP_')
```

Then the above variable would be `MYAPP_REQUEST_TIMEOUT`. If you want to disable loading from environment variables you can set it to `False` instead:

```
app = Sanic(load_env=False)
```

## From an Object

If there are a lot of configuration values and they have sensible defaults it might be helpful to put them into a module:

```
import myapp.default_settings

app = Sanic('myapp')
app.config.from_object(myapp.default_settings)
```

or also by path to config:

```
app = Sanic('myapp')
app.config.from_object('config.path.config.Class')
```

You could use a class or any other object as well.

## From a File

Usually you will want to load configuration from a file that is not part of the distributed application. You can load configuration from a file using `from_pyfile(/path/to/config_file)`. However, that requires the program to know the path to the config file. So instead you can specify the location of the config file in an environment variable and tell Sanic to use that to find the config file:

```
app = Sanic('myapp')
app.config.from_envvar('MYAPP_SETTINGS')
```

Then you can run your application with the `MYAPP_SETTINGS` environment variable set:

```
$ MYAPP_SETTINGS=/path/to/config_file python3 myapp.py
INFO: Goin' Fast @ http://0.0.0.0:8000
```

The config files are regular Python files which are executed in order to load them. This allows you to use arbitrary logic for constructing the right configuration. Only uppercase variables are added to the configuration. Most commonly the configuration consists of simple key value pairs:

```
# config_file
DB_HOST = 'localhost'
DB_NAME = 'appdb'
DB_USER = 'appuser'
```

### 2.2.3 Builtin Configuration Values

Out of the box there are just a few predefined values which can be overwritten when creating the application.

Variable	Default	Description
-----	-----	-----
REQUEST_MAX_SIZE	100000000	How big a request may be (bytes)

(continues on next page)

(continued from previous page)

REQUEST_BUFFER_QUEUE_SIZE	100	Request streaming buffer queue size.
↪		
REQUEST_TIMEOUT	60	How long a request can take to
↪ arrive (sec)		
RESPONSE_TIMEOUT	60	How long a response can take to
↪ process (sec)		
KEEP_ALIVE	<b>True</b>	Disables keep-alive when <b>False</b>
↪		
KEEP_ALIVE_TIMEOUT	5	How long to hold a TCP connection.
↪ open (sec)		
GRACEFUL_SHUTDOWN_TIMEOUT	15.0	How long to wait to force close non-
↪ idle connection (sec)		
ACCESS_LOG	<b>True</b>	Disable <b>or</b> enable access log
↪		
PROXIES_COUNT	-1	The number of proxy servers <b>in</b>
↪ front of the app (e.g. nginx; see below)		
FORWARDED_FOR_HEADER	"X-Forwarded-For"	The name of "X-Forwarded-For" HTTP
↪ header that contains client <b>and</b> proxy ip		
REAL_IP_HEADER	"X-Real-IP"	The name of "X-Real-IP" HTTP header
↪ that contains real client ip		

## The different Timeout variables:

### REQUEST\_TIMEOUT

A request timeout measures the duration of time between the instant when a new open TCP connection is passed to the Sanic backend server, and the instant when the whole HTTP request is received. If the time taken exceeds the `REQUEST_TIMEOUT` value (in seconds), this is considered a Client Error so Sanic generates an HTTP 408 response and sends that to the client. Set this parameter's value higher if your clients routinely pass very large request payloads or upload requests very slowly.

### RESPONSE\_TIMEOUT

A response timeout measures the duration of time between the instant the Sanic server passes the HTTP request to the Sanic App, and the instant a HTTP response is sent to the client. If the time taken exceeds the `RESPONSE_TIMEOUT` value (in seconds), this is considered a Server Error so Sanic generates an HTTP 503 response and sends that to the client. Set this parameter's value higher if your application is likely to have long-running process that delay the generation of a response.

### KEEP\_ALIVE\_TIMEOUT

## What is Keep Alive? And what does the Keep Alive Timeout value do?

Keep-Alive is a HTTP feature introduced in HTTP 1.1. When sending a HTTP request, the client (usually a web browser application) can set a Keep-Alive header to indicate the http server (Sanic) to not close the TCP connection after it has send the response. This allows the client to reuse the existing TCP connection to send subsequent HTTP requests, and ensures more efficient network traffic for both the client and the server.

The `KEEP_ALIVE` config variable is set to `True` in Sanic by default. If you don't need this feature in your application, set it to `False` to cause all client connections to close immediately after a response is sent, regardless of the Keep-Alive header on the request.

The amount of time the server holds the TCP connection open is decided by the server itself. In Sanic, that value is configured using the `KEEP_ALIVE_TIMEOUT` value. By default, it is set to 5 seconds. This is the same default setting as the Apache HTTP server and is a good balance between allowing enough time for the client to send a new request, and not holding open too many connections at once. Do not exceed 75 seconds unless you know your clients are using a browser which supports TCP connections held open for that long.

For reference:

```
Apache httpd server default keepalive timeout = 5 seconds
Nginx server default keepalive timeout = 75 seconds
Nginx performance tuning guidelines uses keepalive = 15 seconds
IE (5-9) client hard keepalive limit = 60 seconds
Firefox client hard keepalive limit = 115 seconds
Opera 11 client hard keepalive limit = 120 seconds
Chrome 13+ client keepalive limit > 300+ seconds
```

## Proxy configuration

When you use a reverse proxy server (e.g. nginx), the value of `request.ip` will contain ip of a proxy, typically `127.0.0.1`. Sanic may be configured to use proxy headers for determining the true client IP, available as `request.remote_addr`. The full external URL is also constructed from header fields if available.

Without proper precautions, a malicious client may use proxy headers to spoof its own IP. To avoid such issues, Sanic does not use any proxy headers unless explicitly enabled.

Services behind reverse proxies must configure `FORWARDED_SECRET`, `REAL_IP_HEADER` and/or `PROXIES_COUNT`.

## Forwarded header

```
Forwarded: for="1.2.3.4"; proto="https"; host="yoursite.com"; secret="Pr0xy",
          for="10.0.0.1"; proto="http"; host="proxy.internal"; by="_1234proxy"
```

- Set `FORWARDED_SECRET` to an identifier used by the proxy of interest.

The secret is used to securely identify a specific proxy server. Given the above header, secret `Pr0xy` would use the information on the first line and secret `_1234proxy` would use the second line. The secret must exactly match the value of `secret` or `by`. A secret in `by` must begin with an underscore and use only characters specified in [RFC 7239 section 6.3](#), while `secret` has no such restrictions.

Sanic ignores any elements without the secret key, and will not even parse the header if no secret is set.

All other proxy headers are ignored once a trusted forwarded element is found, as it already carries complete information about the client.

## Traditional proxy headers

```
X-Real-IP: 1.2.3.4
X-Forwarded-For: 1.2.3.4, 10.0.0.1
X-Forwarded-Proto: https
X-Forwarded-Host: yoursite.com
```

- Set `REAL_IP_HEADER` to `x-real-ip`, `true-client-ip`, `cf-connecting-ip` or other name of such header.

- Set `PROXIES_COUNT` to the number of entries expected in `x-forwarded-for` (name configurable via `FORWARDED_FOR_HEADER`).

If client IP is found by one of these methods, Sanic uses the following headers for URL parts:

- `x-forwarded-proto`, `x-forwarded-host`, `x-forwarded-port`, `x-forwarded-path` and if necessary, `x-scheme`.

### Proxy config if using ...

- a proxy that supports `forwarded`: set `FORWARDED_SECRET` to the value that the proxy inserts in the header
  - Apache Traffic Server: `CONFIG proxy.config.http.insert_forwarded STRING for|proto|host|by=_secret`
  - NGHTTPX: `nghttpx --add-forwarded=for,proto,host,by --forwarded-for=ip --forwarded-by=_secret`
  - NGINX: after the official instructions, add anywhere in your config:

```
proxy_set_header Forwarded "$proxy_add_forwarded;by=\"_$_server_name\";proto=↵$scheme;host=\"$http_host\";path=\"$request_uri\";secret=_secret";
```

- a custom header with client IP: set `REAL_IP_HEADER` to the name of that header
- `x-forwarded-for`: set `PROXIES_COUNT` to 1 for a single proxy, or a greater number to allow Sanic to select the correct IP
- no proxies: no configuration required!

### Changes in Sanic 19.9

Earlier Sanic versions had unsafe default settings. From 19.9 onwards proxy settings must be set manually, and support for negative `PROXIES_COUNT` has been removed.

## 2.3 Logging

Sanic allows you to do different types of logging (access log, error log) on the requests based on the [python3 logging API](#). You should have some basic knowledge on python3 logging if you want to create a new configuration.

### 2.3.1 Quick Start

A simple example using default settings would be like this:

```
from sanic import Sanic
from sanic.log import logger
from sanic.response import text

app = Sanic('test')

@app.route('/')
async def test(request):
    logger.info('Here is your log')
```

(continues on next page)

(continued from previous page)

```

return text('Hello World!')

if __name__ == "__main__":
    app.run(debug=True, access_log=True)

```

After the server is running, you can see some messages looks like:

```

[2018-11-06 21:16:53 +0800] [24622] [INFO] Goin' Fast @ http://127.0.0.1:8000
[2018-11-06 21:16:53 +0800] [24667] [INFO] Starting worker [24667]

```

You can send a request to server and it will print the log messages:

```

[2018-11-06 21:18:53 +0800] [25685] [INFO] Here is your log
[2018-11-06 21:18:53 +0800] - (sanic.access)[INFO][127.0.0.1:57038]: GET http://
↳localhost:8000/ 200 12

```

To use your own logging config, simply use `logging.config.dictConfig`, or pass `log_config` when you initialize Sanic app:

```
app = Sanic('test', log_config=LOGGING_CONFIG)
```

And to close logging, simply assign `access_log=False`:

```

if __name__ == "__main__":
    app.run(access_log=False)

```

This would skip calling logging functions when handling requests. And you could even do further in production to gain extra speed:

```

if __name__ == "__main__":
    # disable debug messages
    app.run(debug=False, access_log=False)

```

## 2.3.2 Configuration

By default, `log_config` parameter is set to use `sanic.log.LOGGING_CONFIG_DEFAULTS` dictionary for configuration.

There are three loggers used in sanic, and **must be defined if you want to create your own logging configuration**:

Logger Name	Usecase
<code>sanic.root</code>	Used to log internal messages.
<code>sanic.error</code>	Used to log error logs.
<code>sanic.access</code>	Used to log access logs.

### Log format:

In addition to default parameters provided by python (`asctime`, `levelname`, `message`), Sanic provides additional parameters for access logger with:

Log Context Parameter	Parameter Value	Datatype
host	request.ip	str
request	request.method + " " + request.url	str
status	response.status	int
byte	len(response.body)	int

The default access log format is `%(asctime)s - %(name)s [%(levelname)s] [%(host)s] : %(request)s %(message)s %(status)d %(byte)d`

## 2.4 Request Data

When an endpoint receives a HTTP request, the route function is passed a Request object.

The following variables are accessible as properties on Request objects:

- `json` (any) - JSON body

```
from sanic.response import json

@app.route("/json")
def post_json(request):
    return json({ "received": True, "message": request.json })
```

- `args` (dict) - Query string variables. A query string is the section of a URL that resembles `?key1=value1&key2=value2`. If that URL were to be parsed, the `args` dictionary would look like `{'key1': ['value1'], 'key2': ['value2']}`. The request's `query_string` variable holds the unparsed string value. Property is providing the default parsing strategy. If you would like to change it look to the section below (Changing the default parsing rules of the queryset).

```
from sanic.response import json

@app.route("/query_string")
def query_string(request):
    return json({ "parsed": True, "args": request.args, "url": request.url,
    ↪"query_string": request.query_string })
```

- `query_args` (list) - On many cases you would need to access the url arguments in a less packed form. `query_args` is the list of (key, value) tuples. Property is providing the default parsing strategy. If you would like to change it look to the section below (Changing the default parsing rules of the queryset). For the same previous URL queryset `?key1=value1&key2=value2`, the `query_args` list would look like `[('key1', 'value1'), ('key2', 'value2')]`. And in case of the multiple params with the same key like `?key1=value1&key2=value2&key1=value3` the `query_args` list would look like `[('key1', 'value1'), ('key2', 'value2'), ('key1', 'value3')]`.

The difference between `Request.args` and `Request.query_args` for the queryset `?key1=value1&key2=value2&key1=value3`

```
from sanic import Sanic
from sanic.response import json

app = Sanic(__name__)

@app.route("/test_request_args")
```

(continues on next page)



(continued from previous page)

```

async def test_request_args(request):
    return json({
        "parsed": True,
        "url": request.url,
        "query_string": request.query_string,
        "args": request.args,
        "raw_args": request.raw_args,
        "query_args": request.query_args,
    })

if __name__ == '__main__':
    app.run(host="0.0.0.0", port=8000)

```

**Output**

```

{
  "parsed":true,
  "url":"http://0.0.0.0:8000/test_request_args?key1=value1&key2=value2&
↪key1=value3",
  "query_string":"key1=value1&key2=value2&key1=value3",
  "args":{"key1":["value1","value3"],"key2":["value2"]},
  "raw_args":{"key1":"value1","key2":"value2"},
  "query_args":[["key1","value1"],["key2","value2"],["key1","value3"]]
}

```

raw\_args contains only the first entry of key1. Will be deprecated in the future versions.

- files (dictionary of File objects) - List of files that have a name, body, and type

```

from sanic.response import json

@app.route("/files")
def post_json(request):
    test_file = request.files.get('test')

    file_parameters = {
        'body': test_file.body,
        'name': test_file.name,
        'type': test_file.type,
    }

    return json({ "received": True, "file_names": request.files.keys(), "test_
↪file_parameters": file_parameters })

```

- form (dict) - Posted form variables.

```

from sanic.response import json

@app.route("/form")
def post_json(request):
    return json({ "received": True, "form_data": request.form, "test": request.
↪form.get('test') })

```

- body (bytes) - Posted raw body. This property allows retrieval of the request's raw data, regardless of content type.

```

from sanic.response import text

@app.route("/users", methods=["POST",])
def create_user(request):
    return text("You are trying to create a user with the following POST: %s" % request.body)

```

- headers (dict) - A case-insensitive dictionary that contains the request headers.
- method (str) - HTTP method of the request (ie GET, POST).
- ip (str) - IP address of the requester.
- port (str) - Port address of the requester.
- socket (tuple) - (IP, port) of the requester.
- app - a reference to the Sanic application object that is handling this request. This is useful when inside blueprints or other handlers in modules that do not have access to the global app object.

```

from sanic.response import json
from sanic import Blueprint

bp = Blueprint('my_blueprint')

@bp.route('/')
async def bp_root(request):
    if request.app.config['DEBUG']:
        return json({'status': 'debug'})
    else:
        return json({'status': 'production'})

```

- url: The full URL of the request, ie: `http://localhost:8000/posts/1/?foo=bar`
- scheme: The URL scheme associated with the request: 'http|https|wslwss' or arbitrary value given by the headers.
- host: The host associated with the request(which in the Host header): `localhost:8080`
- server\_name: The hostname of the server, without port number. the value is seeked in this order: `config.SERVER_NAME`, `x-forwarded-host` header, `:func:Request.host`
- server\_port: Like `server_name`. Seeked in this order: `x-forwarded-port` header, `:func:Request.host`, actual port used by the transport layer socket.
- path: The path of the request: `/posts/1/`
- query\_string: The query string of the request: `foo=bar` or a blank string `' '`
- uri\_template: Template for matching route handler: `/posts/<id>/`
- token: The value of Authorization header: `Basic YWRtaW46YWRtaW4=`
- url\_for: Just like `sanic.Sanic.url_for`, but automatically determine scheme and netloc base on the request. Since this method is aiming to generate correct schema & netloc, `_external` is implied.

## 2.4.1 Changing the default parsing rules of the queryset

The default parameters that are using internally in `args` and `query_args` properties to parse queryset:

- `keep_blank_values` (bool): False - flag indicating whether blank values in percent-encoded queries should be treated as blank strings. A true value indicates that blanks should be retained as blank strings. The default false value indicates that blank values are to be ignored and treated as if they were not included.
- `strict_parsing` (bool): False - flag indicating what to do with parsing errors. If false (the default), errors are silently ignored. If true, errors raise a `ValueError` exception.
- `encoding and errors` (str): 'utf-8' and 'replace' - specify how to decode percent-encoded sequences into Unicode characters, as accepted by the `bytes.decode()` method.

If you would like to change that default parameters you could call `get_args` and `get_query_args` methods with the new values.

For the queryset `?test1=value1&test2=&test3=value3`:

```
from sanic.response import json

@app.route("/query_string")
def query_string(request):
    args_with_blank_values = request.get_args(keep_blank_values=True)
    return json({
        "parsed": True,
        "url": request.url,
        "args_with_blank_values": args_with_blank_values,
        "query_string": request.query_string
    })
```

The output will be:

```
{
  "parsed": true,
  "url": "http://\0.0.0.0:8000\query_string?test1=value1&test2=&test3=value3",
  "args_with_blank_values": {"test1": ["value1"], "test2": "", "test3": ["value3"]},
  "query_string": "test1=value1&test2=&test3=value3"
}
```

## 2.4.2 Accessing values using `get` and `getlist`

The request properties which return a dictionary actually return a subclass of `dict` called `RequestParameters`. The key difference when using this object is the distinction between the `get` and `getlist` methods.

- `get(key, default=None)` operates as normal, except that when the value of the given key is a list, *only the first item is returned*.
- `getlist(key, default=None)` operates as normal, *returning the entire list*.

```
from sanic.request import RequestParameters

args = RequestParameters()
args['titles'] = ['Post 1', 'Post 2']

args.get('titles') # => 'Post 1'

args.getlist('titles') # => ['Post 1', 'Post 2']
```

### 2.4.3 Accessing the handler name with the request.endpoint attribute

The `request.endpoint` attribute holds the handler's name. For instance, the below route will return "hello".

```
from sanic.response import text
from sanic import Sanic

app = Sanic()

@app.get("/")
def hello(request):
    return text(request.endpoint)
```

Or, with a blueprint it will be include both, separated by a period. For example, the below route would return `foo.bar`:

```
from sanic import Sanic
from sanic import Blueprint
from sanic.response import text

app = Sanic(__name__)
blueprint = Blueprint('foo')

@blueprint.get('/')
async def bar(request):
    return text(request.endpoint)

app.blueprint(blueprint)

app.run(host="0.0.0.0", port=8000, debug=True)
```

## 2.5 Response

Use functions in `sanic.response` module to create responses.

### 2.5.1 Plain Text

```
from sanic import response

@app.route('/text')
def handle_request(request):
    return response.text('Hello world!')
```

### 2.5.2 HTML

```
from sanic import response

@app.route('/html')
def handle_request(request):
    return response.html('<p>Hello world!</p>')
```

### 2.5.3 JSON

```
from sanic import response

@app.route('/json')
def handle_request(request):
    return response.json({'message': 'Hello world!'})
```

### 2.5.4 File

```
from sanic import response

@app.route('/file')
async def handle_request(request):
    return await response.file('/srv/www/whatever.png')
```

### 2.5.5 Streaming

```
from sanic import response

@app.route("/streaming")
async def index(request):
    async def streaming_fn(response):
        await response.write('foo')
        await response.write('bar')
    return response.stream(streaming_fn, content_type='text/plain')
```

See [Streaming](#) for more information.

### 2.5.6 File Streaming

For large files, a combination of [File](#) and [Streaming](#) above

```
from sanic import response

@app.route('/big_file.png')
async def handle_request(request):
    return await response.file_stream('/srv/www/whatever.png')
```

### 2.5.7 Redirect

```
from sanic import response

@app.route('/redirect')
def handle_request(request):
    return response.redirect('/json')
```

## 2.5.8 Raw

Response without encoding the body

```
from sanic import response

@app.route('/raw')
def handle_request(request):
    return response.raw(b'raw data')
```

## 2.5.9 Modify headers or status

To modify headers or status code, pass the `headers` or `status` argument to those functions:

```
from sanic import response

@app.route('/json')
def handle_request(request):
    return response.json(
        {'message': 'Hello world!'},
        headers={'X-Served-By': 'sanic'},
        status=200
    )
```

## 2.6 Cookies

Cookies are pieces of data which persist inside a user's browser. Sanic can both read and write cookies, which are stored as key-value pairs.

**Warning:** Cookies can be freely altered by the client. Therefore you cannot just store data such as login information in cookies as-is, as they can be freely altered by the client. To ensure data you store in cookies is not forged or tampered with by the client, use something like [itsdangerous](#) to cryptographically sign the data.

### 2.6.1 Reading cookies

A user's cookies can be accessed via the `Request` object's `cookies` dictionary.

```
from sanic.response import text

@app.route("/cookie")
async def test(request):
    test_cookie = request.cookies.get('test')
    return text("Test cookie set to: {}".format(test_cookie))
```

### 2.6.2 Writing cookies

When returning a response, cookies can be set on the `Response` object.

```

from sanic.response import text

@app.route("/cookie")
async def test(request):
    response = text("There's a cookie up in this response")
    response.cookies['test'] = 'It worked!'
    response.cookies['test']['domain'] = '.gotta-go-fast.com'
    response.cookies['test']['httponly'] = True
    return response

```

### 2.6.3 Deleting cookies

Cookies can be removed semantically or explicitly.

```

from sanic.response import text

@app.route("/cookie")
async def test(request):
    response = text("Time to eat some cookies muahaha")

    # This cookie will be set to expire in 0 seconds
    del response.cookies['kill_me']

    # This cookie will self destruct in 5 seconds
    response.cookies['short_life'] = 'Glad to be here'
    response.cookies['short_life']['max-age'] = 5
    del response.cookies['favorite_color']

    # This cookie will remain unchanged
    response.cookies['favorite_color'] = 'blue'
    response.cookies['favorite_color'] = 'pink'
    del response.cookies['favorite_color']

    return response

```

Response cookies can be set like dictionary values and have the following parameters available:

- `expires` (datetime): The time for the cookie to expire on the client's browser.
- `path` (string): The subset of URLs to which this cookie applies. Defaults to `/`.
- `comment` (string): A comment (metadata).
- `domain` (string): Specifies the domain for which the cookie is valid. An explicitly specified domain must always start with a dot.
- `max-age` (number): Number of seconds the cookie should live for.
- `secure` (boolean): Specifies whether the cookie will only be sent via HTTPS.
- `httponly` (boolean): Specifies whether the cookie cannot be read by Javascript.

## 2.7 Routing

Routing allows the user to specify handler functions for different URL endpoints.

A basic route looks like the following, where `app` is an instance of the `Sanic` class:

```
from sanic.response import json

@app.route("/")
async def test(request):
    return json({ "hello": "world" })
```

When the url `http://server.url/` is accessed (the base url of the server), the final `/` is matched by the router to the handler function, `test`, which then returns a JSON object.

Sanic handler functions must be defined using the `async def` syntax, as they are asynchronous functions.

## 2.7.1 Request parameters

Sanic comes with a basic router that supports request parameters.

To specify a parameter, surround it with angle quotes like so: `<PARAM>`. Request parameters will be passed to the route handler functions as keyword arguments.

```
from sanic.response import text

@app.route('/tag/<tag>')
async def tag_handler(request, tag):
    return text('Tag - {}'.format(tag))
```

To specify a type for the parameter, add a `:type` after the parameter name, inside the quotes. If the parameter does not match the specified type, Sanic will throw a `NotFound` exception, resulting in a `404: Page not found` error on the URL.

### Supported types

- `string`
  - "Bob"
  - "Python 3"
- `int`
  - 10
  - 20
  - 30
  - -10
  - (No floats work here)
- `number`
  - 1
  - 1.5
  - 10
  - -10
- `alpha`
  - "Bob"



- "Python"
- (If it contains a symbol or a non alphanumeric character it will fail)
- path
  - "hello"
  - "hello.text"
  - "hello world"
- uuid
  - 123a123a-a12a-1a1a-a1a1-1a12a1a12345 (UUIDv4 Support)
- regex expression

If no type is set then a string is expected. The argument given to the function will always be a string, independent of the type.

```

from sanic.response import text

@app.route('/string/<string_arg:string>')
async def string_handler(request, string_arg):
    return text('String - {}'.format(string_arg))

@app.route('/int/<integer_arg:int>')
async def integer_handler(request, integer_arg):
    return text('Integer - {}'.format(integer_arg))

@app.route('/number/<number_arg:number>')
async def number_handler(request, number_arg):
    return text('Number - {}'.format(number_arg))

@app.route('/alpha/<alpha_arg:alpha>')
async def number_handler(request, alpha_arg):
    return text('Alpha - {}'.format(alpha_arg))

@app.route('/path/<path_arg:path>')
async def number_handler(request, path_arg):
    return text('Path - {}'.format(path_arg))

@app.route('/uuid/<uuid_arg:uuid>')
async def number_handler(request, uuid_arg):
    return text('Uuid - {}'.format(uuid_arg))

@app.route('/person/<name:[A-z]+>')
async def person_handler(request, name):
    return text('Person - {}'.format(name))

@app.route('/folder/<folder_id:[A-z0-9]{0,4}>')
async def folder_handler(request, folder_id):
    return text('Folder - {}'.format(folder_id))

```

**Warning** `str` is not a valid type tag. If you want `str` recognition then you must use `string`

## 2.7.2 HTTP request types

By default, a route defined on a URL will be available for only GET requests to that URL. However, the `@app.route` decorator accepts an optional parameter, `methods`, which allows the handler function to work with any of the HTTP

methods in the list.

```
from sanic.response import text

@app.route('/post', methods=['POST'])
async def post_handler(request):
    return text('POST request - {}'.format(request.json))

@app.route('/get', methods=['GET'])
async def get_handler(request):
    return text('GET request - {}'.format(request.args))
```

There is also an optional `host` argument (which can be a list or a string). This restricts a route to the host or hosts provided. If there is also a route with no host, it will be the default.

```
@app.route('/get', methods=['GET'], host='example.com')
async def get_handler(request):
    return text('GET request - {}'.format(request.args))

# if the host header doesn't match example.com, this route will be used
@app.route('/get', methods=['GET'])
async def get_handler(request):
    return text('GET request in default - {}'.format(request.args))
```

There are also shorthand method decorators:

```
from sanic.response import text

@app.post('/post')
async def post_handler(request):
    return text('POST request - {}'.format(request.json))

@app.get('/get')
async def get_handler(request):
    return text('GET request - {}'.format(request.args))
```

### 2.7.3 The `add_route` method

As we have seen, routes are often specified using the `@app.route` decorator. However, this decorator is really just a wrapper for the `app.add_route` method, which is used as follows:

```
from sanic.response import text

# Define the handler functions
async def handler1(request):
    return text('OK')

async def handler2(request, name):
    return text('Folder - {}'.format(name))

async def person_handler2(request, name):
    return text('Person - {}'.format(name))

# Add each handler function as a route
app.add_route(handler1, '/test')
app.add_route(handler2, '/folder/<name>')
app.add_route(person_handler2, '/person/<name:[A-z]>', methods=['GET'])
```

## 2.7.4 URL building with `url_for`

Sanic provides a `url_for` method, to generate URLs based on the handler method name. This is useful if you want to avoid hardcoding url paths into your app; instead, you can just reference the handler name. For example:

```
from sanic.response import redirect

@app.route('/')
async def index(request):
    # generate a URL for the endpoint `post_handler`
    url = app.url_for('post_handler', post_id=5)
    # the URL is `/posts/5`, redirect to it
    return redirect(url)

@app.route('/posts/<post_id>')
async def post_handler(request, post_id):
    return text('Post - {}'.format(post_id))
```

Other things to keep in mind when using `url_for`:

- Keyword arguments passed to `url_for` that are not request parameters will be included in the URL's query string. For example:

```
url = app.url_for('post_handler', post_id=5, arg_one='one', arg_two='two')
# /posts/5?arg_one=one&arg_two=two
```

- Multivalue argument can be passed to `url_for`. For example:

```
url = app.url_for('post_handler', post_id=5, arg_one=['one', 'two'])
# /posts/5?arg_one=one&arg_one=two
```

- Also some special arguments (`_anchor`, `_external`, `_scheme`, `_method`, `_server`) passed to `url_for` will have special url building (`_method` is not supported now and will be ignored). For example:

```
url = app.url_for('post_handler', post_id=5, arg_one='one', _anchor='anchor')
# /posts/5?arg_one=one#anchor

url = app.url_for('post_handler', post_id=5, arg_one='one', _external=True)
# //server/posts/5?arg_one=one
# _external requires you to pass an argument _server or set SERVER_NAME in app.config_
↳if not url will be same as no _external

url = app.url_for('post_handler', post_id=5, arg_one='one', _scheme='http', _
↳external=True)
# http://server/posts/5?arg_one=one
# when specifying _scheme, _external must be True

# you can pass all special arguments at once
url = app.url_for('post_handler', post_id=5, arg_one=['one', 'two'], arg_two=2, _
↳anchor='anchor', _scheme='http', _external=True, _server='another_server:8888')
# http://another_server:8888/posts/5?arg_one=one&arg_one=two&arg_two=2#anchor
```

- All valid parameters must be passed to `url_for` to build a URL. If a parameter is not supplied, or if a parameter does not match the specified type, a `URLBuildError` will be raised.

## 2.7.5 WebSocket routes

Routes for the WebSocket protocol can be defined with the `@app.websocket` decorator:

```
@app.websocket('/feed')
async def feed(request, ws):
    while True:
        data = 'hello!'
        print('Sending: ' + data)
        await ws.send(data)
        data = await ws.recv()
        print('Received: ' + data)
```

Alternatively, the `app.add_websocket_route` method can be used instead of the decorator:

```
async def feed(request, ws):
    pass

app.add_websocket_route(my_websocket_handler, '/feed')
```

Handlers to a WebSocket route are invoked with the request as first argument, and a WebSocket protocol object as second argument. The protocol object has `send` and `recv` methods to send and receive data respectively.

WebSocket support requires the `websockets` package by Aymeric Augustin.

## 2.7.6 About `strict_slashes`

You can make routes strict to trailing slash or not, it's configurable.

```
# provide default strict_slashes value for all routes
app = Sanic('test_route_strict_slash', strict_slashes=True)

# you can also overwrite strict_slashes value for specific route
@app.get('/get', strict_slashes=False)
def handler(request):
    return text('OK')

# It also works for blueprints
bp = Blueprint('test_bp_strict_slash', strict_slashes=True)

@bp.get('/bp/get', strict_slashes=False)
def handler(request):
    return text('OK')

app.blueprint(bp)
```

The behavior of how the `strict_slashes` flag follows a defined hierarchy which decides if a specific route falls under the `strict_slashes` behavior.

```
|__ Route
  |__ Blueprint
    |__ Application
```

Above hierarchy defines how the `strict_slashes` flag will behave. The first non `None` value of the `strict_slashes` found in the above order will be applied to the route in question.

```

from sanic import Sanic, Blueprint
from sanic.response import text

app = Sanic("sample_strict_slashes", strict_slashes=True)

@app.get("/r1")
def r1(request):
    return text("strict_slashes is applicable from App level")

@app.get("/r2", strict_slashes=False)
def r2(request):
    return text("strict_slashes is not applicable due to False value set in route_
↳level")

bp = Blueprint("bp", strict_slashes=False)

@bp.get("/r3", strict_slashes=True)
def r3(request):
    return text("strict_slashes applicable from blueprint route level")

bp1 = Blueprint("bp1", strict_slashes=True)

@bp.get("/r4")
def r3(request):
    return text("strict_slashes applicable from blueprint level")

```

### 2.7.7 User defined route name

A custom route name can be used by passing a name argument while registering the route which will override the default route name generated using the handler.\_\_name\_\_ attribute.

```

app = Sanic('test_named_route')

@app.get('/get', name='get_handler')
def handler(request):
    return text('OK')

# then you need use `app.url_for('get_handler')`
# instead of # `app.url_for('handler')`

# It also works for blueprints
bp = Blueprint('test_named_bp')

@bp.get('/bp/get', name='get_handler')
def handler(request):
    return text('OK')

app.blueprint(bp)

# then you need use `app.url_for('test_named_bp.get_handler')`
# instead of `app.url_for('test_named_bp.handler')`

# different names can be used for same url with different methods

@app.get('/test', name='route_test')

```

(continues on next page)

(continued from previous page)

```

def handler(request):
    return text('OK')

@app.post('/test', name='route_post')
def handler2(request):
    return text('OK POST')

@app.put('/test', name='route_put')
def handler3(request):
    return text('OK PUT')

# below url are the same, you can use any of them
# '/test'
app.url_for('route_test')
# app.url_for('route_post')
# app.url_for('route_put')

# for same handler name with different methods
# you need specify the name (it's url_for issue)
@app.get('/get')
def handler(request):
    return text('OK')

@app.post('/post', name='post_handler')
def handler(request):
    return text('OK')

# then
# app.url_for('handler') == '/get'
# app.url_for('post_handler') == '/post'

```

## 2.7.8 Build URL for static files

Sanic supports using `url_for` method to build static file urls. In case if the static url is pointing to a directory, `filename` parameter to the `url_for` can be ignored. `q`

```

app = Sanic('test_static')
app.static('/static', './static')
app.static('/uploads', './uploads', name='uploads')
app.static('/the_best.png', '/home/ubuntu/test.png', name='best_png')

bp = Blueprint('bp', url_prefix='bp')
bp.static('/static', './static')
bp.static('/uploads', './uploads', name='uploads')
bp.static('/the_best.png', '/home/ubuntu/test.png', name='best_png')
app.blueprint(bp)

# then build the url
app.url_for('static', filename='file.txt') == '/static/file.txt'
app.url_for('static', name='static', filename='file.txt') == '/static/file.txt'
app.url_for('static', name='uploads', filename='file.txt') == '/uploads/file.txt'
app.url_for('static', name='best_png') == '/the_best.png'

# blueprint url building

```

(continues on next page)

(continued from previous page)

```
app.url_for('static', name='bp.static', filename='file.txt') == '/bp/static/file.txt'
app.url_for('static', name='bp.uploads', filename='file.txt') == '/bp/uploads/file.txt'
↪
app.url_for('static', name='bp.best_png') == '/bp/static/the_best.png'
```

## 2.8 Blueprints

Blueprints are objects that can be used for sub-routing within an application. Instead of adding routes to the application instance, blueprints define similar methods for adding routes, which are then registered with the application in a flexible and pluggable manner.

Blueprints are especially useful for larger applications, where your application logic can be broken down into several groups or areas of responsibility.

### 2.8.1 My First Blueprint

The following shows a very simple blueprint that registers a handler-function at the root / of your application.

Suppose you save this file as `my_blueprint.py`, which can be imported into your main application later.

```
from sanic.response import json
from sanic import Blueprint

bp = Blueprint('my_blueprint')

@bp.route('/')
async def bp_root(request):
    return json({'my': 'blueprint'})
```

### 2.8.2 Registering blueprints

Blueprints must be registered with the application.

```
from sanic import Sanic
from my_blueprint import bp

app = Sanic(__name__)
app.blueprint(bp)

app.run(host='0.0.0.0', port=8000, debug=True)
```

This will add the blueprint to the application and register any routes defined by that blueprint. In this example, the registered routes in the `app.router` will look like:

```
[Route(handler=<function bp_root at 0x7f908382f9d8>, methods=frozenset({'GET'}),
↪pattern=re.compile('^/$'), parameters=[], name='my_blueprint.bp_root', uri='/')]
```

### 2.8.3 Blueprint groups and nesting

Blueprints may also be registered as part of a list or tuple, where the registrar will recursively cycle through any sub-sequences of blueprints and register them accordingly. The `Blueprint.group` method is provided to simplify this

process, allowing a ‘mock’ backend directory structure mimicking what’s seen from the front end. Consider this (quite contrived) example:

```
api/
├── content/
│   ├── authors.py
│   ├── static.py
│   └── __init__.py
├── info.py
└── __init__.py
app.py
```

Initialization of this app’s blueprint hierarchy could go as follows:

```
# api/content/authors.py
from sanic import Blueprint

authors = Blueprint('content_authors', url_prefix='/authors')
```

```
# api/content/static.py
from sanic import Blueprint

static = Blueprint('content_static', url_prefix='/static')
```

```
# api/content/__init__.py
from sanic import Blueprint

from .static import static
from .authors import authors

content = Blueprint.group(static, authors, url_prefix='/content')
```

```
# api/info.py
from sanic import Blueprint

info = Blueprint('info', url_prefix='/info')
```

```
# api/__init__.py
from sanic import Blueprint

from .content import content
from .info import info

api = Blueprint.group(content, info, url_prefix='/api')
```

And registering these blueprints in `app.py` can now be done like so:

```
# app.py
from sanic import Sanic

from .api import api

app = Sanic(__name__)

app.blueprint(api)
```



## 2.8.4 Using Blueprints

Blueprints have almost the same functionality as an application instance.

### WebSocket routes

WebSocket handlers can be registered on a blueprint using the `@bp.websocket` decorator or `bp.add_websocket_route` method.

### Blueprint Middleware

Using blueprints allows you to also register middleware globally.

```
@bp.middleware
async def print_on_request(request):
    print("I am a spy")

@bp.middleware('request')
async def halt_request(request):
    return text('I halted the request')

@bp.middleware('response')
async def halt_response(request, response):
    return text('I halted the response')
```

### Blueprint Group Middleware

Using this middleware will ensure that you can apply a common middleware to all the blueprints that form the current blueprint group under consideration.

```
bp1 = Blueprint('bp1', url_prefix='/bp1')
bp2 = Blueprint('bp2', url_prefix='/bp2')

@bp1.middleware('request')
async def bp1_only_middleware(request):
    print('applied on Blueprint : bp1 Only')

@bp1.route('/')
async def bp1_route(request):
    return text('bp1')

@bp2.route('/<param>')
async def bp2_route(request, param):
    return text(param)

group = Blueprint.group(bp1, bp2)

@group.middleware('request')
async def group_middleware(request):
    print('common middleware applied for both bp1 and bp2')

# Register Blueprint group under the app
app.blueprint(group)
```

## Exceptions

Exceptions can be applied exclusively to blueprints globally.

```
@bp.exception(NotFound)
def ignore_404s(request, exception):
    return text("Yep, I totally found the page: {}".format(request.url))
```

## Static files

Static files can be served globally, under the blueprint prefix.

```
# suppose bp.name == 'bp'

bp.static('/web/path', '/folder/to/serve')
# also you can pass name parameter to it for url_for
bp.static('/web/path', '/folder/to/server', name='uploads')
app.url_for('static', name='bp.uploads', filename='file.txt') == '/bp/web/path/file.
↳txt'
```

## 2.8.5 Start and stop

Blueprints can run functions during the start and stop process of the server. If running in multiprocessor mode (more than 1 worker), these are triggered after the workers fork.

Available events are:

- `before_server_start`: Executed before the server begins to accept connections
- `after_server_start`: Executed after the server begins to accept connections
- `before_server_stop`: Executed before the server stops accepting connections
- `after_server_stop`: Executed after the server is stopped and all requests are complete

```
bp = Blueprint('my_blueprint')

@bp.listener('before_server_start')
async def setup_connection(app, loop):
    global database
    database = mysql.connect(host='127.0.0.1'...)

@bp.listener('after_server_stop')
async def close_connection(app, loop):
    await database.close()
```

## 2.8.6 Use-case: API versioning

Blueprints can be very useful for API versioning, where one blueprint may point at `/v1/<routes>`, and another pointing at `/v2/<routes>`.

When a blueprint is initialised, it can take an optional `version` argument, which will be prepended to all routes defined on the blueprint. This feature can be used to implement our API versioning scheme.

```
# blueprints.py
from sanic.response import text
from sanic import Blueprint

blueprint_v1 = Blueprint('v1', url_prefix='/api', version="v1")
blueprint_v2 = Blueprint('v2', url_prefix='/api', version="v2")

@blueprint_v1.route('/')
async def api_v1_root(request):
    return text('Welcome to version 1 of our documentation')

@blueprint_v2.route('/')
async def api_v2_root(request):
    return text('Welcome to version 2 of our documentation')
```

When we register our blueprints on the app, the routes `/v1/api` and `/v2/api` will now point to the individual blueprints, which allows the creation of *sub-sites* for each API version.

```
# main.py
from sanic import Sanic
from blueprints import blueprint_v1, blueprint_v2

app = Sanic(__name__)
app.blueprint(blueprint_v1)
app.blueprint(blueprint_v2)

app.run(host='0.0.0.0', port=8000, debug=True)
```

## 2.8.7 URL Building with `url_for`

If you wish to generate a URL for a route inside of a blueprint, remember that the endpoint name takes the format `<blueprint_name>.<handler_name>`. For example:

```
@blueprint_v1.route('/')
async def root(request):
    url = request.app.url_for('v1.post_handler', post_id=5) # --> '/v1/api/post/5'
    return redirect(url)

@blueprint_v1.route('/post/<post_id>')
async def post_handler(request, post_id):
    return text('Post {} in Blueprint V1'.format(post_id))
```

## 2.9 Static Files

Static files and directories, such as an image file, are served by Sanic when registered with the `app.static()` method. The method takes an endpoint URL and a filename. The file specified will then be accessible via the given endpoint.

```
from sanic import Sanic
from sanic.blueprints import Blueprint

app = Sanic(__name__)
```

(continues on next page)

(continued from previous page)

```
# Serves files from the static folder to the URL /static
app.static('/static', './static')
# use url_for to build the url, name defaults to 'static' and can be ignored
app.url_for('static', filename='file.txt') == '/static/file.txt'
app.url_for('static', name='static', filename='file.txt') == '/static/file.txt'

# Serves the file /home/ubuntu/test.png when the URL /the_best.png
# is requested
app.static('/the_best.png', '/home/ubuntu/test.png', name='best_png')

# you can use url_for to build the static file url
# you can ignore name and filename parameters if you don't define it
app.url_for('static', name='best_png') == '/the_best.png'
app.url_for('static', name='best_png', filename='any') == '/the_best.png'

# you need define the name for other static files
app.static('/another.png', '/home/ubuntu/another.png', name='another')
app.url_for('static', name='another') == '/another.png'
app.url_for('static', name='another', filename='any') == '/another.png'

# also, you can use static for blueprint
bp = Blueprint('bp', url_prefix='/bp')
bp.static('/static', './static')

# specify a different content_type for your files
# such as adding 'charset'
app.static('/', '/public/index.html', content_type="text/html; charset=utf-8")

# servers the file directly
bp.static('/the_best.png', '/home/ubuntu/test.png', name='best_png')
app.blueprint(bp)

app.url_for('static', name='bp.static', filename='file.txt') == '/bp/static/file.txt'
app.url_for('static', name='bp.best_png') == '/bp/test_best.png'

app.run(host="0.0.0.0", port=8000)
```

**Note:** Sanic does not provide directory index when you serve a static directory.

## 2.9.1 Virtual Host

The `app.static()` method also support **virtual host**. You can serve your static files with specific **virtual host** with `host` argument. For example:

```
from sanic import Sanic

app = Sanic(__name__)

app.static('/static', './static')
app.static('/example_static', './example_static', host='www.example.com')
```

## 2.9.2 Streaming Large File

In some cases, you might server large file(ex: videos, images, etc.) with Sanic. You can choose to use **streaming file** rather than download directly.

Here is an example:

```
from sanic import Sanic

app = Sanic(__name__)

app.static('/large_video.mp4', '/home/ubuntu/large_video.mp4', stream_large_
↳files=True)
```

When `stream_large_files` is `True`, Sanic will use `file_stream()` instead of `file()` to serve static files. This will use **1KB** as the default chunk size. And, if needed, you can also use a custom chunk size. For example:

```
from sanic import Sanic

app = Sanic(__name__)

chunk_size = 1024 * 1024 * 8 # Set chunk size to 8KB
app.static('/large_video.mp4', '/home/ubuntu/large_video.mp4', stream_large_
↳files=chunk_size)
```

## 2.10 Versioning

You can pass the `version` keyword to the route decorators, or to a blueprint initializer. It will result in the `v{version}` url prefix where `{version}` is the version number.

### 2.10.1 Per route

You can pass a version number to the routes directly.

```
from sanic import response

@app.route('/text', version=1)
def handle_request(request):
    return response.text('Hello world! Version 1')

@app.route('/text', version=2)
def handle_request(request):
    return response.text('Hello world! Version 2')

app.run(port=80)
```

Then with curl:

```
curl localhost/v1/text
curl localhost/v2/text
```

## 2.10.2 Global blueprint version

You can also pass a version number to the blueprint, which will apply to all routes.

```
from sanic import response
from sanic.blueprints import Blueprint

bp = Blueprint('test', version=1)

@bp.route('/html')
def handle_request(request):
    return response.html('<p>Hello world!</p>')
```

Then with curl:

```
curl localhost/v1/html
```

## 2.11 Exceptions

Exceptions can be thrown from within request handlers and will automatically be handled by Sanic. Exceptions take a message as their first argument, and can also take a status code to be passed back in the HTTP response.

### 2.11.1 Throwing an exception

To throw an exception, simply raise the relevant exception from the `sanic.exceptions` module.

```
from sanic.exceptions import ServerError

@app.route('/killme')
async def i_am_ready_to_die(request):
    raise ServerError("Something bad happened", status_code=500)
```

You can also use the `abort` function with the appropriate status code:

```
from sanic.exceptions import abort
from sanic.response import text

@app.route('/youshallnotpass')
async def no_no(request):
    abort(401)
    # this won't happen
    text("OK")
```

### 2.11.2 Handling exceptions

To override Sanic's default handling of an exception, the `@app.exception` decorator is used. The decorator expects a list of exceptions to handle as arguments. You can pass `SanicException` to catch them all! The decorated exception handler function must take a `Request` and `Exception` object as arguments.

```
from sanic.response import text
from sanic.exceptions import NotFound
```

(continues on next page)

(continued from previous page)

```
@app.exception(NotFound)
async def ignore_404s(request, exception):
    return text("Yep, I totally found the page: {}".format(request.url))
```

You can also add an exception handler as such:

```
from sanic import Sanic

async def server_error_handler(request, exception):
    return text("Oops, server error", status=500)

app = Sanic()
app.error_handler.add(Exception, server_error_handler)
```

In some cases, you might want to add some more error handling functionality to what is provided by default. In that case, you can subclass Sanic's default error handler as such:

```
from sanic import Sanic
from sanic.handlers import ErrorHandler

class CustomErrorHandler(ErrorHandler):
    def default(self, request, exception):
        ''' handles errors that have no error handlers assigned '''
        # You custom error handling logic...
        return super().default(request, exception)

app = Sanic()
app.error_handler = CustomErrorHandler()
```

### 2.11.3 Useful exceptions

Some of the most useful exceptions are presented below:

- `NotFound`: called when a suitable route for the request isn't found.
- `ServerError`: called when something goes wrong inside the server. This usually occurs if there is an exception raised in user code.

See the `sanic.exceptions` module for the full list of exceptions to throw.

## 2.12 Middleware And Listeners

Middleware are functions which are executed before or after requests to the server. They can be used to modify the *request to* or *response from* user-defined handler functions.

Additionally, Sanic provides listeners which allow you to run code at various points of your application's lifecycle.

### 2.12.1 Middleware

There are two types of middleware: request and response. Both are declared using the `@app.middleware` decorator, with the decorator's parameter being a string representing its type: 'request' or 'response'.

- Request middleware receives only the `request` as argument.

- Response middleware receives both the request and response.

The simplest middleware doesn't modify the request or response at all:

```
@app.middleware('request')
async def print_on_request(request):
    print("I print when a request is received by the server")

@app.middleware('response')
async def print_on_response(request, response):
    print("I print when a response is returned by the server")
```

### 2.12.2 Modifying the request or response

Middleware can modify the request or response parameter it is given, *as long as it does not return it*. The following example shows a practical use-case for this.

```
app = Sanic(__name__)

@app.middleware('request')
async def add_key(request):
    # Arbitrary data may be stored in request context:
    request.ctx.foo = 'bar'

@app.middleware('response')
async def custom_banner(request, response):
    response.headers["Server"] = "Fake-Server"

@app.middleware('response')
async def prevent_xss(request, response):
    response.headers["x-xss-protection"] = "1; mode=block"

@app.get("/")
async def index(request):
    return sanic.response.text(request.ctx.foo)

app.run(host="0.0.0.0", port=8000)
```

The three middlewares are executed in order:

1. The first request middleware **add\_key** adds a new key `foo` into request context.
2. Request is routed to handler **index**, which gets the key from context and returns a text response.
3. The first response middleware **custom\_banner** changes the HTTP response header `Server` to say *Fake-Server*
4. The second response middleware **prevent\_xss** adds the HTTP header for preventing Cross-Site-Scripting (XSS) attacks.



### 2.12.3 Responding early

If middleware returns a `HTTPResponse` object, the request will stop processing and the response will be returned. If this occurs to a request before the relevant user route handler is reached, the handler will never be called. Returning a response will also prevent any further middleware from running.

```
@app.middleware('request')
async def halt_request(request):
    return text('I halted the request')

@app.middleware('response')
async def halt_response(request, response):
    return text('I halted the response')
```

### 2.12.4 Custom context

Arbitrary data may be stored in `request.ctx`. A typical use case would be to store the user object acquired from database in an authentication middleware. Keys added are accessible to all later middleware as well as the handler over the duration of the request.

Custom context is reserved for applications and extensions. Sanic itself makes no use of it.

### 2.12.5 Listeners

If you want to execute startup/teardown code as your server starts or closes, you can use the following listeners:

- `before_server_start`
- `after_server_start`
- `before_server_stop`
- `after_server_stop`

These listeners are implemented as decorators on functions which accept the app object as well as the asyncio loop.

For example:

```
@app.listener('before_server_start')
async def setup_db(app, loop):
    app.db = await db_setup()

@app.listener('after_server_start')
async def notify_server_started(app, loop):
    print('Server successfully started!')

@app.listener('before_server_stop')
async def notify_server_stopping(app, loop):
    print('Server shutting down!')

@app.listener('after_server_stop')
async def close_db(app, loop):
    await app.db.close()
```

It's also possible to register a listener using the `register_listener` method. This may be useful if you define your listeners in another module besides the one you instantiate your app in.

```
app = Sanic()

async def setup_db(app, loop):
    app.db = await db_setup()

app.register_listener(setup_db, 'before_server_start')
```

If you want to schedule a background task to run after the loop has started, Sanic provides the `add_task` method to easily do so.

```
async def notify_server_started_after_five_seconds():
    await asyncio.sleep(5)
    print('Server successfully started!')

app.add_task(notify_server_started_after_five_seconds())
```

Sanic will attempt to automatically inject the `app`, passing it as an argument to the task:

```
async def notify_server_started_after_five_seconds(app):
    await asyncio.sleep(5)
    print(app.name)

app.add_task(notify_server_started_after_five_seconds)
```

Or you can pass the `app` explicitly for the same effect:

```
async def notify_server_started_after_five_seconds(app):
    await asyncio.sleep(5)
    print(app.name)

app.add_task(notify_server_started_after_five_seconds(app))
```

## 2.13 WebSocket

Sanic provides an easy to use abstraction on top of *websockets*. Sanic Supports websocket versions 7 and 8.

To setup a WebSocket:

```
from sanic import Sanic
from sanic.response import json
from sanic.websocket import WebSocketProtocol

app = Sanic()

@app.websocket('/feed')
async def feed(request, ws):
    while True:
        data = 'hello!'
        print('Sending: ' + data)
        await ws.send(data)
        data = await ws.recv()
        print('Received: ' + data)
```

(continues on next page)

(continued from previous page)

```
if __name__ == "__main__":
    app.run(host="0.0.0.0", port=8000, protocol=WebSocketProtocol)
```

Alternatively, the `app.add_websocket_route` method can be used instead of the decorator:

```
async def feed(request, ws):
    pass

app.add_websocket_route(feed, '/feed')
```

Handlers for a WebSocket route is invoked with the request as first argument, and a WebSocket protocol object as second argument. The protocol object has `send` and `recv` methods to send and receive data respectively.

You could setup your own WebSocket configuration through `app.config`, like

```
app.config.WEBSOCKET_MAX_SIZE = 2 ** 20
app.config.WEBSOCKET_MAX_QUEUE = 32
app.config.WEBSOCKET_READ_LIMIT = 2 ** 16
app.config.WEBSOCKET_WRITE_LIMIT = 2 ** 16
```

Find more in [Configuration section](#).

## 2.14 Handler Decorators

Since Sanic handlers are simple Python functions, you can apply decorators to them in a similar manner to Flask. A typical use case is when you want some code to run before a handler's code is executed.

### 2.14.1 Authorization Decorator

Let's say you want to check that a user is authorized to access a particular endpoint. You can create a decorator that wraps a handler function, checks a request if the client is authorized to access a resource, and sends the appropriate response.

```
from functools import wraps
from sanic.response import json

def authorized():
    def decorator(f):
        @wraps(f)
        async def decorated_function(request, *args, **kwargs):
            # run some method that checks the request
            # for the client's authorization status
            is_authorized = check_request_for_authorization_status(request)

            if is_authorized:
                # the user is authorized.
                # run the handler method and return the response
                response = await f(request, *args, **kwargs)
                return response
            else:
                # the user is not authorized.
                return json({'status': 'not_authorized'}, 403)
        return decorated_function
```

(continues on next page)

(continued from previous page)

```
    return decorator

@app.route("/")
@authorized()
async def test(request):
    return json({'status': 'authorized'})
```

## 2.15 Streaming

### 2.15.1 Request Streaming

Sanic allows you to get request data by stream, as below. When the request ends, `await request.stream.read()` returns `None`. Only `post`, `put` and `patch` decorator have `stream` argument.

```
from sanic import Sanic
from sanic.views import CompositionView
from sanic.views import HTTPMethodView
from sanic.views import stream as stream_decorator
from sanic.blueprints import Blueprint
from sanic.response import stream, text

bp = Blueprint('blueprint_request_stream')
app = Sanic('request_stream')

class SimpleView(HTTPMethodView):

    @stream_decorator
    async def post(self, request):
        result = ''
        while True:
            body = await request.stream.read()
            if body is None:
                break
            result += body.decode('utf-8')
        return text(result)

@app.post('/stream', stream=True)
async def handler(request):
    async def streaming(response):
        while True:
            body = await request.stream.read()
            if body is None:
                break
            body = body.decode('utf-8').replace('l', 'A')
            await response.write(body)
    return stream(streaming)

@bp.put('/bp_stream', stream=True)
async def bp_put_handler(request):
```

(continues on next page)

(continued from previous page)

```

result = ''
while True:
    body = await request.stream.read()
    if body is None:
        break
    result += body.decode('utf-8').replace('1', 'A')
return text(result)

# You can also use `bp.add_route()` with stream argument
async def bp_post_handler(request):
    result = ''
    while True:
        body = await request.stream.read()
        if body is None:
            break
        result += body.decode('utf-8').replace('1', 'A')
    return text(result)

bp.add_route(bp_post_handler, '/bp_stream', methods=['POST'], stream=True)

async def post_handler(request):
    result = ''
    while True:
        body = await request.stream.read()
        if body is None:
            break
        result += body.decode('utf-8')
    return text(result)

app.blueprint(bp)
app.add_route(SimpleView.as_view(), '/method_view')
view = CompositionView()
view.add(['POST'], post_handler, stream=True)
app.add_route(view, '/composition_view')

if __name__ == '__main__':
    app.run(host='127.0.0.1', port=8000)

```

## 2.15.2 Response Streaming

Sanic allows you to stream content to the client with the `stream` method. This method accepts a coroutine callback which is passed a `StreamingHTTPResponse` object that is written to. A simple example is like follows:

```

from sanic import Sanic
from sanic.response import stream

app = Sanic(__name__)

@app.route("/")
async def test(request):
    async def sample_streaming_fn(response):
        await response.write('foo,')

```

(continues on next page)

(continued from previous page)

```
await response.write('bar')

return stream(sample_streaming_fn, content_type='text/csv')
```

This is useful in situations where you want to stream content to the client that originates in an external service, like a database. For example, you can stream database records to the client with the asynchronous cursor that `asyncpg` provides:

```
@app.route("/")
async def index(request):
    async def stream_from_db(response):
        conn = await asyncpg.connect(database='test')
        async with conn.transaction():
            async for record in conn.cursor('SELECT generate_series(0, 10)'):
                await response.write(record[0])

    return stream(stream_from_db)
```

If a client supports HTTP/1.1, Sanic will use `chunked transfer encoding`; you can explicitly enable or disable it using `chunked` option of the `stream` function.

### 2.15.3 File Streaming

Sanic provides `sanic.response.file_stream` function that is useful when you want to send a large file. It returns a `StreamingHTTPResponse` object and will use `chunked transfer encoding` by default; for this reason Sanic doesn't add `Content-Length` HTTP header in the response. If you want to use this header, you can disable `chunked transfer encoding` and add it manually:

```
from aiofiles import os as async_os
from sanic.response import file_stream

@app.route("/")
async def index(request):
    file_path = "/srv/www/whatever.png"

    file_stat = await async_os.stat(file_path)
    headers = {"Content-Length": str(file_stat.st_size)}

    return await file_stream(
        file_path,
        headers=headers,
        chunked=False,
    )
```

## 2.16 Class-Based Views

Class-based views are simply classes which implement response behaviour to requests. They provide a way to compartmentalise handling of different HTTP request types at the same endpoint. Rather than defining and decorating three different handler functions, one for each of an endpoint's supported request type, the endpoint can be assigned a class-based view.

### 2.16.1 Defining views

A class-based view should subclass `HTTPMethodView`. You can then implement class methods for every HTTP request type you want to support. If a request is received that has no defined method, a `405: Method not allowed` response will be generated.

To register a class-based view on an endpoint, the `app.add_route` method is used. The first argument should be the defined class with the method `as_view` invoked, and the second should be the URL endpoint.

The available methods are `get`, `post`, `put`, `patch`, and `delete`. A class using all these methods would look like the following.

```
from sanic import Sanic
from sanic.views import HTTPMethodView
from sanic.response import text

app = Sanic('some_name')

class SimpleView(HTTPMethodView):

    def get(self, request):
        return text('I am get method')

    def post(self, request):
        return text('I am post method')

    def put(self, request):
        return text('I am put method')

    def patch(self, request):
        return text('I am patch method')

    def delete(self, request):
        return text('I am delete method')

app.add_route(SimpleView.as_view(), '/')
```

You can also use `async` syntax.

```
from sanic import Sanic
from sanic.views import HTTPMethodView
from sanic.response import text

app = Sanic('some_name')

class SimpleAsyncView(HTTPMethodView):

    async def get(self, request):
        return text('I am async get method')

app.add_route(SimpleAsyncView.as_view(), '/')
```

### 2.16.2 URL parameters

If you need any URL parameters, as discussed in the routing guide, include them in the method definition.

```
class NameView(HTTPMethodView):  
  
    def get(self, request, name):  
        return text('Hello {}'.format(name))  
  
app.add_route(NameView.as_view(), '<name>')
```

### 2.16.3 Decorators

If you want to add any decorators to the class, you can set the `decorators` class variable. These will be applied to the class when `as_view` is called.

```
class ViewWithDecorator(HTTPMethodView):  
    decorators = [some_decorator_here]  
  
    def get(self, request, name):  
        return text('Hello I have a decorator')  
  
    def post(self, request, name):  
        return text("Hello I also have a decorator")  
  
app.add_route(ViewWithDecorator.as_view(), '/url')
```

But if you just want to decorate some functions and not all functions, you can do as follows:

```
class ViewWithSomeDecorator(HTTPMethodView):  
  
    @staticmethod  
    @some_decorator_here  
    def get(request, name):  
        return text("Hello I have a decorator")  
  
    def post(self, request, name):  
        return text("Hello I don't have any decorators")
```

### 2.16.4 URL Building

If you wish to build a URL for an `HTTPMethodView`, remember that the class name will be the endpoint that you will pass into `url_for`. For example:

```
@app.route('/')  
def index(request):  
    url = app.url_for('SpecialClassView')  
    return redirect(url)  
  
class SpecialClassView(HTTPMethodView):  
    def get(self, request):  
        return text('Hello from the Special Class View!')  
  
app.add_route(SpecialClassView.as_view(), '/special_class_view')
```



## 2.16.5 Using CompositionView

As an alternative to the `HTTPMethodView`, you can use `CompositionView` to move handler functions outside of the view class.

Handler functions for each supported HTTP method are defined elsewhere in the source, and then added to the view using the `CompositionView.add` method. The first parameter is a list of HTTP methods to handle (e.g. `['GET', 'POST']`), and the second is the handler function. The following example shows `CompositionView` usage with both an external handler function and an inline lambda:

```
from sanic import Sanic
from sanic.views import CompositionView
from sanic.response import text

app = Sanic(__name__)

def get_handler(request):
    return text('I am a get method')

view = CompositionView()
view.add(['GET'], get_handler)
view.add(['POST', 'PUT'], lambda request: text('I am a post/put method'))

# Use the new view to handle requests to the base URL
app.add_route(view, '/')
```

Note: currently you cannot build a URL for a `CompositionView` using `url_for`.

## 2.17 Custom Protocols

---

**Note:** This is advanced usage, and most readers will not need such functionality.

---

You can change the behavior of Sanic's protocol by specifying a custom protocol, which should be a subclass of `asyncio.protocol`. This protocol can then be passed as the keyword argument `protocol` to the `sanic.run` method.

The constructor of the custom protocol class receives the following keyword arguments from Sanic.

- `loop`: an `asyncio`-compatible event loop.
- `connections`: a set to store protocol objects. When Sanic receives `SIGINT` or `SIGTERM`, it executes `protocol.close_if_idle` for all protocol objects stored in this set.
- `signal`: a `sanic.server.Signal` object with the `stopped` attribute. When Sanic receives `SIGINT` or `SIGTERM`, `signal.stopped` is assigned `True`.
- `request_handler`: a coroutine that takes a `sanic.request.Request` object and a response call-back as arguments.
- `error_handler`: a `sanic.exceptions.Handler` which is called when exceptions are raised.
- `request_timeout`: the number of seconds before a request times out.
- `request_max_size`: an integer specifying the maximum size of a request, in bytes.

## 2.17.1 Example

An error occurs in the default protocol if a handler function does not return an `HTTPResponse` object.

By overriding the `write_response` protocol method, if a handler returns a string it will be converted to an `HTTPResponse` object.

```
from sanic import Sanic
from sanic.server import HttpProtocol
from sanic.response import text

app = Sanic(__name__)

class CustomHttpProtocol(HttpProtocol):

    def __init__(self, *, loop, request_handler, error_handler,
                 signal, connections, request_timeout, request_max_size):
        super().__init__(
            loop=loop, request_handler=request_handler,
            error_handler=error_handler, signal=signal,
            connections=connections, request_timeout=request_timeout,
            request_max_size=request_max_size)

    def write_response(self, response):
        if isinstance(response, str):
            response = text(response)
        self.transport.write(
            response.output(self.request.version)
        )
        self.transport.close()

@app.route('/')
async def string(request):
    return 'string'

@app.route('/1')
async def response(request):
    return text('response')

app.run(host='0.0.0.0', port=8000, protocol=CustomHttpProtocol)
```

## 2.18 Sockets

Sanic can use the python `socket` module to accommodate non IPv4 sockets.

IPv6 example:

```
from sanic import Sanic
from sanic.response import json
import socket

sock = socket.socket(socket.AF_INET6, socket.SOCK_STREAM)
sock.bind((':::', 7777))
```

(continues on next page)

(continued from previous page)

```

app = Sanic()

@app.route("/")
async def test(request):
    return json({"hello": "world"})

if __name__ == "__main__":
    app.run(sock=sock)

```

to test IPv6 `curl -g -6 "http://[::1]:7777/"`

UNIX socket example:

```

import signal
import sys
import socket
import os
from sanic import Sanic
from sanic.response import json

server_socket = '/tmp/sanic.sock'

sock = socket.socket(socket.AF_UNIX, socket.SOCK_STREAM)
sock.bind(server_socket)

app = Sanic()

@app.route("/")
async def test(request):
    return json({"hello": "world"})

def signal_handler(sig, frame):
    print('Exiting')
    os.unlink(server_socket)
    sys.exit(0)

if __name__ == "__main__":
    app.run(sock=sock)

```

to test UNIX: `curl -v --unix-socket /tmp/sanic.sock http://localhost/hello`

## 2.19 SSL Example

Optionally pass in an SSLContext:

```

import ssl
context = ssl.create_default_context(purpose=ssl.Purpose.CLIENT_AUTH)
context.load_cert_chain("/path/to/cert", keyfile="/path/to/keyfile")

```

(continues on next page)

(continued from previous page)

```
app.run(host="0.0.0.0", port=8443, ssl=context)
```

You can also pass in the locations of a certificate and key as a dictionary:

```
ssl = {'cert': "/path/to/cert", 'key': "/path/to/keyfile"}
app.run(host="0.0.0.0", port=8443, ssl=ssl)
```

## 2.20 Debug Mode

When enabling Sanic's debug mode, Sanic will provide a more verbose logging output and by default will enable the Auto Reload feature.

**Warning:** Sanic's debug mode will slow down the server's performance and is therefore advised to enable it only in development environments.

### 2.20.1 Setting the debug mode

By setting the debug mode a more verbose output from Sanic will be outputted and the Automatic Reloader will be activated.

```
from sanic import Sanic
from sanic.response import json

app = Sanic()

@app.route('/')
async def hello_world(request):
    return json({"hello": "world"})

if __name__ == '__main__':
    app.run(host="0.0.0.0", port=8000, debug=True)
```

### 2.20.2 Manually setting auto reload

Sanic offers a way to enable or disable the Automatic Reloader manually, the `auto_reload` argument will activate or deactivate the Automatic Reloader.

```
from sanic import Sanic
from sanic.response import json

app = Sanic()

@app.route('/')
async def hello_world(request):
    return json({"hello": "world"})

if __name__ == '__main__':
    app.run(host="0.0.0.0", port=8000, auto_reload=True)
```

## 2.21 Testing

Sanic endpoints can be tested locally using the `test_client` object, which depends on the additional `requests-async` library, which implements an API that mirrors the `requests` library.

The `test_client` exposes `get`, `post`, `put`, `delete`, `patch`, `head` and `options` methods for you to run against your application. A simple example (using `pytest`) is like follows:

```
# Import the Sanic app, usually created with Sanic(__name__)
from external_server import app

def test_index_returns_200():
    request, response = app.test_client.get('/')
    assert response.status == 200

def test_index_put_not_allowed():
    request, response = app.test_client.put('/')
    assert response.status == 405
```

Internally, each time you call one of the `test_client` methods, the Sanic app is run at `127.0.0.1:42101` and your test request is executed against your application, using `requests-async`.

The `test_client` methods accept the following arguments and keyword arguments:

- `uri` (*default*  `'/'`) A string representing the URI to test.
- `gather_request` (*default*  `True`) A boolean which determines whether the original request will be returned by the function. If set to  `True`, the return value is a tuple of ( `request`,  `response`), if  `False` only the response is returned.
- `server_kwargs` \*(*default*  `{}`) a dict of additional arguments to pass into  `app.run` before the test request is run.
- `debug` (*default*  `False`) A boolean which determines whether to run the server in debug mode.

The function further takes the `*request_args` and `**request_kwargs`, which are passed directly to the request.

For example, to supply data to a GET request, you would do the following:

```
def test_get_request_includes_data():
    params = {'key1': 'value1', 'key2': 'value2'}
    request, response = app.test_client.get('/', params=params)
    assert request.args.get('key1') == 'value1'
```

And to supply data to a JSON POST request:

```
def test_post_json_request_includes_data():
    data = {'key1': 'value1', 'key2': 'value2'}
    request, response = app.test_client.post('/', data=json.dumps(data))
    assert request.json.get('key1') == 'value1'
```

More information about the available arguments to `requests-async` can be found in the [documentation for requests](#).

### 2.21.1 Using a random port

If you need to test using a free unprivileged port chosen by the kernel instead of the default with `SanicTestClient`, you can do so by specifying `port=None`. On most systems the port will be in the range 1024 to 65535.

```
# Import the Sanic app, usually created with Sanic(__name__)
from external_server import app
from sanic.testing import SanicTestClient

def test_index_returns_200():
    request, response = SanicTestClient(app, port=None).get('/')
    assert response.status == 200
```

## 2.21.2 pytest-sanic

pytest-sanic is a pytest plugin, it helps you to test your code asynchronously. Just write tests like,

```
async def test_sanic_db_find_by_id(app):
    """
    Let's assume that, in db we have,
    {
        "id": "123",
        "name": "Kobe Bryant",
        "team": "Lakers",
    }
    """
    doc = await app.db["players"].find_by_id("123")
    assert doc.name == "Kobe Bryant"
    assert doc.team == "Lakers"
```

pytest-sanic also provides some useful fixtures, like `loop`, `unused_port`, `test_server`, `test_client`.

```
@pytest.yield_fixture
def app():
    app = Sanic("test_sanic_app")

    @app.route("/test_get", methods=['GET'])
    async def test_get(request):
        return response.json({"GET": True})

    @app.route("/test_post", methods=['POST'])
    async def test_post(request):
        return response.json({"POST": True})

    yield app

@pytest.fixture
def test_cli(loop, app, test_client):
    return loop.run_until_complete(test_client(app, protocol=WebSocketProtocol))

#####
# Tests #
#####

async def test_fixture_test_client_get(test_cli):
    """
    GET request
    """
    resp = await test_cli.get('/test_get')
```

(continues on next page)

(continued from previous page)

```
assert resp.status == 200
resp_json = await resp.json()
assert resp_json == {"GET": True}

async def test_fixture_test_client_post(test_cli):
    """
    POST request
    """
    resp = await test_cli.post('/test_post')
    assert resp.status == 200
    resp_json = await resp.json()
    assert resp_json == {"POST": True}
```

## 2.22 Deploying

Deploying Sanic is very simple using one of three options: the inbuilt webserver, an [ASGI webserver](#), or [gunicorn](#). It is also very common to place Sanic behind a reverse proxy, like [nginx](#).

### 2.22.1 Running via Sanic webserver

After defining an instance of `sanic.Sanic`, we can call the `run` method with the following keyword arguments:

- `host` (*default "127.0.0.1"*): Address to host the server on.
- `port` (*default 8000*): Port to host the server on.
- `debug` (*default False*): Enables debug output (slows server).
- `ssl` (*default None*): `SSLContext` for SSL encryption of worker(s).
- `sock` (*default None*): Socket for the server to accept connections from.
- `workers` (*default 1*): Number of worker processes to spawn.
- `loop` (*default None*): An `asyncio`-compatible event loop. If none is specified, Sanic creates its own event loop.
- `protocol` (*default `HttpProtocol`*): Subclass of `asyncio.protocol`.
- `access_log` (*default True*): Enables log on handling requests (significantly slows server).

```
app.run(host='0.0.0.0', port=1337, access_log=False)
```

In the above example, we decided to turn off the access log in order to increase performance.

### Workers

By default, Sanic listens in the main process using only one CPU core. To crank up the juice, just specify the number of workers in the `run` arguments.

```
app.run(host='0.0.0.0', port=1337, workers=4)
```

Sanic will automatically spin up multiple processes and route traffic between them. We recommend as many workers as you have available cores.

## Running via command

If you like using command line arguments, you can launch a Sanic webserver by executing the module. For example, if you initialized Sanic as `app` in a file named `server.py`, you could run the server like so:

```
python -m sanic server.app --host=0.0.0.0 --port=1337 --workers=4
```

With this way of running sanic, it is not necessary to invoke `app.run` in your Python file. If you do, make sure you wrap it so that it only executes when directly run by the interpreter.

```
if __name__ == '__main__':
    app.run(host='0.0.0.0', port=1337, workers=4)
```

### 2.22.2 Running via ASGI

Sanic is also ASGI-compliant. This means you can use your preferred ASGI webserver to run Sanic. The three main implementations of ASGI are [Daphne](#), [Uvicorn](#), and [Hypercorn](#).

Follow their documentation for the proper way to run them, but it should look something like:

```
daphne myapp:app
uvicorn myapp:app
hypercorn myapp:app
```

A couple things to note when using ASGI:

1. When using the Sanic webserver, websockets will run using the `websockets` package. In ASGI mode, there is no need for this package since websockets are managed in the ASGI server.
2. The ASGI [lifespan protocol](#) supports only two server events: startup and shutdown. Sanic has four: before startup, after startup, before shutdown, and after shutdown. Therefore, in ASGI mode, the startup and shutdown events will run consecutively and not actually around the server process beginning and ending (since that is now controlled by the ASGI server). Therefore, it is best to use `after_server_start` and `before_server_stop`.
3. ASGI mode is still in “beta” as of Sanic v19.6.

### 2.22.3 Running via Gunicorn

[Gunicorn](#) ‘Green Unicorn’ is a WSGI HTTP Server for UNIX. It’s a pre-fork worker model ported from Ruby’s Unicorn project.

In order to run Sanic application with Gunicorn, you need to use the special `sanic.worker.GunicornWorker` for Gunicorn `worker-class` argument:

```
gunicorn myapp:app --bind 0.0.0.0:1337 --worker-class sanic.worker.GunicornWorker
```

If your application suffers from memory leaks, you can configure Gunicorn to gracefully restart a worker after it has processed a given number of requests. This can be a convenient way to help limit the effects of the memory leak.

See the [Gunicorn Docs](#) for more information.

### 2.22.4 Other deployment considerations



## Running behind a reverse proxy

Sanic can be used with a reverse proxy (e.g. nginx). There's a simple example of nginx configuration:

```
server {
    listen 80;
    server_name example.org;

    location / {
        proxy_pass http://127.0.0.1:8000;
        proxy_set_header Host $host;
        proxy_set_header X-Real-IP $remote_addr;
        proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
    }
}
```

If you want to get real client ip, you should configure X-Real-IP and X-Forwarded-For HTTP headers and set `app.config.PROXIES_COUNT` to 1; see the [configuration page](#) for more information.

## Disable debug logging for performance

To improve the performance add `debug=False` and `access_log=False` in the run arguments.

```
app.run(host='0.0.0.0', port=1337, workers=4, debug=False, access_log=False)
```

Running via Gunicorn you can set Environment variable `SANIC_ACCESS_LOG="False"`

```
env SANIC_ACCESS_LOG="False" gunicorn myapp:app --bind 0.0.0.0:1337 --worker-class_
↳sanic.worker.GunicornWorker --log-level warning
```

Or you can rewrite app config directly

```
app.config.ACCESS_LOG = False
```

## Asynchronous support and sharing the loop

This is suitable if you *need* to share the Sanic process with other applications, in particular the `loop`. However, be advised that this method does not support using multiple processes, and is not the preferred way to run the app in general.

Here is an incomplete example (please see `run_async.py` in examples for something more practical):

```
server = app.create_server(host="0.0.0.0", port=8000, return_asyncio_server=True)
loop = asyncio.get_event_loop()
task = asyncio.ensure_future(server)
loop.run_forever()
```

Caveat: using this method, calling `app.create_server()` will trigger “before\_server\_start” server events, but not “after\_server\_start”, “before\_server\_stop”, or “after\_server\_stop” server events.

For more advanced use-cases, you can trigger these events using the `AsyncioServer` object, returned by awaiting the server task.

Here is an incomplete example (please see `run_async_advanced.py` in examples for something more complete):

```
serv_coro = app.create_server(host="0.0.0.0", port=8000, return_asyncio_server=True)
loop = asyncio.get_event_loop()
serv_task = asyncio.ensure_future(serv_coro, loop=loop)
server = loop.run_until_complete(serv_task)
server.after_start()
try:
    loop.run_forever()
except KeyboardInterrupt as e:
    loop.stop()
finally:
    server.before_stop()

    # Wait for server to close
    close_task = server.close()
    loop.run_until_complete(close_task)

    # Complete all tasks on the loop
    for connection in server.connections:
        connection.close_if_idle()
    server.after_stop()
```

## 2.23 Extensions

Moved to the [awesome-sanic](#) list.

## 2.24 Examples

This section of the documentation is a simple collection of example code that can help you get a quick start on your application development. Most of these examples are categorized and provide you with a link to the working code example in the [Sanic Repository](#)

### 2.24.1 Basic Examples

This section of the examples are a collection of code that provide a simple use case example of the sanic application.

#### Simple Apps

A simple sanic application with a single async method with text and json type response.

```
from sanic import Sanic
from sanic import response as res

app = Sanic(__name__)

@app.route("/")
async def test(req):
    return res.text("I\'m a teapot", status=418)
```

(continues on next page)

(continued from previous page)

```
if __name__ == '__main__':
    app.run(host="0.0.0.0", port=8000)
```

```
from sanic import Sanic
from sanic import response

app = Sanic(__name__)

@app.route("/")
async def test(request):
    return response.json({"test": True})

if __name__ == '__main__':
    app.run(host="0.0.0.0", port=8000)
```

## Simple App with Sanic Views

Showcasing the simple mechanism of using `sanic.views.HTTPMethodView` as well as a way to extend the same into providing a custom `async` behavior for view.

```
from sanic import Sanic
from sanic.views import HTTPMethodView
from sanic.response import text

app = Sanic('some_name')

class SimpleView(HTTPMethodView):

    def get(self, request):
        return text('I am get method')

    def post(self, request):
        return text('I am post method')

    def put(self, request):
        return text('I am put method')

    def patch(self, request):
        return text('I am patch method')

    def delete(self, request):
        return text('I am delete method')

class SimpleAsyncView(HTTPMethodView):

    async def get(self, request):
        return text('I am async get method')

    async def post(self, request):
        return text('I am async post method')
```

(continues on next page)

(continued from previous page)

```

async def put(self, request):
    return text('I am async put method')

app.add_route(SimpleView.as_view(), '/')
app.add_route(SimpleAsyncView.as_view(), '/async')

if __name__ == '__main__':
    app.run(host="0.0.0.0", port=8000, debug=True)

```

## URL Redirect

```

from sanic import Sanic
from sanic import response

app = Sanic(__name__)

@app.route('/')
def handle_request(request):
    return response.redirect('/redirect')

@app.route('/redirect')
async def test(request):
    return response.json({"Redirected": True})

if __name__ == '__main__':
    app.run(host="0.0.0.0", port=8000)

```

## Named URL redirection

Sanic provides an easy to use way of redirecting the requests via a helper method called `url_for` that takes a unique url name as argument and returns you the actual route assigned for it. This will help in simplifying the efforts required in redirecting the user between different section of the application.

```

from sanic import Sanic
from sanic import response

app = Sanic(__name__)

@app.route('/')
async def index(request):
    # generate a URL for the endpoint `post_handler`
    url = app.url_for('post_handler', post_id=5)
    # the URL is `/posts/5`, redirect to it
    return response.redirect(url)

@app.route('/posts/<post_id>')
async def post_handler(request, post_id):

```

(continues on next page)

(continued from previous page)

```

    return response.text('Post - {}'.format(post_id))

if __name__ == '__main__':
    app.run(host="0.0.0.0", port=8000, debug=True)

```

## Blueprints

Sanic provides an amazing feature to group your APIs and routes under a logical collection that can easily be imported and plugged into any of your sanic application and it's called blueprints

```

from sanic import Blueprint, Sanic
from sanic.response import file, json

app = Sanic(__name__)
blueprint = Blueprint('name', url_prefix='/my_blueprint')
blueprint2 = Blueprint('name2', url_prefix='/my_blueprint2')
blueprint3 = Blueprint('name3', url_prefix='/my_blueprint3')

@blueprint.route('/foo')
async def foo(request):
    return json({'msg': 'hi from blueprint'})

@blueprint2.route('/foo')
async def foo2(request):
    return json({'msg': 'hi from blueprint2'})

@blueprint3.route('/foo')
async def index(request):
    return await file('websocket.html')

@app.websocket('/feed')
async def foo3(request, ws):
    while True:
        data = 'hello!'
        print('Sending: ' + data)
        await ws.send(data)
        data = await ws.recv()
        print('Received: ' + data)

app.blueprint(blueprint)
app.blueprint(blueprint2)
app.blueprint(blueprint3)

app.run(host="0.0.0.0", port=8000, debug=True)

```

## Logging Enhancements

Even though Sanic comes with a battery of Logging support it allows the end users to customize the way logging is handled in the application runtime.

```

from sanic import Sanic
from sanic import response
import logging

logging_format = "[% (asctime)s] %(process)d-% (levelname)s "
logging_format += "% (module)s::%(funcName)s():l%(lineno)d: "
logging_format += "% (message)s"

logging.basicConfig(
    format=logging_format,
    level=logging.DEBUG
)
log = logging.getLogger()

# Set logger to override default basicConfig
sanic = Sanic()

@sanic.route("/")
def test(request):
    log.info("received request; responding with 'hey'")
    return response.text("hey")

sanic.run(host="0.0.0.0", port=8000)

```

The following sample provides an example code that demonstrates the usage of `sanic.app.Sanic.middleware()` in order to provide a mechanism to assign a unique request ID for each of the incoming requests and log them via `aiotask-context`.

```

'''
Based on example from https://github.com/Skyscanner/aiotask-context
and `examples/{override_logging,run_async}.py`.

Needs https://github.com/Skyscanner/aiotask-context/tree/
↪ 52efbc21e2e1def2d52abb9a8e951f3ce5e6f690 or newer

$ pip install git+https://github.com/Skyscanner/aiotask-context.git
'''

import asyncio
import uuid
import logging
from signal import signal, SIGINT

from sanic import Sanic
from sanic import response

import uvloop
import aiotask_context as context

log = logging.getLogger(__name__)

class RequestIdFilter(logging.Filter):
    def filter(self, record):
        record.request_id = context.get('X-Request-ID')
        return True

```

(continues on next page)

(continued from previous page)

```

LOG_SETTINGS = {
    'version': 1,
    'disable_existing_loggers': False,
    'handlers': {
        'console': {
            'class': 'logging.StreamHandler',
            'level': 'DEBUG',
            'formatter': 'default',
            'filters': ['requestid'],
        },
    },
    'filters': {
        'requestid': {
            '()': RequestIdFilter,
        },
    },
    'formatters': {
        'default': {
            'format': '%(asctime)s %(levelname)s %(name)s:%(lineno)d %(request_id)s |
→ %(message)s',
        },
    },
    'loggers': {
        '': {
            'level': 'DEBUG',
            'handlers': ['console'],
            'propagate': True
        },
    }
}

app = Sanic(__name__, log_config=LOG_SETTINGS)

@app.middleware('request')
async def set_request_id(request):
    request_id = request.headers.get('X-Request-ID') or str(uuid.uuid4())
    context.set("X-Request-ID", request_id)

@app.route("/")
async def test(request):
    log.debug('X-Request-ID: %s', context.get('X-Request-ID'))
    log.info('Hello from test!')
    return response.json({"test": True})

if __name__ == '__main__':
    asyncio.set_event_loop(uvloop.new_event_loop())
    server = app.create_server(host="0.0.0.0", port=8000, return_asyncio_server=True)
    loop = asyncio.get_event_loop()
    loop.set_task_factory(context.task_factory)
    task = asyncio.ensure_future(server)
    try:

```

(continues on next page)

(continued from previous page)

```
    loop.run_forever()
except:
    loop.stop()
```

## Sanic Streaming Support

Sanic framework comes with in-built support for streaming large files and the following code explains the process to setup a Sanic application with streaming support.

```
from sanic import Sanic
from sanic.views import CompositionView
from sanic.views import HTTPMethodView
from sanic.views import stream as stream_decorator
from sanic.blueprints import Blueprint
from sanic.response import stream, text

bp = Blueprint('blueprint_request_stream')
app = Sanic('request_stream')

class SimpleView(HTTPMethodView):

    @stream_decorator
    async def post(self, request):
        result = ''
        while True:
            body = await request.stream.get()
            if body is None:
                break
            result += body.decode('utf-8')
        return text(result)

@app.post('/stream', stream=True)
async def handler(request):
    async def streaming(response):
        while True:
            body = await request.stream.get()
            if body is None:
                break
            body = body.decode('utf-8').replace('l', 'A')
            await response.write(body)
    return stream(streaming)

@bp.put('/bp_stream', stream=True)
async def bp_handler(request):
    result = ''
    while True:
        body = await request.stream.get()
        if body is None:
            break
        result += body.decode('utf-8').replace('l', 'A')
    return text(result)
```

(continues on next page)



(continued from previous page)

```

async def post_handler(request):
    result = ''
    while True:
        body = await request.stream.get()
        if body is None:
            break
        result += body.decode('utf-8')
    return text(result)

app.blueprint(bp)
app.add_route(SimpleView.as_view(), '/method_view')
view = CompositionView()
view.add(['POST'], post_handler, stream=True)
app.add_route(view, '/composition_view')

if __name__ == '__main__':
    app.run(host='0.0.0.0', port=8000)

```

Sample Client app to show the usage of streaming application by a client code.

```

import requests

# Warning: This is a heavy process.

data = ""
for i in range(1, 250000):
    data += str(i)

r = requests.post('http://0.0.0.0:8000/stream', data=data)
print(r.text)

```

## Sanic Concurrency Support

Sanic supports the ability to start an app with multiple worker support. However, it's important to be able to limit the concurrency per process/loop in order to ensure an efficient execution. The following section of the code provides a brief example of how to limit the concurrency with the help of `asyncio.Semaphore`.

```

from sanic import Sanic
from sanic.response import json

import asyncio
import aiohttp

app = Sanic(__name__)

sem = None

@app.listener('before_server_start')
def init(sanic, loop):
    global sem
    concurrency_per_worker = 4
    sem = asyncio.Semaphore(concurrency_per_worker, loop=loop)

```

(continues on next page)

(continued from previous page)

```

async def bounded_fetch(session, url):
    """
    Use session object to perform 'get' request on url
    """
    async with sem, session.get(url) as response:
        return await response.json()

@app.route("/")
async def test(request):
    """
    Download and serve example JSON
    """
    url = "https://api.github.com/repos/channelcat/sanic"

    async with aiohttp.ClientSession() as session:
        response = await bounded_fetch(session, url)
        return json(response)

app.run(host="0.0.0.0", port=8000, workers=2)

```

## Sanic Deployment via Docker

Deploying a sanic app via docker and docker-compose is an easy task to achieve and the following example provides a deployment of the sample `simple_server.py`

```

FROM python:3.5
MAINTAINER Channel Cat <channelcat@gmail.com>

ADD . /code
RUN pip3 install git+https://github.com/channelcat/sanic

EXPOSE 8000

WORKDIR /code

CMD ["python", "simple_server.py"]

```

```

version: '2'
services:
  sanic:
    build: .
    ports:
      - "8000:8000"

```

## Monitoring and Error Handling

Sanic provides an extendable bare minimum implementation of a global exception handler via `sanic.handlers.ErrorHandler`. This example shows how to extend it to enable some custom behaviors.

```

"""
Example intercepting uncaught exceptions using Sanic's error handler framework.
This may be useful for developers wishing to use Sentry, Airbrake, etc.
or a custom system to log and monitor unexpected errors in production.
First we create our own class inheriting from Handler in sanic.exceptions,
and pass in an instance of it when we create our Sanic instance. Inside this
class' default handler, we can do anything including sending exceptions to
an external service.
"""
from sanic.handlers import ErrorHandler
from sanic.exceptions import SanicException
"""
Imports and code relevant for our CustomHandler class
(Ordinarily this would be in a separate file)
"""

class CustomHandler(ErrorHandler):

    def default(self, request, exception):
        # Here, we have access to the exception object
        # and can do anything with it (log, send to external service, etc)

        # Some exceptions are trivial and built into Sanic (404s, etc)
        if not isinstance(exception, SanicException):
            print(exception)

        # Then, we must finish handling the exception by returning
        # our response to the client
        # For this we can just call the super class' default handler
        return super().default(request, exception)

"""
This is an ordinary Sanic server, with the exception that we set the
server's error_handler to an instance of our CustomHandler
"""

from sanic import Sanic

app = Sanic(__name__)

handler = CustomHandler()
app.error_handler = handler

@app.route("/")
async def test(request):
    # Here, something occurs which causes an unexpected exception
    # This exception will flow to our custom handler.
    raise SanicException('You Broke It!')

if __name__ == '__main__':
    app.run(host="0.0.0.0", port=8000, debug=True)

```

## Monitoring using external Service Providers

- LogDNA

```

import logging
import socket
from os import getenv
from platform import node
from uuid import getnode as get_mac

from logdna import LogDNAHandler

from sanic import Sanic
from sanic.response import json
from sanic.request import Request

log = logging.getLogger('logdna')
log.setLevel(logging.INFO)

def get_my_ip_address(remote_server="google.com"):
    with socket.socket(socket.AF_INET, socket.SOCK_DGRAM) as s:
        s.connect((remote_server, 80))
        return s.getsockname()[0]

def get_mac_address():
    h = iter(hex(get_mac())[2:].zfill(12))
    return ":".join(i + next(h) for i in h)

logdna_options = {
    "app": __name__,
    "index_meta": True,
    "hostname": node(),
    "ip": get_my_ip_address(),
    "mac": get_mac_address()
}

logdna_handler = LogDNAHandler(getenv("LOGDNA_API_KEY"), options=logdna_options)

logdna = logging.getLogger(__name__)
logdna.setLevel(logging.INFO)
logdna.addHandler(logdna_handler)

app = Sanic(__name__)

@app.middleware
def log_request(request: Request):
    logdna.info("I was Here with a new Request to URL: {}".format(request.url))

@app.route("/")
def default(request):
    return json({
        "response": "I was here"
    })

```

(continues on next page)

(continued from previous page)

```

if __name__ == "__main__":
    app.run(
        host="0.0.0.0",
        port=getenv("PORT", 8080)
    )

```

- RayGun

```

from os import getenv

from raygun4py.raygunprovider import RaygunSender

from sanic import Sanic
from sanic.exceptions import SanicException
from sanic.handlers import ErrorHandler

class RaygunExceptionReporter(ErrorHandler):

    def __init__(self, raygun_api_key=None):
        super().__init__()
        if raygun_api_key is None:
            raygun_api_key = getenv("RAYGUN_API_KEY")

        self.sender = RaygunSender(raygun_api_key)

    def default(self, request, exception):
        self.sender.send_exception(exception=exception)
        return super().default(request, exception)

raygun_error_reporter = RaygunExceptionReporter()
app = Sanic(__name__, error_handler=raygun_error_reporter)

@app.route("/raise")
async def test(request):
    raise SanicException('You Broke It!')

if __name__ == '__main__':
    app.run(
        host="0.0.0.0",
        port=getenv("PORT", 8080)
    )

```

- Rollbar

```

import rollbar

from sanic.handlers import ErrorHandler
from sanic import Sanic
from sanic.exceptions import SanicException
from os import getenv

```

(continues on next page)

(continued from previous page)

```
rollbar.init(getenv("ROLLBAR_API_KEY"))

class RollbarExceptionHandler(ErrorHandler):

    def default(self, request, exception):
        rollbar.report_message(str(exception))
        return super().default(request, exception)

app = Sanic(__name__, error_handler=RollbarExceptionHandler())

@app.route("/raise")
def create_error(request):
    raise SanicException("I was here and I don't like where I am")

if __name__ == "__main__":
    app.run(
        host="0.0.0.0",
        port=getenv("PORT", 8080)
    )
```

- Sentry

```
from os import getenv

from sentry_sdk import init as sentry_init
from sentry_sdk.integrations.sanic import SanicIntegration

from sanic import Sanic
from sanic.response import json

sentry_init(
    dsn=getenv("SENTRY_DSN"),
    integrations=[SanicIntegration()],
)

app = Sanic(__name__)

# noinspection PyUnusedLocal
@app.route("/working")
async def working_path(request):
    return json({
        "response": "Working API Response"
    })

# noinspection PyUnusedLocal
@app.route("/raise-error")
async def raise_error(request):
    raise Exception("Testing Sentry Integration")

if __name__ == '__main__':
```

(continues on next page)

(continued from previous page)

```
app.run(  
    host="0.0.0.0",  
    port=getenv("PORT", 8080)  
)
```

## Security

The following sample code shows a simple decorator based authentication and authorization mechanism that can be setup to secure your sanic api endpoints.

```
# -*- coding: utf-8 -*-  
  
from sanic import Sanic  
from functools import wraps  
from sanic.response import json  
  
app = Sanic()  
  
def check_request_for_authorization_status(request):  
    # Note: Define your check, for instance cookie, session.  
    flag = True  
    return flag  
  
def authorized():  
    def decorator(f):  
        @wraps(f)  
        async def decorated_function(request, *args, **kwargs):  
            # run some method that checks the request  
            # for the client's authorization status  
            is_authorized = check_request_for_authorization_status(request)  
  
            if is_authorized:  
                # the user is authorized.  
                # run the handler method and return the response  
                response = await f(request, *args, **kwargs)  
                return response  
            else:  
                # the user is not authorized.  
                return json({'status': 'not_authorized'}, 403)  
            return decorated_function  
        return decorator  
  
@app.route("/")  
@authorized()  
async def test(request):  
    return json({'status': 'authorized'})  
  
if __name__ == "__main__":  
    app.run(host="0.0.0.0", port=8000)
```

## Sanic Websocket

Sanic provides an ability to easily add a route and map it to a websocket handlers.

```
<!DOCTYPE html>
<html>
  <head>
    <title>WebSocket demo</title>
  </head>
  <body>
    <script>
      var ws = new WebSocket('ws://' + document.domain + ':' + location.port +
→ '/feed'),
        messages = document.createElement('ul');
      ws.onmessage = function (event) {
        var messages = document.getElementsByTagName('ul')[0],
            message = document.createElement('li'),
            content = document.createTextNode('Received: ' + event.data);
        message.appendChild(content);
        messages.appendChild(message);
      };
      document.body.appendChild(messages);
      window.setInterval(function() {
        data = 'bye!'
        ws.send(data);
        var messages = document.getElementsByTagName('ul')[0],
            message = document.createElement('li'),
            content = document.createTextNode('Sent: ' + data);
        message.appendChild(content);
        messages.appendChild(message);
      }, 1000);
    </script>
  </body>
</html>
```

```
from sanic import Sanic
from sanic.response import file

app = Sanic(__name__)

@app.route('/')
async def index(request):
    return await file('websocket.html')

@app.websocket('/feed')
async def feed(request, ws):
    while True:
        data = 'hello!'
        print('Sending: ' + data)
        await ws.send(data)
        data = await ws.recv()
        print('Received: ' + data)

if __name__ == '__main__':
```

(continues on next page)



(continued from previous page)

```
app.run(host="0.0.0.0", port=8000, debug=True)
```

## vhost Support

```
from sanic import response
from sanic import Sanic
from sanic.blueprints import Blueprint

# Usage
# curl -H "Host: example.com" localhost:8000
# curl -H "Host: sub.example.com" localhost:8000
# curl -H "Host: bp.example.com" localhost:8000/question
# curl -H "Host: bp.example.com" localhost:8000/answer

app = Sanic()
bp = Blueprint("bp", host="bp.example.com")

@app.route('/', host=["example.com",
                    "somethingelse.com",
                    "therestofyourdomains.com"])
async def hello(request):
    return response.text("Some defaults")

@app.route('/', host="sub.example.com")
async def hello(request):
    return response.text("42")

@bp.route("/question")
async def hello(request):
    return response.text("What is the meaning of life?")

@bp.route("/answer")
async def hello(request):
    return response.text("42")

app.blueprint(bp)

if __name__ == '__main__':
    app.run(host="0.0.0.0", port=8000)
```

## Unit Testing With Parallel Test Run Support

The following example shows you how to get up and running with unit testing sanic application with parallel test execution support provided by the `pytest-xdist` plugin.

```
"""pytest-xdist example for sanic server

Install testing tools:
```

(continues on next page)

(continued from previous page)

```

    $ pip install pytest pytest-xdist

Run with xdist params:

    $ pytest examples/pytest_xdist.py -n 8 # 8 workers
"""
import re
from sanic import Sanic
from sanic.response import text
from sanic.testing import PORT as PORT_BASE, SanicTestClient
import pytest

@pytest.fixture(scope="session")
def test_port(worker_id):
    m = re.search(r'[0-9]+', worker_id)
    if m:
        num_id = m.group(0)
    else:
        num_id = 0
    port = PORT_BASE + int(num_id)
    return port

@pytest.fixture(scope="session")
def app():
    app = Sanic()

    @app.route('/')
    async def index(request):
        return text('OK')

    return app

@pytest.fixture(scope="session")
def client(app, test_port):
    return SanicTestClient(app, test_port)

@pytest.mark.parametrize('run_id', range(100))
def test_index(client, run_id):
    request, response = client._sanic_endpoint_test('get', '/')
    assert response.status == 200
    assert response.text == 'OK'

```

## Amending Request Object

The request object in Sanic is a kind of dict object, this means that request object can be manipulated as a regular dict object.

```

from sanic import Sanic
from sanic.response import text
from random import randint

```

(continues on next page)

(continued from previous page)

```
app = Sanic()

@app.middleware('request')
def append_request(request):
    # Add new key with random value
    request['num'] = randint(0, 100)

@app.get('/pop')
def pop_handler(request):
    # Pop key from request object
    num = request.pop('num')
    return text(num)

@app.get('/key_exist')
def key_exist_handler(request):
    # Check the key is exist or not
    if 'num' in request:
        return text('num exist in request')

    return text('num does not exist in request')

app.run(host="0.0.0.0", port=8000, debug=True)
```

For more examples and useful samples please visit the [Huge-Sanic's GitHub Page](#)

## 2.25 Changelog

### 2.25.1 Version 19.6.3

#### Features

- Enable Towncrier Support

As part of this feature, *towncrier* is being introduced as a mechanism to partially automate the process of generating and managing change logs as part of each of pull requests. (#1631)

#### Improved Documentation

- Documentation infrastructure changes
  - Enable having a single common *CHANGELOG* file for both GitHub page and documentation
  - Fix Sphinx deprecation warnings
  - Fix documentation warnings due to invalid *rst* indentation
  - Enable common contribution guidelines file across GitHub and documentation via *CONTRIBUTING.rst* (#1631)

## 2.25.2 Version 19.6.2

### Features

- #1562 Remove `aiohttp` dependency and create new `SanicTestClient` based upon `requests-async`
- #1475 Added ASGI support (Beta)
- #1436 Add Configure support from object string

### Bugfixes

- #1587 Add missing handle for Expect header.
- #1560 Allow to disable Transfer-Encoding: chunked.
- #1558 Fix graceful shutdown.
- #1594 Strict Slashes behavior fix

### Deprecations and Removals

- #1544 Drop dependency on `distutil`
- #1562 Drop support for Python 3.5
- #1568 Deprecate route removal.

**Warning:** Sanic will not support Python 3.5 from version 19.6 and forward. However, version 18.12LTS will have its support period extended thru December 2020, and therefore passing Python's official support version 3.5, which is set to expire in September 2020.

## 2.25.3 Version 19.3

### Features

- #1497 Add support for zero-length and RFC 5987 encoded filename for multipart/form-data requests.
- #1484 The type of `expires` attribute of `sanic.cookies.Cookie` is now enforced to be of type `datetime`.
- #1482 Add support for the `stream` parameter of `sanic.Sanic.add_route()` available to `sanic.Blueprint.add_route()`.
- #1481 Accept negative values for route parameters with type `int` or `number`.
- #1476 Deprecated the use of `sanic.request.Request.raw_args` - it has a fundamental flaw in which is drops repeated query string parameters. Added `sanic.request.Request.query_args` as a replacement for the original use-case.
- #1472 Remove an unwanted `None` check in `Request` class `repr` implementation. This changes the default `repr` of a `Request` from `<Request>` to `<Request: None />`
- #1470 Added 2 new parameters to `sanic.app.Sanic.create_server`:
  - `return_asyncio_server` - whether to return an `asyncio.Server`.

- `asyncio_server_kwargs` - kwargs to pass to `loop.create_server` for the event loop that sanic is using.

This is a breaking change.

- #1499 Added a set of test cases that test and benchmark route resolution.
- #1457 The type of the "max-age" value in a `sanic.cookies.Cookie` is now enforced to be an integer. Non-integer values are replaced with 0.
- #1445 Added the `endpoint` attribute to an incoming request, containing the name of the handler function.
- #1423 Improved request streaming. `request.stream` is now a bounded-size buffer instead of an unbounded queue. Callers must now call `await request.stream.read()` instead of `await request.stream.get()` to read each portion of the body.

This is a breaking change.

## Bugfixes

- #1502 Sanic was prefetching `time.time()` and updating it once per second to avoid excessive `time.time()` calls. The implementation was observed to cause memory leaks in some cases. The benefit of the prefetch appeared to negligible, so this has been removed. Fixes #1500
- #1501 Fix a bug in the auto-reloader when the process was launched as a module i.e. `python -m init0.mod1` where the sanic server is started in `init0/mod1.py` with debug enabled and imports another module in `init0`.
- #1376 Allow sanic client to bind to a random port by specifying `port=None` when constructing a `SanicTestClient`
- #1399 Added the ability to specify middleware on a blueprint group, so that all routes produced from the blueprints in the group have the middleware applied.
- #1442 Allow the use the `SANIC_ACCESS_LOG` environment variable to enable/disable the access log when not explicitly passed to `app.run()`. This allows the access log to be disabled for example when running via gunicorn.

## Developer infrastructure

- #1529 Update project PyPI credentials
- #1515 fix linter issue causing travis build failures (fix #1514)
- #1490 Fix python version in doc build
- #1478 Upgrade setuptools version and use native docutils in doc build
- #1464 Upgrade pytest, and fix caplog unit tests

## Improved Documentation

- #1516 Fix typo at the exception documentation
- #1510 fix typo in Asyncio example
- #1486 Documentation typo
- #1477 Fix grammar in README.md
- #1489 Added "databases" to the extensions list

- [#1483](#) Add sanic-zipkin to extensions list
- [#1487](#) Removed link to deleted repo, Sanic-OAuth, from the extensions list
- [#1460](#) 18.12 changelog
- [#1449](#) Add example of amending request object
- [#1446](#) Update README
- [#1444](#) Update README
- [#1443](#) Update README, including new logo
- [#1440](#) fix minor type and pip install instruction mismatch
- [#1424](#) Documentation Enhancements

Note: 19.3.0 was skipped for packaging purposes and not released on PyPI

### 2.25.4 Version 18.12

#### 18.12.0

- Changes:
  - Improved codebase test coverage from 81% to 91%.
  - Added `stream_large_files` and host examples in `static_file` document
  - Added methods to append and finish body content on Request ([#1379](#))
  - Integrated with `.appveyor.yml` for windows ci support
  - Added documentation for `AF_INET6` and `AF_UNIX` socket usage
  - Adopt `black/isort` for codestyle
  - Cancel task when `connection_lost`
  - Simplify request ip and port retrieval logic
  - Handle config error in load config file.
  - Integrate with `codecov` for CI
  - Add missed documentation for config section.
  - Deprecate `Handler.log`
  - Pinned `httptools` requirement to version 0.0.10+
- Fixes:
  - Fix `remove_entity_headers` helper function ([#1415](#))
  - Fix `TypeError` when use `Blueprint.group()` to group blueprint with default `url_prefix`, Use `os.path.normpath` to avoid invalid `url_prefix` like `api//v1 f8a6af1` Rename the `http` module to `helpers` to prevent conflicts with the built-in Python http library (fixes [#1323](#))
  - Fix unittests on windows
  - Fix Namespacing of sanic logger
  - Fix missing quotes in decorator example
  - Fix redirect with quoted param

- Fix doc for latest blueprint code
- Fix build of latex documentation relating to markdown lists
- Fix loop exception handling in app.py
- Fix content length mismatch in windows and other platform
- Fix Range header handling for static files (#1402)
- Fix the logger and make it work (#1397)
- Fix type pickle->pickle in multiprocessing test
- Fix pickling blueprints Change the string passed in the “name” section of the namedtuples in Blueprint to match the name of the Blueprint module attribute name. This allows blueprints to be pickled and unpickled, without errors, which is a requirement of running Sanic in multiprocessing mode in Windows. Added a test for pickling and unpickling blueprints Added a test for pickling and unpickling sanic itself Added a test for enabling multiprocessing on an app with a blueprint (only useful to catch this bug if the tests are run on Windows).
- Fix document for logging

## 2.25.5 Version 0.8

### 0.8.3

- Changes:
  - Ownership changed to org ‘huge-success’

### 0.8.0

- Changes:
  - Add Server-Sent Events extension (Innokenty Lebedev)
  - Graceful handling of request\_handler\_task cancellation (Ashley Sommer)
  - Sanitize URL before redirection (aveao)
  - Add url\_bytes to request (johndoe46)
  - py37 support for travisci (yunstanford)
  - Auto reloader support for OSX (garyo)
  - Add UUID route support (Volodymyr Maksymiv)
  - Add pausable response streams (Ashley Sommer)
  - Add weakref to request slots (vopankov)
  - remove ubuntu 12.04 from test fixture due to deprecation (yunstanford)
  - Allow streaming handlers in add\_route (kinware)
  - use travis\_retry for tox (Raphael Deem)
  - update aiohttp version for test client (yunstanford)
  - add redirect import for clarity (yingshaoxo)
  - Update HTTP Entity headers (Arnulfo Solís)

- Add register\_listener method (Stephan Fitzpatrick)
- Remove uvloop/ujson dependencies for Windows (abuckeneheimer)
- Content-length header on 204/304 responses (Arnulfo Solís)
- Extend WebSocketProtocol arguments and add docs (Bob Olde Hampsink, yunstanford)
- Update development status from pre-alpha to beta (Maksim Anisenkov)
- KeepAlive Timeout log level changed to debug (Arnulfo Solís)
- Pin pytest to 3.3.2 because of pytest-dev/pytest#3170 (Maksim Anisenkov)
- Install Python 3.5 and 3.6 on docker container for tests (Shahin Azad)
- Add support for blueprint groups and nesting (Elias Tarhini)
- Remove uvloop for windows setup (Aleksandr Kurlov)
- Auto Reload (Yaser Amari)
- Documentation updates/fixups (multiple contributors)
- Fixes:
  - Fix: auto\_reload in Linux (Ashley Sommer)
  - Fix: broken tests for aiohttp >= 3.3.0 (Ashley Sommer)
  - Fix: disable auto\_reload by default on windows (abuckeneheimer)
  - Fix (1143): Turn off access log with gunicorn (hqy)
  - Fix (1268): Support status code for file response (Cosmo Borsky)
  - Fix (1266): Add content\_type flag to Sanic.static (Cosmo Borsky)
  - Fix: subprotocols parameter missing from add\_websocket\_route (ciscorn)
  - Fix (1242): Responses for CI header (yunstanford)
  - Fix (1237): add version constraint for websockets (yunstanford)
  - Fix (1231): memory leak - always release resource (Phillip Xu)
  - Fix (1221): make request truthy if transport exists (Raphael Deem)
  - Fix failing tests for aiohttp>=3.1.0 (Ashley Sommer)
  - Fix try\_everything examples (PyManiacGR, kot83)
  - Fix (1158): default to auto\_reload in debug mode (Raphael Deem)
  - Fix (1136): ErrorHandler.response handler call too restrictive (Julien Castiaux)
  - Fix: raw requires bytes-like object (cloudship)
  - Fix (1120): passing a list in to a route decorator's host arg (Timothy Ebiuwhe)
  - Fix: Bug in multipart/form-data parser (DirkGuijt)
  - Fix: Exception for missing parameter when value is null (NyanKiyoshi)
  - Fix: Parameter check (Howie Hu)
  - Fix (1089): Routing issue with named parameters and different methods (yunstanford)
  - Fix (1085): Signal handling in multi-worker mode (yunstanford)
  - Fix: single quote in readme.rst (Cosven)



- Fix: method typos (Dmitry Dygalo)
- Fix: log\_response correct output for ip and port (Wibowo Arindrarto)
- Fix (1042): Exception Handling (Raphael Deem)
- Fix: Chinese URIs (Howie Hu)
- Fix (1079): timeout bug when self.transport is None (Raphael Deem)
- Fix (1074): fix strict\_slashes when route has slash (Raphael Deem)
- Fix (1050): add samesite cookie to cookie keys (Raphael Deem)
- Fix (1065): allow add\_task after server starts (Raphael Deem)
- Fix (1061): double quotes in unauthorized exception (Raphael Deem)
- Fix (1062): inject the app in add\_task method (Raphael Deem)
- Fix: update environment.yml for readthedocs (Eli Uriegas)
- Fix: Cancel request task when response timeout is triggered (Jeong YunWon)
- Fix (1052): Method not allowed response for RFC7231 compliance (Raphael Deem)
- Fix: IPv6 Address and Socket Data Format (Dan Palmer)

Note: Changelog was unmaintained between 0.1 and 0.7

## 2.25.6 Version 0.1

### 0.1.7

- Reversed static url and directory arguments to meet spec

### 0.1.6

- Static files
- Lazy Cookie Loading

### 0.1.5

- Cookies
- Blueprint listeners and ordering
- Faster Router
- Fix: Incomplete file reads on medium+ sized post requests
- Breaking: after\_start and before\_stop now pass sanic as their first argument

### 0.1.4

- Multiprocessing

### 0.1.3

- Blueprint support
- Faster Response processing

### 0.1.1 - 0.1.2

- Struggling to update pypi via CI

### 0.1.0

- Released to public

## 2.26 Contributing

Thank you for your interest! Sanic is always looking for contributors. If you don't feel comfortable contributing code, adding docstrings to the source files is very appreciated.

We are committed to providing a friendly, safe and welcoming environment for all, regardless of gender, sexual orientation, disability, ethnicity, religion, or similar personal characteristic. Our [code of conduct](#) sets the standards for behavior.

### 2.26.1 Installation

To develop on sanic (and mainly to just run the tests) it is highly recommend to install from sources.

So assume you have already cloned the repo and are in the working directory with a virtual environment already set up, then run:

```
pip3 install -e . "[dev]"
```

### 2.26.2 Dependency Changes

Sanic doesn't use `requirements*.txt` files to manage any kind of dependencies related to it in order to simplify the effort required in managing the dependencies. Please make sure you have read and understood the following section of the document that explains the way `sanic` manages dependencies inside the `setup.py` file.

Dependency Type	Usage	Installation
requirements	Bare minimum dependencies required for sanic to function	<code>pip3 install -e .</code>
tests_require / extras_require['test']	Dependencies required to run the Unit Tests for sanic	<code>pip3 install -e '[test]'</code>
extras_require['dev']	Additional Development requirements to add contributing	<code>pip3 install -e '[dev]'</code>
extras_require['docs']	Dependencies required to enable building and enhancing sanic documentation	<code>pip3 install -e '[docs]'</code>

### 2.26.3 Running all tests

To run the tests for Sanic it is recommended to use tox like so:

```
tox
```

See it's that simple!

`tox.ini` contains different environments. Running `tox` without any arguments will run all unittests, perform lint and other checks.

### 2.26.4 Run unittests

tox environment -> “[testenv]“

To execute only unittests, run `tox` with environment like so:

```
tox -e py36 -v -- tests/test_config.py
# or
tox -e py37 -v -- tests/test_config.py
```

### 2.26.5 Run lint checks

tox environment -> [testenv:lint]

Perform flake8, black and isort checks.

```
tox -e lint
```

### 2.26.6 Run other checks

tox environment -> [testenv:check]

Perform other checks.

```
tox -e check
```

### 2.26.7 Run Static Analysis

tox environment -> [testenv:security]

Perform static analysis security scan

```
tox -e security
```

### 2.26.8 Run Documentation sanity check

tox environment -> [testenv:docs]

Perform sanity check on documentation

```
tox -e docs
```

## 2.26.9 Code Style

To maintain the code consistency, Sanic uses following tools.

1. `isort`
2. `black`
3. `flake8`

### **isort**

`isort` sorts Python imports. It divides imports into three categories sorted each in alphabetical order.

1. built-in
2. third-party
3. project-specific

### **black**

`black` is a Python code formatter.

### **flake8**

`flake8` is a Python style guide that wraps following tools into one.

1. PyFlakes
2. pycodestyle
3. Ned Batchelder's McCabe script

`isort`, `black` and `flake8` checks are performed during `tox` lint checks.

Refer `tox` documentation for more details.

## 2.26.10 Pull requests

So the pull request approval rules are pretty simple:

1. All pull requests must have a changelog details associated with it.
2. All pull requests must pass unit tests.
3. All pull requests must be reviewed and approved by at least one current collaborator on the project.
4. All pull requests must pass `flake8` checks.
5. All pull requests must be consistent with the existing code.
6. If you decide to remove/change anything from any common interface a deprecation message should accompany it.
7. If you implement a new feature you should have at least one unit test to accompany it.

8. An example must be one of the following:
- Example of how to use Sanic
  - Example of how to use Sanic extensions
  - Example of how to use Sanic and asynchronous library

### 2.26.11 Changelog

It is mandatory to add documentation for Change log as part of your Pull request when you fix/contribute something to the `sanic` community. This will enable us in generating better and well defined change logs during the release which can aid community users in a great way.

---

**Note:** Single line explaining the details of the PR in brief

Detailed description of what the PR is about and what changes or enhancements are being done. No need to include examples or any other details here. But it is important that you provide enough context here to let user understand what this change is all about and why it is being introduced into the `sanic` codebase.

Make sure you leave an line space after the first line to make sure the document rendering is clean

---

Contribution Type	Changelog file name format	Changelog file location
Features	<git_issue>.feature.rst	changelogs
Bugfixes	<git_issue>.bugfix.rst	changelogs
Improved Documentation	<git_issue>.doc.rst	changelogs
Deprecations and Removals	<git_issue>.removal.rst	changelogs
Miscellaneous internal changes	<git_issue>.misc.rst	changelogs

### 2.26.12 Documentation

Sanic's documentation is built using `sphinx`. Guides are written in Markdown and can be found in the `docs` folder, while the module reference is automatically generated using `sphinx-apidoc`.

To generate the documentation from scratch:

```
sphinx-apidoc -fo docs/_api/ sanic
sphinx-build -b html docs docs/_build

# There is a simple make command provided to ease the work required in generating
# the documentation
make docs
```

The HTML documentation will be created in the `docs/_build` folder.

**Warning:** One of the main goals of Sanic is speed. Code that lowers the performance of Sanic without significant gains in usability, security, or features may not be merged. Please don't let this intimidate you! If you have any concerns about an idea, open an issue for discussion and help.

## 2.27 API Reference

### 2.27.1 Submodules

### 2.27.2 `sanic.app` module

**class** `sanic.app.Sanic` (*name=None, router=None, error\_handler=None, load\_env=True, request\_class=None, strict\_slashes=False, log\_config=None, configure\_logging=True*)

Bases: `object`

**add\_route** (*handler, uri, methods=frozenset({'GET'})*, *host=None, strict\_slashes=None, version=None, name=None, stream=False*)

A helper method to register class instance or functions as a handler to the application url routes.

#### Parameters

- **handler** – function or class instance
- **uri** – path of the URL
- **methods** – list or tuple of methods allowed, these are overridden if using a `HTTPMethodView`
- **host** –
- **strict\_slashes** –
- **version** –
- **name** – user defined route name for `url_for`
- **stream** – boolean specifying if the handler is a stream handler

**Returns** function or class instance

**add\_task** (*task*)

Schedule a task to run later, after the loop has started. Different from `asyncio.ensure_future` in that it does not also return a future, and the actual `ensure_future` call is delayed until before server start.

**Parameters** **task** – future, coroutine or awaitable

**add\_websocket\_route** (*handler, uri, host=None, strict\_slashes=None, subprotocols=None, name=None*)

A helper method to register a function as a websocket route.

#### Parameters

- **handler** – a callable function or instance of a class that can handle the websocket request
- **host** – Host IP or FQDN details
- **uri** – URL path that will be mapped to the websocket handler
- **strict\_slashes** – If the API endpoint needs to terminate with a “/” or not
- **subprotocols** – Subprotocols to be used with websocket handshake
- **name** – A unique name assigned to the URL so that it can be used with `url_for()`

**Returns** Objected decorated by `websocket()`

**property** `asgi_client`

**blueprint** (*blueprint*, *\*\*options*)

Register a blueprint on the application.

#### Parameters

- **blueprint** – Blueprint object or (list, tuple) thereof
- **options** – option dictionary with blueprint defaults

**Returns** Nothing

**converted\_response\_type** (*response*)

No implementation provided.

**async create\_server** (*host: Optional[str] = None, port: Optional[int] = None, debug: bool = False, ssl: Union[dict, ssl.SSLContext, None] = None, sock: Optional[socket.socket] = None, protocol: Type[asyncio.protocols.Protocol] = None, backlog: int = 100, stop\_event: Any = None, access\_log: Optional[bool] = None, return\_asyncio\_server=False, asyncio\_server\_kwargs=None*) → None

Asynchronous version of `run()`.

This method will take care of the operations necessary to invoke the `before_start` events via `trigger_events()` method invocation before starting the `sanic` app in Async mode.

---

**Note:** This does not support multiprocessing and is not the preferred way to run a `Sanic` application.

---

#### Parameters

- **host** (*str*) – Address to host on
- **port** (*int*) – Port to host on
- **debug** (*bool*) – Enables debug output (slows server)
- **ssl** (*SSLContext or dict*) – SSLContext, or location of certificate and key for SSL encryption of worker(s)
- **sock** (*socket*) – Socket for the server to accept connections from
- **protocol** (*type[Protocol]*) – Subclass of asyncio Protocol class
- **backlog** (*int*) – a number of unaccepted connections that the system will allow before refusing new connections
- **stop\_event** (*None*) – event to be triggered before stopping the app - deprecated
- **access\_log** (*bool*) – Enables writing access logs (slows server)
- **return\_asyncio\_server** (*bool*) – flag that defines whether there's a need to return `asyncio.Server` or start it serving right away
- **asyncio\_server\_kwargs** (*dict*) – key-value arguments for `asyncio/uvloop create_server` method

**Returns** Nothing

**delete** (*uri, host=None, strict\_slashes=None, version=None, name=None*)

Add an API URL under the **DELETE HTTP** method

#### Parameters

- **uri** – URL to be tagged to **DELETE** method of **HTTP**

- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct *Sanic* to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with *route()* method

**enable\_websocket** (*enable=True*)

Enable or disable the support for websocket.

Websocket is enabled automatically if websocket routes are added to the application.

**exception** (*\*exceptions*)

Decorate a function to be registered as a handler for exceptions

**Parameters** **exceptions** – exceptions

**Returns** decorated function

**get** (*uri, host=None, strict\_slashes=None, version=None, name=None*)

Add an API URL under the **GET HTTP** method

**Parameters**

- **uri** – URL to be tagged to **GET** method of *HTTP*
- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct *Sanic* to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with *route()* method

**async handle\_request** (*request, write\_callback, stream\_callback*)

Take a request from the HTTP Server and return a response object to be sent back The HTTP Server only expects a response object, so exception handling must be done here

**Parameters**

- **request** – HTTP Request object
- **write\_callback** – Synchronous response function to be called with the response as the only argument
- **stream\_callback** – Coroutine that handles streaming a *StreamingHTTPResponse* if produced by the handler.

**Returns** Nothing

**head** (*uri, host=None, strict\_slashes=None, version=None, name=None*)

**listener** (*event*)

Create a listener from a decorated function.

**Parameters** **event** – event to listen to

**property loop**

Synonymous with *asyncio.get\_event\_loop()*.

Only supported when using the *app.run* method.



**middleware** (*middleware\_or\_request*)

Decorate and register middleware to be called before a request. Can either be called as `@app.middleware` or `@app.middleware('request')`

**Param** `middleware_or_request`: Optional parameter to use for identifying which type of middleware is being registered.

**options** (*uri, host=None, strict\_slashes=None, version=None, name=None*)

Add an API URL under the **OPTIONS HTTP** method

#### Parameters

- **uri** – URL to be tagged to **OPTIONS** method of *HTTP*
- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct *Sanic* to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with `route()` method

**patch** (*uri, host=None, strict\_slashes=None, stream=False, version=None, name=None*)

Add an API URL under the **PATCH HTTP** method

#### Parameters

- **uri** – URL to be tagged to **PATCH** method of *HTTP*
- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct *Sanic* to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with `route()` method

**post** (*uri, host=None, strict\_slashes=None, stream=False, version=None, name=None*)

Add an API URL under the **POST HTTP** method

#### Parameters

- **uri** – URL to be tagged to **POST** method of *HTTP*
- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct *Sanic* to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with `route()` method

**put** (*uri, host=None, strict\_slashes=None, stream=False, version=None, name=None*)

Add an API URL under the **PUT HTTP** method

#### Parameters

- **uri** – URL to be tagged to **PUT** method of *HTTP*

- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct *Sanic* to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with *route()* method

**register\_blueprint** (*\*args, \*\*kwargs*)

Proxy method provided for invoking the *blueprint()* method

---

**Note:** To be deprecated in 1.0. Use *blueprint()* instead.

---

#### Parameters

- **args** – Blueprint object or (list, tuple) thereof
- **kwargs** – option dictionary with blueprint defaults

**Returns** None

**register\_listener** (*listener, event*)

Register the listener for a given event.

#### Parameters

- **listener** – callable i.e. *setup\_db(app, loop)*
- **event** – when to register listener i.e. *'before\_server\_start'*

**Returns** listener

**register\_middleware** (*middleware, attach\_to='request'*)

Register an application level middleware that will be attached to all the API URLs registered under this application.

This method is internally invoked by the *middleware()* decorator provided at the app level.

#### Parameters

- **middleware** – Callback method to be attached to the middleware
- **attach\_to** – The state at which the middleware needs to be invoked in the lifecycle of an *HTTP Request*. **request** - Invoke before the request is processed **response** - Invoke before the response is returned back

**Returns** decorated method

**remove\_route** (*uri, clean\_cache=True, host=None*)

This method provides the app user a mechanism by which an already existing route can be removed from the *Sanic* object

**Warning:** *remove\_route* is deprecated in v19.06 and will be removed from future versions.

#### Parameters

- **uri** – URL Path to be removed from the app

- **clean\_cache** – Instruct sanic if it needs to clean up the LRU route cache
- **host** – IP address or FQDN specific to the host

**Returns** None

**route** (*uri*, *methods=frozenset({'GET'})*, *host=None*, *strict\_slashes=None*, *stream=False*, *version=None*, *name=None*)

Decorate a function to be registered as a route

#### Parameters

- **uri** – path of the URL
- **methods** – list or tuple of methods allowed
- **host** –
- **strict\_slashes** –
- **stream** –
- **version** –
- **name** – user defined route name for url\_for

**Returns** decorated function

**run** (*host: Optional[str] = None*, *port: Optional[int] = None*, *debug: bool = False*, *ssl: Union[dict, ssl.SSLContext, None] = None*, *sock: Optional[socket.socket] = None*, *workers: int = 1*, *protocol: Type[asyncio.protocols.Protocol] = None*, *backlog: int = 100*, *stop\_event: Any = None*, *register\_sys\_signals: bool = True*, *access\_log: Optional[bool] = None*, *\*\*kwargs: Any*) → None  
Run the HTTP Server and listen until keyboard interrupt or term signal. On termination, drain connections before closing.

#### Parameters

- **host** (*str*) – Address to host on
- **port** (*int*) – Port to host on
- **debug** (*bool*) – Enables debug output (slows server)
- **ssl** (*SSLContext or dict*) – SSLContext, or location of certificate and key for SSL encryption of worker(s)
- **sock** (*socket*) – Socket for the server to accept connections from
- **workers** (*int*) – Number of processes received before it is respected
- **protocol** (*type[Protocol]*) – Subclass of asyncio Protocol class
- **backlog** (*int*) – a number of unaccepted connections that the system will allow before refusing new connections
- **stop\_event** (*None*) – event to be triggered before stopping the app - deprecated
- **register\_sys\_signals** (*bool*) – Register SIG\* events
- **access\_log** (*bool*) – Enables writing access logs (slows server)

**Returns** Nothing

**static** (*uri*, *file\_or\_directory*, *pattern*='/?.+', *use\_modified\_since*=True, *use\_content\_range*=False, *stream\_large\_files*=False, *name*='static', *host*=None, *strict\_slashes*=None, *content\_type*=None)

Register a root to serve files from. The input can either be a file or a directory. This method will enable an easy and simple way to setup the `Route` necessary to serve the static files.

#### Parameters

- **uri** – URL path to be used for serving static content
- **file\_or\_directory** – Path for the Static file/directory with static files
- **pattern** – Regexp Pattern identifying the valid static files
- **use\_modified\_since** – If true, send file modified time, and return not modified if the browser's matches the server's
- **use\_content\_range** – If true, process header for range requests and sends the file part that is requested
- **stream\_large\_files** – If true, use the `StreamingHTTPResponse.file_stream()` handler rather than the `HTTPResponse.file()` handler to send the file. If this is an integer, this represents the threshold size to switch to `StreamingHTTPResponse.file_stream()`
- **name** – user defined name used for `url_for`
- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct *Sanic* to check if the request URLs need to terminate with a /
- **content\_type** – user defined content type for header

**Returns** None

**stop()**

This kills the Sanic

**property test\_client**

**async trigger\_events** (*events*, *loop*)

Trigger events (functions or async) :param events: one or more sync or async functions to execute :param loop: event loop

**url\_for** (*view\_name*: str, *\*\*kwargs*)

Build a URL based on a view name and the values provided.

In order to build a URL, all request parameters must be supplied as keyword arguments, and each parameter must pass the test for the specified parameter type. If these conditions are not met, a `URLBuildError` will be thrown.

Keyword arguments that are not request parameters will be included in the output URL's query string.

#### Parameters

- **view\_name** – string referencing the view name
- **\*\*kwargs** – keys and values that are used to build request parameters and query string arguments.

**Returns** the built URL

**Raises:** `URLBuildError`

**websocket** (*uri, host=None, strict\_slashes=None, subprotocols=None, name=None*)

Decorate a function to be registered as a websocket route

#### Parameters

- **uri** – path of the URL
- **host** – Host IP or FQDN details
- **strict\_slashes** – If the API endpoint needs to terminate with a “/” or not
- **subprotocols** – optional list of str with supported subprotocols
- **name** – A unique name assigned to the URL so that it can be used with `url_for()`

**Returns** decorated function

## 2.27.3 sanic.blueprints module

**class** `sanic.blueprints.Blueprint` (*name, url\_prefix=None, host=None, version=None, strict\_slashes=None*)

Bases: `object`

**add\_route** (*handler, uri, methods=frozenset({'GET'})*, *host=None, strict\_slashes=None, version=None, name=None, stream=False*)

Create a blueprint route from a function.

#### Parameters

- **handler** – function for handling uri requests. Accepts function, or class instance with a `view_class` method.
- **uri** – endpoint at which the route will be accessible.
- **methods** – list of acceptable HTTP methods.
- **host** – IP Address of FQDN for the sanic server to use.
- **strict\_slashes** – Enforce the API urls are requested with a training /
- **version** – Blueprint Version
- **name** – user defined route name for `url_for`
- **stream** – boolean specifying if the handler is a stream handler

**Returns** function or class instance

**add\_websocket\_route** (*handler, uri, host=None, version=None, name=None*)

Create a blueprint websocket route from a function.

#### Parameters

- **handler** – function for handling uri requests. Accepts function, or class instance with a `view_class` method.
- **uri** – endpoint at which the route will be accessible.
- **host** – IP Address of FQDN for the sanic server to use.
- **version** – Blueprint Version
- **name** – Unique name to identify the Websocket Route

**Returns** function or class instance

**delete** (*uri, host=None, strict\_slashes=None, version=None, name=None*)

Add an API URL under the **DELETE HTTP** method

**Parameters**

- **uri** – URL to be tagged to **DELETE** method of *HTTP*
- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct *sanic.app.Sanic* to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with *route()* method

**exception** (*\*args, \*\*kwargs*)

This method enables the process of creating a global exception handler for the current blueprint under question.

**Parameters**

- **args** – List of Python exceptions to be caught by the handler
- **kwargs** – Additional optional arguments to be passed to the exception handler

**:return a decorated method to handle global exceptions for any** route registered under this blueprint.

**get** (*uri, host=None, strict\_slashes=None, version=None, name=None*)

Add an API URL under the **GET HTTP** method

**Parameters**

- **uri** – URL to be tagged to **GET** method of *HTTP*
- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct *sanic.app.Sanic* to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with *route()* method

**static group** (*\*blueprints, url\_prefix=""*)

Create a list of blueprints, optionally grouping them under a general URL prefix.

**Parameters**

- **blueprints** – blueprints to be registered as a group
- **url\_prefix** – URL route to be prepended to all sub-prefixes

**head** (*uri, host=None, strict\_slashes=None, version=None, name=None*)

Add an API URL under the **HEAD HTTP** method

**Parameters**

- **uri** – URL to be tagged to **HEAD** method of *HTTP*
- **host** – Host IP or FQDN for the service to use

- **strict\_slashes** – Instruct *sanic.app.Sanic* to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with *route()* method

**listener** (*event*)

Create a listener from a decorated function.

**Parameters** **event** – Event to listen to.

**middleware** (*\*args, \*\*kwargs*)

Create a blueprint middleware from a decorated function.

**Parameters**

- **args** – Positional arguments to be used while invoking the middleware
- **kwargs** – optional keyword args that can be used with the middleware.

**options** (*uri, host=None, strict\_slashes=None, version=None, name=None*)

Add an API URL under the **OPTIONS HTTP** method

**Parameters**

- **uri** – URL to be tagged to **OPTIONS** method of *HTTP*
- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct *sanic.app.Sanic* to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with *route()* method

**patch** (*uri, host=None, strict\_slashes=None, stream=False, version=None, name=None*)

Add an API URL under the **PATCH HTTP** method

**Parameters**

- **uri** – URL to be tagged to **PATCH** method of *HTTP*
- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct *sanic.app.Sanic* to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with *route()* method

**post** (*uri, host=None, strict\_slashes=None, stream=False, version=None, name=None*)

Add an API URL under the **POST HTTP** method

**Parameters**

- **uri** – URL to be tagged to **POST** method of *HTTP*
- **host** – Host IP or FQDN for the service to use

- **strict\_slashes** – Instruct `sanic.app.Sanic` to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with `route()` method

**put** (`uri`, `host=None`, `strict_slashes=None`, `stream=False`, `version=None`, `name=None`)  
Add an API URL under the **PUT HTTP** method

**Parameters**

- **uri** – URL to be tagged to **PUT** method of **HTTP**
- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct `sanic.app.Sanic` to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with `route()` method

**register** (`app`, `options`)  
Register the blueprint to the sanic app.

**Parameters**

- **app** – Instance of `sanic.app.Sanic` class
- **options** – Options to be used while registering the blueprint into the app. `url_prefix` - URL Prefix to override the blueprint prefix

**route** (`uri`, `methods=frozenset({'GET'})`, `host=None`, `strict_slashes=None`, `stream=False`, `version=None`, `name=None`)  
Create a blueprint route from a decorated function.

**Parameters**

- **uri** – endpoint at which the route will be accessible.
- **methods** – list of acceptable HTTP methods.
- **host** – IP Address of FQDN for the sanic server to use.
- **strict\_slashes** – Enforce the API urls are requested with a training /
- **stream** – If the route should provide a streaming support
- **version** – Blueprint Version
- **name** – Unique name to identify the Route

**:return a decorated method that when invoked will return an object** of type `FutureRoute`

**static** (`uri`, `file_or_directory`, `*args`, `**kwargs`)  
Create a blueprint static route from a decorated function.

**Parameters**

- **uri** – endpoint at which the route will be accessible.
- **file\_or\_directory** – Static asset.



**websocket** (*uri, host=None, strict\_slashes=None, version=None, name=None*)

Create a blueprint websocket route from a decorated function.

#### Parameters

- **uri** – endpoint at which the route will be accessible.
- **host** – IP Address of FQDN for the sanic server to use.
- **strict\_slashes** – Enforce the API urls are requested with a training /
- **version** – Blueprint Version
- **name** – Unique name to identify the Websocket Route

**class** `sanic.blueprints.FutureException` (*handler, args, kwargs*)

Bases: tuple

**property** `args`

Alias for field number 1

**property** `handler`

Alias for field number 0

**property** `kwargs`

Alias for field number 2

**class** `sanic.blueprints.FutureListener` (*handler, uri, methods, host*)

Bases: tuple

**property** `handler`

Alias for field number 0

**property** `host`

Alias for field number 3

**property** `methods`

Alias for field number 2

**property** `uri`

Alias for field number 1

**class** `sanic.blueprints.FutureMiddleware` (*middleware, args, kwargs*)

Bases: tuple

**property** `args`

Alias for field number 1

**property** `kwargs`

Alias for field number 2

**property** `middleware`

Alias for field number 0

**class** `sanic.blueprints.FutureRoute` (*handler, uri, methods, host, strict\_slashes, stream, version, name*)

Bases: tuple

**property** `handler`

Alias for field number 0

**property** `host`

Alias for field number 3

**property** `methods`

Alias for field number 2

**property name**  
Alias for field number 7

**property stream**  
Alias for field number 5

**property strict\_slashes**  
Alias for field number 4

**property uri**  
Alias for field number 1

**property version**  
Alias for field number 6

**class** `sanic.blueprints.FutureStatic` (*uri, file\_or\_directory, args, kwargs*)  
Bases: `tuple`

**property args**  
Alias for field number 2

**property file\_or\_directory**  
Alias for field number 1

**property kwargs**  
Alias for field number 3

**property uri**  
Alias for field number 0

## 2.27.4 `sanic.blueprint_group` module

**class** `sanic.blueprint_group.BlueprintGroup` (*url\_prefix=None*)  
Bases: `collections.abc.MutableSequence`

This class provides a mechanism to implement a Blueprint Group using the `group()` method in `Blueprint`. To avoid having to re-write some of the existing implementation, this class provides a custom iterator implementation that will let you use the object of this class as a list/tuple inside the existing implementation.

**property blueprints**  
Retrieve a list of all the available blueprints under this group. :return: List of Blueprint instance

**insert** (*index: int, item: object*) → None  
The Abstract class `MutableSequence` leverages this insert method to perform the `BlueprintGroup.append` operation.

### Parameters

- **index** – Index to use for removing a new Blueprint item
- **item** – New `Blueprint` object.

**Returns** None

**middleware** (*\*args, \*\*kwargs*)

A decorator that can be used to implement a Middleware plugin to all of the Blueprints that belongs to this specific Blueprint Group.

In case of nested Blueprint Groups, the same middleware is applied across each of the Blueprints recursively.

### Parameters

- **args** – Optional positional Parameters to be use middleware
- **kwargs** – Optional Keyword arg to use with Middleware

**Returns** Partial function to apply the middleware

**property url\_prefix**

Retrieve the URL prefix being used for the Current Blueprint Group :return: string with url prefix

## 2.27.5 sanic.config module

**class** `sanic.config.Config` (*defaults=None, load\_env=True, keep\_alive=None*)

Bases: dict

**from\_envvar** (*variable\_name*)

Load a configuration from an environment variable pointing to a configuration file.

**Parameters** **variable\_name** – name of the environment variable

**Returns** bool. True if able to load config, False otherwise.

**from\_object** (*obj*)

Update the values from the given object. Objects are usually either modules or classes.

Just the uppercase variables in that object are stored in the config. Example usage:

```
from yourapplication import default_config
app.config.from_object(default_config)

or also:
app.config.from_object('myproject.config.MyConfigClass')
```

You should not use this function to load the actual configuration but rather configuration defaults. The actual config should be loaded with `from_pyfile()` and ideally from a location not within the package because the package might be installed system wide.

**Parameters** **obj** – an object holding the configuration

**from\_pyfile** (*filename*)

Update the values in the config from a Python file. Only the uppercase variables in that module are stored in the config.

**Parameters** **filename** – an absolute path to the config file

**load\_environment\_vars** (*prefix='SANIC\_'*)

Looks for prefixed environment variables and applies them to the configuration if present.

`sanic.config.strtobool` (*val*)

This function was borrowed from `distutils.utils`. While `distutils` is part of `stdlib`, it feels odd to use `distutils` in main application code.

The function was modified to walk its talk and actually return bool and not int.

## 2.27.6 sanic.constants module

## 2.27.7 sanic.cookies module

**class** `sanic.cookies.Cookie` (*key, value*)

Bases: dict

A stripped down version of Morsel from SimpleCookie #gottagofast

**encode** (*encoding*)

Encode the cookie content in a specific type of encoding instructed by the developer. Leverages the `str.encode()` method provided by python.

This method can be used to encode and embed `utf-8` content into the cookies.

**Parameters** `encoding` – Encoding to be used with the cookie

**Returns** Cookie encoded in a codec of choosing.

**Except** `UnicodeEncodeError`

**class** `sanic.cookies.CookieJar` (*headers*)

Bases: `dict`

`CookieJar` dynamically writes headers as cookies are added and removed It gets around the limitation of one header per name by using the `MultiHeader` class to provide a unique key that encodes to `Set-Cookie`.

## 2.27.8 `sanic.exceptions` module

**exception** `sanic.exceptions.ContentRangeError` (*message, content\_range*)

Bases: `sanic.exceptions.SanicException`

**status\_code** = 416

**exception** `sanic.exceptions.FileNotFound` (*message, path, relative\_url*)

Bases: `sanic.exceptions.NotFound`

**exception** `sanic.exceptions.Forbidden` (*message, status\_code=None*)

Bases: `sanic.exceptions.SanicException`

**status\_code** = 403

**exception** `sanic.exceptions.HeaderExpectationFailed` (*message, status\_code=None*)

Bases: `sanic.exceptions.SanicException`

**status\_code** = 417

**exception** `sanic.exceptions.HeaderNotFound` (*message, status\_code=None*)

Bases: `sanic.exceptions.InvalidUsage`

**exception** `sanic.exceptions.InvalidRangeType` (*message, content\_range*)

Bases: `sanic.exceptions.ContentRangeError`

**exception** `sanic.exceptions.InvalidUsage` (*message, status\_code=None*)

Bases: `sanic.exceptions.SanicException`

**status\_code** = 400

**exception** `sanic.exceptions.MethodNotSupported` (*message, method, allowed\_methods*)

Bases: `sanic.exceptions.SanicException`

**status\_code** = 405

**exception** `sanic.exceptions.NotFound` (*message, status\_code=None*)

Bases: `sanic.exceptions.SanicException`

**status\_code** = 404

**exception** `sanic.exceptions.PayloadTooLarge` (*message, status\_code=None*)

Bases: `sanic.exceptions.SanicException`

**status\_code** = 413

**exception** `sanic.exceptions.PyFileError` (*file*)

Bases: `Exception`

**exception** `sanic.exceptions.RequestTimeout` (*message, status\_code=None*)

Bases: `sanic.exceptions.SanicException`

The Web server (running the Web site) thinks that there has been too long an interval of time between 1) the establishment of an IP connection (socket) between the client and the server and 2) the receipt of any data on that socket, so the server has dropped the connection. The socket connection has actually been lost - the Web server has ‘timed out’ on that particular socket connection.

**status\_code** = 408

**exception** `sanic.exceptions.SanicException` (*message, status\_code=None*)

Bases: `Exception`

**exception** `sanic.exceptions.ServerError` (*message, status\_code=None*)

Bases: `sanic.exceptions.SanicException`

**status\_code** = 500

**exception** `sanic.exceptions.ServiceUnavailable` (*message, status\_code=None*)

Bases: `sanic.exceptions.SanicException`

The server is currently unavailable (because it is overloaded or down for maintenance). Generally, this is a temporary state.

**status\_code** = 503

**exception** `sanic.exceptions.URLBuildError` (*message, status\_code=None*)

Bases: `sanic.exceptions.ServerError`

**exception** `sanic.exceptions.Unauthorized` (*message, status\_code=None, scheme=None, \*\*kwargs*)

Bases: `sanic.exceptions.SanicException`

Unauthorized exception (401 HTTP status code).

#### Parameters

- **message** – Message describing the exception.
- **status\_code** – HTTP Status code.
- **scheme** – Name of the authentication scheme to be used.

When present, `kwargs` is used to complete the WWW-Authentication header.

Examples:

```
# With a Basic auth-scheme, realm MUST be present:
raise Unauthorized("Auth required.",
                  scheme="Basic",
                  realm="Restricted Area")

# With a Digest auth-scheme, things are a bit more complicated:
raise Unauthorized("Auth required.",
                  scheme="Digest",
                  realm="Restricted Area",
                  qop="auth, auth-int",
                  algorithm="MD5",
                  nonce="abcdef",
                  opaque="zyxwvu")
```

(continues on next page)

(continued from previous page)

```
# With a Bearer auth-scheme, realm is optional so you can write:
raise Unauthorized("Auth required.", scheme="Bearer")

# or, if you want to specify the realm:
raise Unauthorized("Auth required.",
                  scheme="Bearer",
                  realm="Restricted Area")
```

```
status_code = 401
```

`sanic.exceptions.abort` (*status\_code*, *message=None*)

Raise an exception based on `SanicException`. Returns the HTTP response message appropriate for the given status code, unless provided.

#### Parameters

- **status\_code** – The HTTP status code to return.
- **message** – The HTTP response body. Defaults to the messages in `response.py` for the given status code.

`sanic.exceptions.add_status_code` (*code*)

Decorator used for adding exceptions to `SanicException`.

## 2.27.9 `sanic.handlers` module

**class** `sanic.handlers.ContentRangeHandler` (*request*, *stats*)

Bases: `object`

A mechanism to parse and process the incoming request headers to extract the content range information.

#### Parameters

- **request** (`sanic.request.Request`) – Incoming api request
- **stats** (`posix.stat_result`) – Stats related to the content

#### Variables

- **start** – Content Range start
- **end** – Content Range end
- **size** – Length of the content
- **total** – Total size identified by the `posix.stat_result` instance
- **`ContentRangeHandler.headers`** – Content range header dict

`end`

`headers`

`size`

`start`

`total`

**class** `sanic.handlers.ErrorHandler`

Bases: `object`

Provide `sanic.app.Sanic` application with a mechanism to handle and process any and all uncaught exceptions in a way the application developer will set fit.

This error handling framework is built into the core that can be extended by the developers to perform a wide range of tasks from recording the error stats to reporting them to an external service that can be used for realtime alerting system.

**add** (*exception, handler*)

Add a new exception handler to an already existing handler object.

**Parameters**

- **exception** (`sanic.exceptions.SanicException` or `Exception`) – Type of exception that need to be handled
- **handler** (`function`) – Reference to the method that will handle the exception

**Returns** `None`

**cached\_handlers = None**

**default** (*request, exception*)

Provide a default behavior for the objects of `ErrorHandler`. If a developer chooses to extent the `ErrorHandler` they can provide a custom implementation for this method to behave in a way they see fit.

**Parameters**

- **request** (`sanic.request.Request`) – Incoming request
- **exception** (`sanic.exceptions.SanicException` or `Exception`) – Exception object

**Returns**

**handlers = None**

**log** (*message, level='error'*)

Deprecated, do not use.

**lookup** (*exception*)

Lookup the existing instance of `ErrorHandler` and fetch the registered handler for a specific type of exception.

This method leverages a dict lookup to speedup the retrieval process.

**Parameters** **exception** (`sanic.exceptions.SanicException` or `Exception`) – Type of exception

**Returns** Registered function if found `None` otherwise

**response** (*request, exception*)

Fetches and executes an exception handler and returns a response object

**Parameters**

- **request** (`sanic.request.Request`) – Instance of `sanic.request.Request`
- **exception** (`sanic.exceptions.SanicException` or `Exception`) – Exception to handle

**Returns** Wrap the return value obtained from `default()` or registered handler for that type of exception.

## 2.27.10 `sanic.log` module

## 2.27.11 `sanic.request` module

**class** `sanic.request.File` (*type, body, name*)

Bases: `tuple`

**property** `body`

Alias for field number 1

**property** `name`

Alias for field number 2

**property** `type`

Alias for field number 0

**class** `sanic.request.Request` (*url\_bytes, headers, version, method, transport, app*)

Bases: `object`

Properties of an HTTP request such as URL, headers, etc.

**app**

**property** `args`

Method to parse *query\_string* using *urllib.parse.parse\_qs*. This methods is used by *args* property. Can be used directly if you need to change default parameters.

### Parameters

- **keep\_blank\_values** (*bool*) – flag indicating whether blank values in percent-encoded queries should be treated as blank strings. A true value indicates that blanks should be retained as blank strings. The default false value indicates that blank values are to be ignored and treated as if they were not included.
- **strict\_parsing** (*bool*) – flag indicating what to do with parsing errors. If false (the default), errors are silently ignored. If true, errors raise a `ValueError` exception.
- **encoding** (*str*) – specify how to decode percent-encoded sequences into Unicode characters, as accepted by the `bytes.decode()` method.
- **errors** (*str*) – specify how to decode percent-encoded sequences into Unicode characters, as accepted by the `bytes.decode()` method.

**Returns** `RequestParameters`

**body**

**body\_finish**()

**body\_init**()

**body\_push**(*data*)

**property** `content_type`

**property** `cookies`

**ctx**

**endpoint**

**property** `files`

**property** `form`

**property** `forwarded`



**get** (*key*, *default=None*)

Deprecated since version 19.9.

Custom context is now stored in *request.custom\_context.yourkey*

**get\_args** (*keep\_blank\_values: bool = False*, *strict\_parsing: bool = False*, *encoding: str = 'utf-8'*, *errors: str = 'replace'*) → `sanic.request.RequestParameters`

Method to parse *query\_string* using *urllib.parse.parse\_qs*. This methods is used by *args* property. Can be used directly if you need to change default parameters.

#### Parameters

- **keep\_blank\_values** (*bool*) – flag indicating whether blank values in percent-encoded queries should be treated as blank strings. A true value indicates that blanks should be retained as blank strings. The default false value indicates that blank values are to be ignored and treated as if they were not included.
- **strict\_parsing** (*bool*) – flag indicating what to do with parsing errors. If false (the default), errors are silently ignored. If true, errors raise a `ValueError` exception.
- **encoding** (*str*) – specify how to decode percent-encoded sequences into Unicode characters, as accepted by the `bytes.decode()` method.
- **errors** (*str*) – specify how to decode percent-encoded sequences into Unicode characters, as accepted by the `bytes.decode()` method.

**Returns** `RequestParameters`

**get\_query\_args** (*keep\_blank\_values: bool = False*, *strict\_parsing: bool = False*, *encoding: str = 'utf-8'*, *errors: str = 'replace'*) → `list`

Method to parse *query\_string* using *urllib.parse.parse\_qs*. This methods is used by *query\_args* property. Can be used directly if you need to change default parameters.

#### Parameters

- **keep\_blank\_values** (*bool*) – flag indicating whether blank values in percent-encoded queries should be treated as blank strings. A true value indicates that blanks should be retained as blank strings. The default false value indicates that blank values are to be ignored and treated as if they were not included.
- **strict\_parsing** (*bool*) – flag indicating what to do with parsing errors. If false (the default), errors are silently ignored. If true, errors raise a `ValueError` exception.
- **encoding** (*str*) – specify how to decode percent-encoded sequences into Unicode characters, as accepted by the `bytes.decode()` method.
- **errors** (*str*) – specify how to decode percent-encoded sequences into Unicode characters, as accepted by the `bytes.decode()` method.

**Returns** `list`

**headers**

**property host**

**Returns** proxied or direct Host header. Hostname and port number may be separated by `sanic.headers.parse_host(request.host)`.

**property ip**

**Returns** peer ip of the socket

**property json**

**load\_json** (*loads=<built-in function loads>*)

**property match\_info**

return matched info after resolving route

**method****parsed\_args****parsed\_files****parsed\_form****parsed\_forwarded****parsed\_json****parsed\_not\_grouped\_args****property path****property port**

**Returns** peer port of the socket

**property query\_args**

Method to parse *query\_string* using *urllib.parse.parse\_qs*. This methods is used by *query\_args* property. Can be used directly if you need to change default parameters.

**Parameters**

- **keep\_blank\_values** (*bool*) – flag indicating whether blank values in percent-encoded queries should be treated as blank strings. A true value indicates that blanks should be retained as blank strings. The default false value indicates that blank values are to be ignored and treated as if they were not included.
- **strict\_parsing** (*bool*) – flag indicating what to do with parsing errors. If false (the default), errors are silently ignored. If true, errors raise a `ValueError` exception.
- **encoding** (*str*) – specify how to decode percent-encoded sequences into Unicode characters, as accepted by the `bytes.decode()` method.
- **errors** (*str*) – specify how to decode percent-encoded sequences into Unicode characters, as accepted by the `bytes.decode()` method.

**Returns** list

**property query\_string****property raw\_args****raw\_url****property remote\_addr**

Attempt to return the original client ip based on *forwarded*, *x-forwarded-for* or *x-real-ip*. If HTTP headers are unavailable or untrusted, returns an empty string.

**Returns** original client ip.

**property scheme**

Attempt to get the request scheme. Seeking the value in this order: *forwarded* header, *x-forwarded-proto* header, *x-scheme* header, the sanic app itself.

**Returns** http/https/wslwss or arbitrary value given by the headers.

**Return type** str

**property server\_name**

Attempt to get the server's external hostname in this order: `config.SERVER_NAME`, proxied or direct Host headers `Request.host()`

**Returns** the server name without port number

**Return type** str

**property server\_port**

Attempt to get the server's external port number in this order: `config.SERVER_NAME`, proxied or direct Host headers `Request.host()`, actual port used by the transport layer socket. :return: server port :rtype: int

**property socket****stream****property token**

Attempt to return the auth header token.

**Returns** token related to request

**transport****uri\_template****property url****url\_for** (*view\_name*, *\*\*kwargs*)

Same as `sanic.Sanic.url_for()`, but automatically determine *scheme* and *netloc* base on the request. Since this method is aiming to generate correct schema & netloc, *\_external* is implied.

**Parameters** *kwargs* – takes same parameters as in `sanic.Sanic.url_for()`

**Returns** an absolute url to the given view

**Return type** str

**version****class** `sanic.request.RequestParameters`

Bases: dict

Hosts a dict with lists as values where `get` returns the first value of the list and `getlist` returns the whole shebang

**get** (*name*, *default=None*)

Return the first value, either the default or actual

**getlist** (*name*, *default=None*)

Return the entire list

**class** `sanic.request.StreamBuffer` (*buffer\_size=100*)

Bases: object

**is\_full** ()**async put** (*payload*)**async read** ()

Stop reading when gets None

`sanic.request.parse_multipart_form` (*body*, *boundary*)

Parse a request body and returns fields and files

**Parameters**

- **body** – bytes request body

- **boundary** – bytes multipart boundary

**Returns** fields (RequestParameters), files (RequestParameters)

## 2.27.12 sanic.response module

**class** `sanic.response.BaseHTTPResponse`

Bases: `object`

**property** `cookies`

**class** `sanic.response.HTTPResponse` (*body=None, status=200, headers=None, content\_type='text/plain', body\_bytes=b''*)

Bases: `sanic.response.BaseHTTPResponse`

**body**

**content\_type**

**property** `cookies`

**headers**

**output** (*version='1.1', keep\_alive=False, keep\_alive\_timeout=None*)

**status**

**class** `sanic.response.StreamingHTTPResponse` (*streaming\_fn, status=200, headers=None, content\_type='text/plain', chunked=True*)

Bases: `sanic.response.BaseHTTPResponse`

**chunked**

**content\_type**

**get\_headers** (*version='1.1', keep\_alive=False, keep\_alive\_timeout=None*)

**headers**

**protocol**

**status**

**async stream** (*version='1.1', keep\_alive=False, keep\_alive\_timeout=None*)

Streams headers, runs the *streaming\_fn* callback that writes content to the response body, then finalizes the response body.

**streaming\_fn**

**async write** (*data*)

Writes a chunk of data to the streaming response.

**Parameters** `data` – bytes-ish data to be written.

**async** `sanic.response.file` (*location, status=200, mime\_type=None, headers=None, filename=None, \_range=None*)

Return a response object with file data.

**Parameters**

- **location** – Location of file on system.
- **mime\_type** – Specific mime\_type.
- **headers** – Custom Headers.
- **filename** – Override filename.

- **\_range** –

**async** `sanic.response.file_stream`(*location*, *status=200*, *chunk\_size=4096*, *mime\_type=None*,  
*headers=None*, *filename=None*, *chunked=True*,  
*\_range=None*)

Return a streaming response object with file data.

#### Parameters

- **location** – Location of file on system.
- **chunk\_size** – The size of each chunk in the stream (in bytes)
- **mime\_type** – Specific mime\_type.
- **headers** – Custom Headers.
- **filename** – Override filename.
- **chunked** – Enable or disable chunked transfer-encoding
- **\_range** –

`sanic.response.html`(*body*, *status=200*, *headers=None*)

Returns response object with body in html format.

#### Parameters

- **body** – Response data to be encoded.
- **status** – Response code.
- **headers** – Custom Headers.

`sanic.response.json`(*body*, *status=200*, *headers=None*, *content\_type='application/json'*,  
*dumps=<built-in function dumps>*, *\*\*kwargs*)

Returns response object with body in json format.

#### Parameters

- **body** – Response data to be serialized.
- **status** – Response code.
- **headers** – Custom Headers.
- **kwargs** – Remaining arguments that are passed to the json encoder.

`sanic.response.raw`(*body*, *status=200*, *headers=None*, *content\_type='application/octet-stream'*)

Returns response object without encoding the body.

#### Parameters

- **body** – Response data.
- **status** – Response code.
- **headers** – Custom Headers.
- **content\_type** – the content type (string) of the response.

`sanic.response.redirect`(*to*, *headers=None*, *status=302*, *content\_type='text/html; charset=utf-8'*)

Abort execution and cause a 302 redirect (by default).

#### Parameters

- **to** – path or fully qualified URL to redirect to
- **headers** – optional dict of headers to include in the new request

- **status** – status code (int) of the new request, defaults to 302
- **content\_type** – the content type (string) of the response

**Returns** the redirecting Response

```
sanic.response.stream(streaming_fn, status=200, headers=None, content_type='text/plain';  
                      charset=utf-8', chunked=True)
```

Accepts an coroutine *streaming\_fn* which can be used to write chunks to a streaming response. Returns a *StreamingHTTPResponse*.

Example usage:

```
@app.route("/")  
async def index(request):  
    async def streaming_fn(response):  
        await response.write('foo')  
        await response.write('bar')  
  
    return stream(streaming_fn, content_type='text/plain')
```

#### Parameters

- **streaming\_fn** – A coroutine accepts a response and writes content to that response.
- **mime\_type** – Specific mime\_type.
- **headers** – Custom Headers.
- **chunked** – Enable or disable chunked transfer-encoding

```
sanic.response.text(body, status=200, headers=None, content_type='text/plain; charset=utf-8')
```

Returns response object with body in text format.

#### Parameters

- **body** – Response data to be encoded.
- **status** – Response code.
- **headers** – Custom Headers.
- **content\_type** – the content type (string) of the response

## 2.27.13 `sanic.router` module

```
class sanic.router.Parameter (name, cast)
```

Bases: tuple

**property** `cast`

Alias for field number 1

**property** `name`

Alias for field number 0

```
exception sanic.router.ParameterNameConflicts
```

Bases: Exception

```
class sanic.router.Route (handler, methods, pattern, parameters, name, uri)
```

Bases: tuple

**property** `handler`

Alias for field number 0

**property methods**

Alias for field number 1

**property name**

Alias for field number 4

**property parameters**

Alias for field number 3

**property pattern**

Alias for field number 2

**property uri**

Alias for field number 5

**exception** `sanic.router.RouteDoesNotExist`Bases: `Exception`**exception** `sanic.router.RouteExists`Bases: `Exception`**class** `sanic.router.Router`Bases: `object`

Router supports basic routing with parameters and method checks

Usage:

```
@sanic.route('/my/url/<my_param>', methods=['GET', 'POST', ...])
def my_route(request, my_param):
    do stuff...
```

or

```
@sanic.route('/my/url/<my_param:my_type>', methods=['GET', 'POST', ...])
def my_route_with_type(request, my_param: my_type):
    do stuff...
```

Parameters will be passed as keyword arguments to the request handling function. Provided parameters can also have a type by appending `:type` to the `<parameter>`. Given parameter must be able to be type-casted to this. If no type is provided, a string is expected. A regular expression can also be passed in as the type. The argument given to the function will always be a string, independent of the type.

**add** (*uri, methods, handler, host=None, strict\_slashes=False, version=None, name=None*)

Add a handler to the route list

**Parameters**

- **uri** – path to match
- **methods** – sequence of accepted method names. If none are provided, any method is allowed
- **handler** – request handler function. When executed, it should provide a response object.
- **strict\_slashes** – strict to trailing slash
- **version** – current version of the route or blueprint. See docs for further details.

**Returns** Nothing**static check\_dynamic\_route\_exists** (*pattern, routes\_to\_check, parameters*)

Check if a URL pattern exists in a list of routes provided based on the comparison of URL pattern and the parameters.

**Parameters**

- **pattern** – URL parameter pattern
- **routes\_to\_check** – list of dynamic routes either hashable or unhashable routes.
- **parameters** – List of *Parameter* items

**Returns** Tuple of index and route if matching route exists else -1 for index and None for route

**find\_route\_by\_view\_name**

Find a route in the router based on the specified view name.

**Parameters**

- **view\_name** – string of view name to search by
- **kwargs** – additional params, usually for static files

**Returns** tuple containing (uri, Route)

**get** (*request*)

Get a request handler based on the URL of the request, or raises an error

**Parameters** **request** – Request object

**Returns** handler, arguments, keyword arguments

**get\_supported\_methods** (*url*)

Get a list of supported methods for a url and optional host.

**Parameters** **url** – URL string (including host)

**Returns** frozenset of supported methods

**is\_stream\_handler** (*request*)

Handler for request is stream or not. :param request: Request object :return: bool

```
parameter_pattern = re.compile('<(.*?)>')
```

```
classmethod parse_parameter_string(parameter_string)
```

Parse a parameter string into its constituent name, type, and pattern

For example:

```
parse_parameter_string('<param_one:[A-z]>')` ->
('param_one', str, '[A-z]')
```

**Parameters** **parameter\_string** – String to parse

**Returns** tuple containing (parameter\_name, parameter\_type, parameter\_pattern)

```
remove(uri, clean_cache=True, host=None)
```

```
routes_always_check = None
```

```
routes_dynamic = None
```

```
routes_static = None
```

```
sanic.router.url_hash(url)
```



## 2.27.14 sanic.server module

**class** `sanic.server.AsyncioServer` (*loop, serve\_coro, connections, after\_start, before\_stop, after\_stop*)

Bases: `object`

Wraps an asyncio server with functionality that might be useful to a user who needs to manage the server lifecycle manually.

**after\_start** ()

Trigger “after\_server\_start” events

**after\_stop** ()

Trigger “after\_server\_stop” events

**before\_stop** ()

Trigger “before\_server\_stop” events

**close** ()

**connections**

**is\_serving** ()

**loop**

**serve\_coro**

**server**

**wait\_closed** ()

**class** `sanic.server.HttpProtocol` (\*, *loop, app, request\_handler, error\_handler, signal=<sanic.server.Signal object>, connections=None, request\_timeout=60, response\_timeout=60, keep\_alive\_timeout=5, request\_max\_size=None, request\_buffer\_queue\_size=100, request\_class=None, access\_log=True, keep\_alive=True, is\_request\_stream=False, router=None, state=None, debug=False, \*\*kwargs*)

Bases: `asyncio.protocols.Protocol`

This class provides a basic HTTP implementation of the sanic framework.

**access\_log**

**app**

**bail\_out** (*message, from\_error=False*)

In case if the transport pipes are closed and the sanic app encounters an error while writing data to the transport pipe, we log the error with proper details.

### Parameters

- **message** (*str*) – Error message to display
- **from\_error** (*bool*) – If the bail out was invoked while handling an exception scenario.

**Returns** `None`

**async body\_append** (*body*)

**cleanup** ()

This is called when KeepAlive feature is used, it resets the connection in order for it to be able to handle receiving another request on the same connection.

**close()**

Force close the connection.

**close\_if\_idle()**

Close the connection if a request is not being sent or received

**Returns** boolean - True if closed, false if staying open

**connection\_lost** (*exc*)

Called when the connection is lost or closed.

The argument is an exception object or None (the latter meaning a regular EOF is received or the connection was aborted or closed).

**connection\_made** (*transport*)

Called when a connection is made.

The argument is the transport representing the pipe connection. To receive data, wait for `data_received()` calls. When the connection is closed, `connection_lost()` is called.

**connections****data\_received** (*data*)

Called when some data is received.

The argument is a bytes object.

**async drain()****error\_handler****execute\_request\_handler()**

Invoke the request handler defined by the `sanic.app.Sanic.handle_request()` method

**Returns** None

**expect\_handler()**

Handler for Expect Header.

**headers****is\_request\_stream****property keep\_alive**

Check if the connection needs to be kept alive based on the params attached to the `_keep_alive` attribute, `Signal.stopped` and `HttpProtocol.parser.should_keep_alive()`

**Returns** True if connection is to be kept alive False else

**keep\_alive\_timeout****keep\_alive\_timeout\_callback()**

Check if elapsed time since last response exceeds our configured maximum keep alive timeout value and if so, close the transport pipe and let the response writer handle the error.

**Returns** None

**log\_response** (*response*)

Helper method provided to enable the logging of responses in case if the `HttpProtocol.access_log` is enabled.

**Parameters response** (`sanic.response.HTTPResponse` or `sanic.response.StreamingHTTPResponse`) – Response generated for the current request

**Returns** None

**loop****on\_body** (*body*)**on\_header** (*name, value*)**on\_headers\_complete** ()**on\_message\_complete** ()**on\_url** (*url*)**parser****pause\_writing** ()

Called when the transport's buffer goes over the high-water mark.

Pause and resume calls are paired – `pause_writing()` is called once when the buffer goes strictly over the high-water mark (even if subsequent writes increases the buffer size even more), and eventually `resume_writing()` is called once when the buffer size reaches the low-water mark.

Note that if the buffer size equals the high-water mark, `pause_writing()` is not called – it must go strictly over. Conversely, `resume_writing()` is called when the buffer size is equal or lower than the low-water mark. These end conditions are important to ensure that things go as expected when either mark is zero.

NOTE: This is the only Protocol callback that is not called through `EventLoop.call_soon()` – if it were, it would have no effect when it's most needed (when the app keeps writing without yielding until `pause_writing()` is called).

**async push\_data** (*data*)**request****request\_buffer\_queue\_size****request\_class****request\_handler****request\_max\_size****request\_timeout****request\_timeout\_callback** ()**response\_timeout****response\_timeout\_callback** ()**resume\_writing** ()

Called when the transport's buffer drains below the low-water mark.

See `pause_writing()` for details.

**router****signal****state****async stream\_response** (*response*)

Streams a response to the client asynchronously. Attaches the transport to the response so the response consumer can write to the response as needed.

**transport****url**

`write_error` (*exception*)

`write_response` (*response*)

Writes response content synchronously to the transport.

`class` `sanic.server.Signal`

Bases: `object`

`stopped = False`

`sanic.server.serve` (*host*, *port*, *app*, *request\_handler*, *error\_handler*, *before\_start=None*, *after\_start=None*, *before\_stop=None*, *after\_stop=None*, *debug=False*, *request\_timeout=60*, *response\_timeout=60*, *keep\_alive\_timeout=5*, *ssl=None*, *sock=None*, *request\_max\_size=None*, *request\_buffer\_queue\_size=100*, *reuse\_port=False*, *loop=None*, *protocol=<class 'sanic.server.HttpProtocol'>*, *backlog=100*, *register\_sys\_signals=True*, *run\_multiple=False*, *run\_async=False*, *connections=None*, *signal=<sanic.server.Signal object>*, *request\_class=None*, *access\_log=True*, *keep\_alive=True*, *is\_request\_stream=False*, *router=None*, *websocket\_max\_size=None*, *websocket\_max\_queue=None*, *websocket\_read\_limit=65536*, *websocket\_write\_limit=65536*, *state=None*, *graceful\_shutdown\_timeout=15.0*, *asyncio\_server\_kwargs=None*)

Start asynchronous HTTP Server on an individual process.

#### Parameters

- **host** – Address to host on
- **port** – Port to host on
- **request\_handler** – Sanic request handler with middleware
- **error\_handler** – Sanic error handler with middleware
- **before\_start** – function to be executed before the server starts listening. Takes arguments *app* instance and *loop*
- **after\_start** – function to be executed after the server starts listening. Takes arguments *app* instance and *loop*
- **before\_stop** – function to be executed when a stop signal is received before it is respected. Takes arguments *app* instance and *loop*
- **after\_stop** – function to be executed when a stop signal is received after it is respected. Takes arguments *app* instance and *loop*
- **debug** – enables debug output (slows server)
- **request\_timeout** – time in seconds
- **response\_timeout** – time in seconds
- **keep\_alive\_timeout** – time in seconds
- **ssl** – SSLContext
- **sock** – Socket for the server to accept connections from
- **request\_max\_size** – size in bytes, *None* for no limit
- **reuse\_port** – *True* for multiple workers
- **loop** – asyncio compatible event loop
- **protocol** – subclass of asyncio protocol class

- **run\_async** – bool: Do not create a new event loop for the server, and return an Async-Server object rather than running it
- **request\_class** – Request class to use
- **access\_log** – disable/enable access log
- **websocket\_max\_size** – enforces the maximum size for incoming messages in bytes.
- **websocket\_max\_queue** – sets the maximum length of the queue that holds incoming messages.
- **websocket\_read\_limit** – sets the high-water limit of the buffer for incoming bytes, the low-water limit is half the high-water limit.
- **websocket\_write\_limit** – sets the high-water limit of the buffer for outgoing bytes, the low-water limit is a quarter of the high-water limit.
- **is\_request\_stream** – disable/enable Request.stream
- **request\_buffer\_queue\_size** – streaming request buffer queue size
- **router** – Router object
- **graceful\_shutdown\_timeout** – How long take to Force close non-idle connection
- **asyncio\_server\_kwargs** – key-value args for asyncio/uvloop create\_server method

**Returns** Nothing

`sanic.server.serve_multiple` (*server\_settings*, *workers*)

Start multiple server processes simultaneously. Stop on interrupt and terminate signals, and drain connections when complete.

**Parameters**

- **server\_settings** – kw arguments to be passed to the serve function
- **workers** – number of workers to launch
- **stop\_event** – if provided, is used as a stop signal

**Returns**

`sanic.server.trigger_events` (*events*, *loop*)

Trigger event callbacks (functions or async)

**Parameters**

- **events** – one or more sync or async functions to execute
- **loop** – event loop

### 2.27.15 `sanic.static` module

`sanic.static.register` (*app*, *uri*, *file\_or\_directory*, *pattern*, *use\_modified\_since*, *use\_content\_range*, *stream\_large\_files*, *name='static'*, *host=None*, *strict\_slashes=None*, *content\_type=None*)

Register a static directory handler with Sanic by adding a route to the router and registering a handler.

**Parameters**

- **app** – Sanic
- **file\_or\_directory** – File or directory path to serve from

- **uri** – URL to serve from
- **pattern** – regular expression used to match files in the URL
- **use\_modified\_since** – If true, send file modified time, and return not modified if the browser's matches the server's
- **use\_content\_range** – If true, process header for range requests and sends the file part that is requested
- **stream\_large\_files** – If true, use the `file_stream()` handler rather than the `file()` handler to send the file. If this is an integer, this represents the threshold size to switch to `file_stream()`
- **name** – user defined name used for `url_for`
- **content\_type** – user defined content type for header

## 2.27.16 sanic.testing module

**class** `sanic.testing.SanicASGIAdapter` (*app*, *suppress\_exceptions: bool = False*)

Bases: `requests_async.asgi.ASGIAdapter`

**async send** (*request: requests.models.PreparedRequest*, *gather\_return: bool = False*, *\*args: Any*, *\*\*kwargs: Any*) → `requests_async.models.Response`

This method is taken MOSTLY verbatim from `requests-async`. The difference is the capturing of a response on the ASGI call and then returning it on the response object. This is implemented to achieve:

```
request, response = await app.asgi_client.get("/")
```

You can see the original code here: [https://github.com/encode/requests-async/blob/614f40f77f19e6c6da8a212ae799107b0384dbf9/requests\\_async/asgi.py#L51](https://github.com/encode/requests-async/blob/614f40f77f19e6c6da8a212ae799107b0384dbf9/requests_async/asgi.py#L51)

**class** `sanic.testing.SanicASGITestClient` (*app*, *base\_url: str = 'http://mockserver'*, *suppress\_exceptions: bool = False*)

Bases: `requests_async.asgi.ASGISession`

**merge\_environment\_settings** (*\*args*, *\*\*kwargs*)

Check the environment and merge it with some settings.

**Return type** `dict`

**async request** (*method*, *url*, *gather\_request=True*, *\*args*, *\*\*kwargs*)

Constructs a `Request`, prepares it and sends it. Returns `Response` object.

### Parameters

- **method** – method for the new `Request` object.
- **url** – URL for the new `Request` object.
- **params** – (optional) Dictionary or bytes to be sent in the query string for the `Request`.
- **data** – (optional) Dictionary, list of tuples, bytes, or file-like object to send in the body of the `Request`.
- **json** – (optional) json to send in the body of the `Request`.
- **headers** – (optional) Dictionary of HTTP Headers to send with the `Request`.
- **cookies** – (optional) Dict or `CookieJar` object to send with the `Request`.
- **files** – (optional) Dictionary of 'filename': file-like-objects for multi-part encoding upload.

- **auth** – (optional) Auth tuple or callable to enable Basic/Digest/Custom HTTP Auth.
- **timeout** (*float or tuple*) – (optional) How long to wait for the server to send data before giving up, as a float, or a (connect timeout, read timeout) tuple.
- **allow\_redirects** (*bool*) – (optional) Set to True by default.
- **proxies** – (optional) Dictionary mapping protocol or protocol and hostname to the URL of the proxy.
- **stream** – (optional) whether to immediately download the response content. Defaults to False.
- **verify** – (optional) Either a boolean, in which case it controls whether we verify the server’s TLS certificate, or a string, in which case it must be a path to a CA bundle to use. Defaults to True.
- **cert** – (optional) if String, path to ssl client cert file (.pem). If Tuple, ('cert', 'key') pair.

**Return type** requests.Response

**async websocket** (*uri, subprotocols=None, \*args, \*\*kwargs*)

**class** `sanic.testing.SanicTestClient` (*app, port=42101*)

Bases: object

**delete** (*\*args, \*\*kwargs*)

**get** (*\*args, \*\*kwargs*)

**get\_new\_session** ()

**head** (*\*args, \*\*kwargs*)

**options** (*\*args, \*\*kwargs*)

**patch** (*\*args, \*\*kwargs*)

**post** (*\*args, \*\*kwargs*)

**put** (*\*args, \*\*kwargs*)

**websocket** (*\*args, \*\*kwargs*)

**class** `sanic.testing.TestASGIApp`

Bases: `sanic.asgi.ASGIApp`

**async** `sanic.testing.app_call_with_return` (*self, scope, receive, send*)

## 2.27.17 `sanic.views` module

**class** `sanic.views.CompositionView`

Bases: object

Simple method-function mapped view for the `sanic`. You can add handler functions to methods (`get`, `post`, `put`, `patch`, `delete`) for every HTTP method you want to support.

**For example:** `view = CompositionView()` `view.add(['GET'], lambda request: text('I am get method'))`  
`view.add(['POST', 'PUT'], lambda request: text('I am post/put method'))`

etc.

If someone tries to use a non-implemented method, there will be a 405 response.

**add** (*methods, handler, stream=False*)

**class** `sanic.views.HTTPMethodView`

Bases: `object`

Simple class based implementation of view for the sanic. You should implement methods (get, post, put, patch, delete) for the class to every HTTP method you want to support.

For example:

```
class DummyView(HTTPMethodView):
    def get(self, request, *args, **kwargs):
        return text('I am get method')
    def put(self, request, *args, **kwargs):
        return text('I am put method')
```

etc.

If someone tries to use a non-implemented method, there will be a 405 response.

If you need any url params just mention them in method definition:

```
class DummyView(HTTPMethodView):
    def get(self, request, my_param_here, *args, **kwargs):
        return text('I am get method with %s' % my_param_here)
```

**To add the view into the routing you could use**

- 1) `app.add_route(DummyView.as_view(), '/')`
- 2) `app.route('/') (DummyView.as_view())`

To add any decorator you could set it into decorators variable

**classmethod** `as_view(*class_args, **class_kwargs)`

Return view function for use with the routing system, that dispatches request to appropriate handler method.

**decorators** = []

**dispatch\_request** (*request*, \*args, \*\*kwargs)

`sanic.views.stream` (*func*)

## 2.27.18 `sanic.websocket` module

**exception** `sanic.websocket.ConnectionClosed` (*code*, *reason*)

Bases: `websockets.exceptions.InvalidState`

Exception raised when trying to read or write on a closed connection.

Provides the connection close code and reason in its `code` and `reason` attributes respectively.

```
class sanic.websocket.WebSocketProtocol(*args,
                                       websocket_timeout=10,
                                       websocket_max_size=None,
                                       socket_max_queue=None,
                                       socket_read_limit=65536,
                                       socket_write_limit=65536, **kwargs)
```

Bases: `sanic.server.HttpProtocol`

**access\_log**

**app**



**connection\_lost** (*exc*)

Called when the connection is lost or closed.

The argument is an exception object or None (the latter meaning a regular EOF is received or the connection was aborted or closed).

**connections**

**data\_received** (*data*)

Called when some data is received.

The argument is a bytes object.

**error\_handler**

**headers**

**is\_request\_stream**

**keep\_alive\_timeout**

**keep\_alive\_timeout\_callback** ()

Check if elapsed time since last response exceeds our configured maximum keep alive timeout value and if so, close the transport pipe and let the response writer handle the error.

**Returns** None

**loop**

**parser**

**request**

**request\_buffer\_queue\_size**

**request\_class**

**request\_handler**

**request\_max\_size**

**request\_timeout**

**request\_timeout\_callback** ()

**response\_timeout**

**response\_timeout\_callback** ()

**router**

**signal**

**state**

**transport**

**url**

**async websocket\_handshake** (*request, subprotocols=None*)

**write\_response** (*response*)

Writes response content synchronously to the transport.

```
class sanic.websocket.WebSocketConnection (send: Callable[MutableMapping[str, Any], Awaitable[None]], receive: Callable[Awaitable[MutableMapping[str, Any]]])
```

Bases: object

```
async accept () → None
async close () → None
async receive (*args, **kwargs) → Optional[str]
async recv (*args, **kwargs) → Optional[str]
async send (data: Union[str, bytes], *args, **kwargs) → None
```

## 2.27.19 sanic.worker module

### 2.27.20 Module contents

```
class sanic.Sanic (name=None, router=None, error_handler=None, load_env=True, request_class=None, strict_slashes=False, log_config=None, configure_logging=True)
```

Bases: object

```
add_route (handler, uri, methods=frozenset({'GET'}), host=None, strict_slashes=None, version=None, name=None, stream=False)
```

A helper method to register class instance or functions as a handler to the application url routes.

#### Parameters

- **handler** – function or class instance
- **uri** – path of the URL
- **methods** – list or tuple of methods allowed, these are overridden if using a HTTPMethodView
- **host** –
- **strict\_slashes** –
- **version** –
- **name** – user defined route name for url\_for
- **stream** – boolean specifying if the handler is a stream handler

**Returns** function or class instance

```
add_task (task)
```

Schedule a task to run later, after the loop has started. Different from `asyncio.ensure_future` in that it does not also return a future, and the actual `ensure_future` call is delayed until before server start.

**Parameters** **task** – future, coroutine or awaitable

```
add_websocket_route (handler, uri, host=None, strict_slashes=None, subprotocols=None, name=None)
```

A helper method to register a function as a websocket route.

#### Parameters

- **handler** – a callable function or instance of a class that can handle the websocket request
- **host** – Host IP or FQDN details
- **uri** – URL path that will be mapped to the websocket handler
- **strict\_slashes** – If the API endpoint needs to terminate with a “/” or not
- **subprotocols** – Subprotocols to be used with websocket handshake

- **name** – A unique name assigned to the URL so that it can be used with `url_for()`

**Returns** Objected decorated by `websocket()`

#### property `asgi_client`

**blueprint** (*blueprint*, *\*\*options*)

Register a blueprint on the application.

#### Parameters

- **blueprint** – Blueprint object or (list, tuple) thereof
- **options** – option dictionary with blueprint defaults

**Returns** Nothing

**converted\_response\_type** (*response*)

No implementation provided.

**async create\_server** (*host: Optional[str] = None, port: Optional[int] = None, debug: bool = False, ssl: Union[dict, ssl.SSLContext, None] = None, sock: Optional[socket.socket] = None, protocol: Type[asyncio.protocols.Protocol] = None, backlog: int = 100, stop\_event: Any = None, access\_log: Optional[bool] = None, return\_asyncio\_server=False, asyncio\_server\_kwargs=None*) → None

Asynchronous version of `run()`.

This method will take care of the operations necessary to invoke the `before_start` events via `trigger_events()` method invocation before starting the `sanic` app in Async mode.

---

**Note:** This does not support multiprocessing and is not the preferred way to run a `Sanic` application.

---

#### Parameters

- **host** (*str*) – Address to host on
- **port** (*int*) – Port to host on
- **debug** (*bool*) – Enables debug output (slows server)
- **ssl** (*SSLContext or dict*) – SSLContext, or location of certificate and key for SSL encryption of worker(s)
- **sock** (*socket*) – Socket for the server to accept connections from
- **protocol** (*type[Protocol]*) – Subclass of asyncio Protocol class
- **backlog** (*int*) – a number of unaccepted connections that the system will allow before refusing new connections
- **stop\_event** (*None*) – event to be triggered before stopping the app - deprecated
- **access\_log** (*bool*) – Enables writing access logs (slows server)
- **return\_asyncio\_server** (*bool*) – flag that defines whether there's a need to return `asyncio.Server` or start it serving right away
- **asyncio\_server\_kwargs** (*dict*) – key-value arguments for `asyncio/uvloop create_server` method

**Returns** Nothing

**delete** (*uri, host=None, strict\_slashes=None, version=None, name=None*)

Add an API URL under the **DELETE HTTP** method

**Parameters**

- **uri** – URL to be tagged to **DELETE** method of *HTTP*
- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct *Sanic* to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with *route()* method

**enable\_websocket** (*enable=True*)

Enable or disable the support for websocket.

Websocket is enabled automatically if websocket routes are added to the application.

**exception** (*\*exceptions*)

Decorate a function to be registered as a handler for exceptions

**Parameters** **exceptions** – exceptions

**Returns** decorated function

**get** (*uri, host=None, strict\_slashes=None, version=None, name=None*)

Add an API URL under the **GET HTTP** method

**Parameters**

- **uri** – URL to be tagged to **GET** method of *HTTP*
- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct *Sanic* to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with *route()* method

**async handle\_request** (*request, write\_callback, stream\_callback*)

Take a request from the HTTP Server and return a response object to be sent back The HTTP Server only expects a response object, so exception handling must be done here

**Parameters**

- **request** – HTTP Request object
- **write\_callback** – Synchronous response function to be called with the response as the only argument
- **stream\_callback** – Coroutine that handles streaming a StreamingHTTPResponse if produced by the handler.

**Returns** Nothing

**head** (*uri, host=None, strict\_slashes=None, version=None, name=None*)

**listener** (*event*)

Create a listener from a decorated function.

**Parameters** `event` – event to listen to

**property** `loop`

Synonymous with `asyncio.get_event_loop()`.

Only supported when using the `app.run` method.

**middleware** (`middleware_or_request`)

Decorate and register middleware to be called before a request. Can either be called as `@app.middleware` or `@app.middleware('request')`

**Param** `middleware_or_request`: Optional parameter to use for identifying which type of middleware is being registered.

**options** (`uri, host=None, strict_slashes=None, version=None, name=None`)

Add an API URL under the **OPTIONS** HTTP method

**Parameters**

- **uri** – URL to be tagged to **OPTIONS** method of *HTTP*
- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct *Sanic* to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with `route()` method

**patch** (`uri, host=None, strict_slashes=None, stream=False, version=None, name=None`)

Add an API URL under the **PATCH** HTTP method

**Parameters**

- **uri** – URL to be tagged to **PATCH** method of *HTTP*
- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct *Sanic* to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with `route()` method

**post** (`uri, host=None, strict_slashes=None, stream=False, version=None, name=None`)

Add an API URL under the **POST** HTTP method

**Parameters**

- **uri** – URL to be tagged to **POST** method of *HTTP*
- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct *Sanic* to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with `route()` method

**put** (*uri, host=None, strict\_slashes=None, stream=False, version=None, name=None*)  
Add an API URL under the **PUT HTTP** method

**Parameters**

- **uri** – URL to be tagged to **PUT** method of *HTTP*
- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct *Sanic* to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with *route()* method

**register\_blueprint** (*\*args, \*\*kwargs*)  
Proxy method provided for invoking the *blueprint()* method

---

**Note:** To be deprecated in 1.0. Use *blueprint()* instead.

---

**Parameters**

- **args** – Blueprint object or (list, tuple) thereof
- **kwargs** – option dictionary with blueprint defaults

**Returns** None

**register\_listener** (*listener, event*)  
Register the listener for a given event.

**Parameters**

- **listener** – callable i.e. *setup\_db(app, loop)*
- **event** – when to register listener i.e. 'before\_server\_start'

**Returns** listener

**register\_middleware** (*middleware, attach\_to='request'*)  
Register an application level middleware that will be attached to all the API URLs registered under this application.

This method is internally invoked by the *middleware()* decorator provided at the app level.

**Parameters**

- **middleware** – Callback method to be attached to the middleware
- **attach\_to** – The state at which the middleware needs to be invoked in the lifecycle of an *HTTP Request*. **request** - Invoke before the request is processed **response** - Invoke before the response is returned back

**Returns** decorated method

**remove\_route** (*uri, clean\_cache=True, host=None*)  
This method provides the app user a mechanism by which an already existing route can be removed from the *Sanic* object

**Warning:** `remove_route` is deprecated in v19.06 and will be removed from future versions.

### Parameters

- **uri** – URL Path to be removed from the app
- **clean\_cache** – Instruct sanic if it needs to clean up the LRU route cache
- **host** – IP address or FQDN specific to the host

**Returns** None

**route** (*uri*, *methods=frozenset({'GET'})*, *host=None*, *strict\_slashes=None*, *stream=False*, *version=None*, *name=None*)

Decorate a function to be registered as a route

### Parameters

- **uri** – path of the URL
- **methods** – list or tuple of methods allowed
- **host** –
- **strict\_slashes** –
- **stream** –
- **version** –
- **name** – user defined route name for `url_for`

**Returns** decorated function

**run** (*host: Optional[str] = None*, *port: Optional[int] = None*, *debug: bool = False*, *ssl: Union[dict, ssl.SSLContext, None] = None*, *sock: Optional[socket.socket] = None*, *workers: int = 1*, *protocol: Type[asyncio.protocols.Protocol] = None*, *backlog: int = 100*, *stop\_event: Any = None*, *register\_sys\_signals: bool = True*, *access\_log: Optional[bool] = None*, *\*\*kwargs: Any*) → None

Run the HTTP Server and listen until keyboard interrupt or term signal. On termination, drain connections before closing.

### Parameters

- **host** (*str*) – Address to host on
- **port** (*int*) – Port to host on
- **debug** (*bool*) – Enables debug output (slows server)
- **ssl** (*SSLContext or dict*) – SSLContext, or location of certificate and key for SSL encryption of worker(s)
- **sock** (*socket*) – Socket for the server to accept connections from
- **workers** (*int*) – Number of processes received before it is respected
- **protocol** (*type[Protocol]*) – Subclass of asyncio Protocol class
- **backlog** (*int*) – a number of unaccepted connections that the system will allow before refusing new connections
- **stop\_event** (*None*) – event to be triggered before stopping the app - deprecated
- **register\_sys\_signals** (*bool*) – Register SIG\* events
- **access\_log** (*bool*) – Enables writing access logs (slows server)

**Returns** Nothing

**static** (*uri*, *file\_or\_directory*, *pattern='/?.'*, *use\_modified\_since=True*, *use\_content\_range=False*, *stream\_large\_files=False*, *name='static'*, *host=None*, *strict\_slashes=None*, *content\_type=None*)

Register a root to serve files from. The input can either be a file or a directory. This method will enable an easy and simple way to setup the `Route` necessary to serve the static files.

**Parameters**

- **uri** – URL path to be used for serving static content
- **file\_or\_directory** – Path for the Static file/directory with static files
- **pattern** – Regex Pattern identifying the valid static files
- **use\_modified\_since** – If true, send file modified time, and return not modified if the browser's matches the server's
- **use\_content\_range** – If true, process header for range requests and sends the file part that is requested
- **stream\_large\_files** – If true, use the `StreamingHTTPResponse.file_stream()` handler rather than the `HTTPResponse.file()` handler to send the file. If this is an integer, this represents the threshold size to switch to `StreamingHTTPResponse.file_stream()`
- **name** – user defined name used for `url_for`
- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct *Sanic* to check if the request URLs need to terminate with a /
- **content\_type** – user defined content type for header

**Returns** None

**stop()**

This kills the Sanic

**property test\_client**

**async trigger\_events** (*events*, *loop*)

Trigger events (functions or async) :param events: one or more sync or async functions to execute :param loop: event loop

**url\_for** (*view\_name: str*, *\*\*kwargs*)

Build a URL based on a view name and the values provided.

In order to build a URL, all request parameters must be supplied as keyword arguments, and each parameter must pass the test for the specified parameter type. If these conditions are not met, a `URLBuildError` will be thrown.

Keyword arguments that are not request parameters will be included in the output URL's query string.

**Parameters**

- **view\_name** – string referencing the view name
- **\*\*kwargs** – keys and values that are used to build request parameters and query string arguments.

**Returns** the built URL

**Raises:** `URLBuildError`



**websocket** (*uri, host=None, strict\_slashes=None, subprotocols=None, name=None*)

Decorate a function to be registered as a websocket route

#### Parameters

- **uri** – path of the URL
- **host** – Host IP or FQDN details
- **strict\_slashes** – If the API endpoint needs to terminate with a “/” or not
- **subprotocols** – optional list of str with supported subprotocols
- **name** – A unique name assigned to the URL so that it can be used with `url_for()`

**Returns** decorated function

**class** `sanic.Blueprint` (*name, url\_prefix=None, host=None, version=None, strict\_slashes=None*)

Bases: `object`

**add\_route** (*handler, uri, methods=frozenset({'GET'})*, *host=None, strict\_slashes=None, version=None, name=None, stream=False*)

Create a blueprint route from a function.

#### Parameters

- **handler** – function for handling uri requests. Accepts function, or class instance with a `view_class` method.
- **uri** – endpoint at which the route will be accessible.
- **methods** – list of acceptable HTTP methods.
- **host** – IP Address of FQDN for the sanic server to use.
- **strict\_slashes** – Enforce the API urls are requested with a training /
- **version** – Blueprint Version
- **name** – user defined route name for `url_for`
- **stream** – boolean specifying if the handler is a stream handler

**Returns** function or class instance

**add\_websocket\_route** (*handler, uri, host=None, version=None, name=None*)

Create a blueprint websocket route from a function.

#### Parameters

- **handler** – function for handling uri requests. Accepts function, or class instance with a `view_class` method.
- **uri** – endpoint at which the route will be accessible.
- **host** – IP Address of FQDN for the sanic server to use.
- **version** – Blueprint Version
- **name** – Unique name to identify the Websocket Route

**Returns** function or class instance

**delete** (*uri, host=None, strict\_slashes=None, version=None, name=None*)

Add an API URL under the **DELETE HTTP** method

#### Parameters

- **uri** – URL to be tagged to **DELETE** method of **HTTP**

- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct `sanic.app.Sanic` to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with `route()` method

**exception** (\*args, \*\*kwargs)

This method enables the process of creating a global exception handler for the current blueprint under question.

**Parameters**

- **args** – List of Python exceptions to be caught by the handler
- **kwargs** – Additional optional arguments to be passed to the exception handler

**:return a decorated method to handle global exceptions for any** route registered under this blueprint.

**get** (uri, host=None, strict\_slashes=None, version=None, name=None)

Add an API URL under the **GET HTTP** method

**Parameters**

- **uri** – URL to be tagged to **GET** method of *HTTP*
- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct `sanic.app.Sanic` to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with `route()` method

**static group** (\*blueprints, url\_prefix=“”)

Create a list of blueprints, optionally grouping them under a general URL prefix.

**Parameters**

- **blueprints** – blueprints to be registered as a group
- **url\_prefix** – URL route to be prepended to all sub-prefixes

**head** (uri, host=None, strict\_slashes=None, version=None, name=None)

Add an API URL under the **HEAD HTTP** method

**Parameters**

- **uri** – URL to be tagged to **HEAD** method of *HTTP*
- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct `sanic.app.Sanic` to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with `route()` method

**listener** (*event*)

Create a listener from a decorated function.

**Parameters** **event** – Event to listen to.

**middleware** (*\*args, \*\*kwargs*)

Create a blueprint middleware from a decorated function.

**Parameters**

- **args** – Positional arguments to be used while invoking the middleware
- **kwargs** – optional keyword args that can be used with the middleware.

**options** (*uri, host=None, strict\_slashes=None, version=None, name=None*)

Add an API URL under the **OPTIONS HTTP** method

**Parameters**

- **uri** – URL to be tagged to **OPTIONS** method of *HTTP*
- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct *sanic.app.Sanic* to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with *route()* method

**patch** (*uri, host=None, strict\_slashes=None, stream=False, version=None, name=None*)

Add an API URL under the **PATCH HTTP** method

**Parameters**

- **uri** – URL to be tagged to **PATCH** method of *HTTP*
- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct *sanic.app.Sanic* to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with *route()* method

**post** (*uri, host=None, strict\_slashes=None, stream=False, version=None, name=None*)

Add an API URL under the **POST HTTP** method

**Parameters**

- **uri** – URL to be tagged to **POST** method of *HTTP*
- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct *sanic.app.Sanic* to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with *route()* method

**put** (*uri, host=None, strict\_slashes=None, stream=False, version=None, name=None*)  
Add an API URL under the **PUT HTTP** method

#### Parameters

- **uri** – URL to be tagged to **PUT** method of *HTTP*
- **host** – Host IP or FQDN for the service to use
- **strict\_slashes** – Instruct *sanic.app.Sanic* to check if the request URLs need to terminate with a /
- **version** – API Version
- **name** – Unique name that can be used to identify the Route

**Returns** Object decorated with *route()* method

**register** (*app, options*)  
Register the blueprint to the *sanic* app.

#### Parameters

- **app** – Instance of *sanic.app.Sanic* class
- **options** – Options to be used while registering the blueprint into the app. *url\_prefix* - URL Prefix to override the blueprint prefix

**route** (*uri, methods=frozenset({'GET'}), host=None, strict\_slashes=None, stream=False, version=None, name=None*)  
Create a blueprint route from a decorated function.

#### Parameters

- **uri** – endpoint at which the route will be accessible.
- **methods** – list of acceptable HTTP methods.
- **host** – IP Address of FQDN for the *sanic* server to use.
- **strict\_slashes** – Enforce the API urls are requested with a training /
- **stream** – If the route should provide a streaming support
- **version** – Blueprint Version
- **name** – Unique name to identify the Route

**:return a decorated method that when invoked will return an object** of type *FutureRoute*

**static** (*uri, file\_or\_directory, \*args, \*\*kwargs*)  
Create a blueprint static route from a decorated function.

#### Parameters

- **uri** – endpoint at which the route will be accessible.
- **file\_or\_directory** – Static asset.

**websocket** (*uri, host=None, strict\_slashes=None, version=None, name=None*)  
Create a blueprint websocket route from a decorated function.

#### Parameters

- **uri** – endpoint at which the route will be accessible.
- **host** – IP Address of FQDN for the *sanic* server to use.

- **strict\_slashes** – Enforce the API urls are requested with a training /
- **version** – Blueprint Version
- **name** – Unique name to identify the Websocket Route

## 2.28 Python 3.7 AsyncIO examples

With Python 3.7 AsyncIO got major update for the following types:

- `asyncio.AbstractEventLoop`
- `asyncio.AbstractServer`

This example shows how to use sanic with Python 3.7, to be precise: how to retrieve an asyncio server instance:

```
import asyncio
import socket
import os

from sanic import Sanic
from sanic.response import json

app = Sanic(__name__)

@app.route("/")
async def test(request):
    return json({"hello": "world"})

server_socket = '/tmp/sanic.sock'

sock = socket.socket(socket.AF_UNIX, socket.SOCK_STREAM)

try:
    os.remove(server_socket)
finally:
    sock.bind(server_socket)

if __name__ == "__main__":
    loop = asyncio.get_event_loop()
    srv_coro = app.create_server(
        sock=sock,
        return_asyncio_server=True,
        asyncio_server_kwargs=dict(
            start_serving=False
        )
    )
    srv = loop.run_until_complete(srv_coro)
    try:
        assert srv.is_serving() is False
        loop.run_until_complete(srv.start_serving())
        assert srv.is_serving() is True
        loop.run_until_complete(srv.serve_forever())
    except KeyboardInterrupt:
        srv.close()
        loop.close()
```

Please note that uvloop does not support these features yet.

## MODULE DOCUMENTATION

- [genindex](#)
- [modindex](#)
- [search](#)





## PYTHON MODULE INDEX

### S

- sanic, 118
- sanic.app, 82
- sanic.blueprint\_group, 94
- sanic.blueprints, 89
- sanic.config, 95
- sanic.constants, 95
- sanic.cookies, 95
- sanic.exceptions, 96
- sanic.handlers, 98
- sanic.log, 100
- sanic.request, 100
- sanic.response, 104
- sanic.router, 106
- sanic.server, 109
- sanic.static, 113
- sanic.testing, 114
- sanic.views, 115
- sanic.websocket, 116



## A

abort () (in module *sanic.exceptions*), 98  
 accept () (*sanic.websocket.WebSocketConnection* method), 117  
 access\_log (*sanic.server.HttpProtocol* attribute), 109  
 access\_log (*sanic.websocket.WebSocketProtocol* attribute), 116  
 add () (*sanic.handlers.ErrorHandler* method), 99  
 add () (*sanic.router.Router* method), 107  
 add () (*sanic.views.CompositionView* method), 115  
 add\_route () (*sanic.app.Sanic* method), 82  
 add\_route () (*sanic.Blueprint* method), 125  
 add\_route () (*sanic.blueprints.Blueprint* method), 89  
 add\_route () (*sanic.Sanic* method), 118  
 add\_status\_code () (in module *sanic.exceptions*), 98  
 add\_task () (*sanic.app.Sanic* method), 82  
 add\_task () (*sanic.Sanic* method), 118  
 add\_websocket\_route () (*sanic.app.Sanic* method), 82  
 add\_websocket\_route () (*sanic.Blueprint* method), 125  
 add\_websocket\_route () (*sanic.blueprints.Blueprint* method), 89  
 add\_websocket\_route () (*sanic.Sanic* method), 118  
 after\_start () (*sanic.server.AsyncioServer* method), 109  
 after\_stop () (*sanic.server.AsyncioServer* method), 109  
 app (*sanic.request.Request* attribute), 100  
 app (*sanic.server.HttpProtocol* attribute), 109  
 app (*sanic.websocket.WebSocketProtocol* attribute), 116  
 app\_call\_with\_return () (in module *sanic.testing*), 115  
 args () (*sanic.blueprints.FutureException* property), 93  
 args () (*sanic.blueprints.FutureMiddleware* property), 93  
 args () (*sanic.blueprints.FutureStatic* property), 94  
 args () (*sanic.request.Request* property), 100  
 as\_view () (*sanic.views.HTTPMethodView* class method), 116

asgi\_client () (*sanic.app.Sanic* property), 82  
 asgi\_client () (*sanic.Sanic* property), 119  
 AsyncioServer (class in *sanic.server*), 109

## B

bail\_out () (*sanic.server.HttpProtocol* method), 109  
 BaseHTTPResponse (class in *sanic.response*), 104  
 before\_stop () (*sanic.server.AsyncioServer* method), 109  
 Blueprint (class in *sanic*), 125  
 Blueprint (class in *sanic.blueprints*), 89  
 blueprint () (*sanic.app.Sanic* method), 82  
 blueprint () (*sanic.Sanic* method), 119  
 BlueprintGroup (class in *sanic.blueprint\_group*), 94  
 blueprints () (*sanic.blueprint\_group.BlueprintGroup* property), 94  
 body (*sanic.request.Request* attribute), 100  
 body (*sanic.response.HTTPResponse* attribute), 104  
 body () (*sanic.request.File* property), 100  
 body\_append () (*sanic.server.HttpProtocol* method), 109  
 body\_finish () (*sanic.request.Request* method), 100  
 body\_init () (*sanic.request.Request* method), 100  
 body\_push () (*sanic.request.Request* method), 100

## C

cached\_handlers (*sanic.handlers.ErrorHandler* attribute), 99  
 cast () (*sanic.router.Parameter* property), 106  
 check\_dynamic\_route\_exists () (*sanic.router.Router* static method), 107  
 chunked (*sanic.response.StreamingHTTPResponse* attribute), 104  
 cleanup () (*sanic.server.HttpProtocol* method), 109  
 close () (*sanic.server.AsyncioServer* method), 109  
 close () (*sanic.server.HttpProtocol* method), 109  
 close () (*sanic.websocket.WebSocketConnection* method), 118  
 close\_if\_idle () (*sanic.server.HttpProtocol* method), 110  
 CompositionView (class in *sanic.views*), 115  
 Config (class in *sanic.config*), 95

connection\_lost() (*sanic.server.HttpProtocol method*), 110  
 connection\_lost() (*sanic.websocket.WebSocketProtocol method*), 116  
 connection\_made() (*sanic.server.HttpProtocol method*), 110  
 ConnectionClosed, 116  
 connections (*sanic.server.AsyncioServer attribute*), 109  
 connections (*sanic.server.HttpProtocol attribute*), 110  
 connections (*sanic.websocket.WebSocketProtocol attribute*), 117  
 content\_type (*sanic.response.HTTPResponse attribute*), 104  
 content\_type (*sanic.response.StreamingHTTPResponse attribute*), 104  
 content\_type() (*sanic.request.Request property*), 100  
 ContentRangeError, 96  
 ContentRangeHandler (*class in sanc.handlers*), 98  
 converted\_response\_type() (*sanic.app.Sanic method*), 83  
 converted\_response\_type() (*sanic.Sanic method*), 119  
 Cookie (*class in sanc.cookies*), 95  
 CookieJar (*class in sanc.cookies*), 96  
 cookies() (*sanic.request.Request property*), 100  
 cookies() (*sanic.response.BaseHTTPResponse property*), 104  
 cookies() (*sanic.response.HTTPResponse property*), 104  
 create\_server() (*sanic.app.Sanic method*), 83  
 create\_server() (*sanic.Sanic method*), 119  
 ctx (*sanic.request.Request attribute*), 100

**D**

data\_received() (*sanic.server.HttpProtocol method*), 110  
 data\_received() (*sanic.websocket.WebSocketProtocol method*), 117  
 decorators (*sanic.views.HTTPMethodView attribute*), 116  
 default() (*sanic.handlers.ErrorHandler method*), 99  
 delete() (*sanic.app.Sanic method*), 83  
 delete() (*sanic.Blueprint method*), 125  
 delete() (*sanic.blueprints.Blueprint method*), 89  
 delete() (*sanic.Sanic method*), 119  
 delete() (*sanic.testing.SanicTestClient method*), 115  
 dispatch\_request() (*sanic.views.HTTPMethodView method*), 116  
 drain() (*sanic.server.HttpProtocol method*), 110

**E**

enable\_websocket() (*sanic.app.Sanic method*), 84  
 enable\_websocket() (*sanic.Sanic method*), 120  
 encode() (*sanic.cookies.Cookie method*), 96  
 end (*sanic.handlers.ContentRangeHandler attribute*), 98  
 endpoint (*sanic.request.Request attribute*), 100  
 error\_handler (*sanic.server.HttpProtocol attribute*), 110  
 error\_handler (*sanic.websocket.WebSocketProtocol attribute*), 117  
 ErrorHandler (*class in sanc.handlers*), 98  
 exception() (*sanic.app.Sanic method*), 84  
 exception() (*sanic.Blueprint method*), 126  
 exception() (*sanic.blueprints.Blueprint method*), 90  
 exception() (*sanic.Sanic method*), 120  
 execute\_request\_handler() (*sanic.server.HttpProtocol method*), 110  
 expect\_handler() (*sanic.server.HttpProtocol method*), 110

**F**

File (*class in sanc.request*), 100  
 file() (*in module sanc.response*), 104  
 file\_or\_directory() (*sanic.blueprints.FutureStatic property*), 94  
 file\_stream() (*in module sanc.response*), 105  
 FileNotFoundError, 96  
 files() (*sanic.request.Request property*), 100  
 find\_route\_by\_view\_name (*sanic.router.Router attribute*), 108  
 Forbidden, 96  
 form() (*sanic.request.Request property*), 100  
 forwarded() (*sanic.request.Request property*), 100  
 from\_envvar() (*sanic.config.Config method*), 95  
 from\_object() (*sanic.config.Config method*), 95  
 from\_pyfile() (*sanic.config.Config method*), 95  
 FutureException (*class in sanc.blueprints*), 93  
 FutureListener (*class in sanc.blueprints*), 93  
 FutureMiddleware (*class in sanc.blueprints*), 93  
 FutureRoute (*class in sanc.blueprints*), 93  
 FutureStatic (*class in sanc.blueprints*), 94

**G**

get() (*sanic.app.Sanic method*), 84  
 get() (*sanic.Blueprint method*), 126  
 get() (*sanic.blueprints.Blueprint method*), 90  
 get() (*sanic.request.Request method*), 100  
 get() (*sanic.request.RequestParameters method*), 103  
 get() (*sanic.router.Router method*), 108  
 get() (*sanic.Sanic method*), 120  
 get() (*sanic.testing.SanicTestClient method*), 115  
 get\_args() (*sanic.request.Request method*), 101

- [get\\_headers\(\)](#) (*sanic.response.StreamingHTTPResponse* method), 104  
[get\\_new\\_session\(\)](#) (*sanic.testing.SanicTestClient* method), 115  
[get\\_query\\_args\(\)](#) (*sanic.request.Request* method), 101  
[get\\_supported\\_methods\(\)](#) (*sanic.router.Router* method), 108  
[getlist\(\)](#) (*sanic.request.RequestParameters* method), 103  
[group\(\)](#) (*sanic.Blueprint* static method), 126  
[group\(\)](#) (*sanic.blueprints.Blueprint* static method), 90
- ## H
- [handle\\_request\(\)](#) (*sanic.app.Sanic* method), 84  
[handle\\_request\(\)](#) (*sanic.Sanic* method), 120  
[handler\(\)](#) (*sanic.blueprints.FutureException* property), 93  
[handler\(\)](#) (*sanic.blueprints.FutureListener* property), 93  
[handler\(\)](#) (*sanic.blueprints.FutureRoute* property), 93  
[handler\(\)](#) (*sanic.router.Route* property), 106  
[handlers](#) (*sanic.handlers.ErrorHandler* attribute), 99  
[head\(\)](#) (*sanic.app.Sanic* method), 84  
[head\(\)](#) (*sanic.Blueprint* method), 126  
[head\(\)](#) (*sanic.blueprints.Blueprint* method), 90  
[head\(\)](#) (*sanic.Sanic* method), 120  
[head\(\)](#) (*sanic.testing.SanicTestClient* method), 115  
[HeaderExpectationFailed](#), 96  
[HeaderNotFound](#), 96  
[headers](#) (*sanic.handlers.ContentRangeHandler* attribute), 98  
[headers](#) (*sanic.request.Request* attribute), 101  
[headers](#) (*sanic.response.HTTPResponse* attribute), 104  
[headers](#) (*sanic.response.StreamingHTTPResponse* attribute), 104  
[headers](#) (*sanic.server.HttpProtocol* attribute), 110  
[headers](#) (*sanic.websocket.WebSocketProtocol* attribute), 117  
[host\(\)](#) (*sanic.blueprints.FutureListener* property), 93  
[host\(\)](#) (*sanic.blueprints.FutureRoute* property), 93  
[host\(\)](#) (*sanic.request.Request* property), 101  
[html\(\)](#) (in module *sanic.response*), 105  
[HTTPMethodView](#) (class in *sanic.views*), 115  
[HttpProtocol](#) (class in *sanic.server*), 109  
[HTTPResponse](#) (class in *sanic.response*), 104
- ## I
- [insert\(\)](#) (*sanic.blueprint\_group.BlueprintGroup* method), 94  
[InvalidRangeType](#), 96  
[InvalidUsage](#), 96  
[ip\(\)](#) (*sanic.request.Request* property), 101  
[is\\_full\(\)](#) (*sanic.request.StreamBuffer* method), 103  
[is\\_request\\_stream](#) (*sanic.server.HttpProtocol* attribute), 110  
[is\\_request\\_stream](#) (*sanic.websocket.WebSocketProtocol* attribute), 117  
[is\\_serving\(\)](#) (*sanic.server.AsyncioServer* method), 109  
[is\\_stream\\_handler\(\)](#) (*sanic.router.Router* method), 108
- ## J
- [json\(\)](#) (in module *sanic.response*), 105  
[json\(\)](#) (*sanic.request.Request* property), 101
- ## K
- [keep\\_alive\(\)](#) (*sanic.server.HttpProtocol* property), 110  
[keep\\_alive\\_timeout](#) (*sanic.server.HttpProtocol* attribute), 110  
[keep\\_alive\\_timeout](#) (*sanic.websocket.WebSocketProtocol* attribute), 117  
[keep\\_alive\\_timeout\\_callback\(\)](#) (*sanic.server.HttpProtocol* method), 110  
[keep\\_alive\\_timeout\\_callback\(\)](#) (*sanic.websocket.WebSocketProtocol* method), 117  
[kwargs\(\)](#) (*sanic.blueprints.FutureException* property), 93  
[kwargs\(\)](#) (*sanic.blueprints.FutureMiddleware* property), 93  
[kwargs\(\)](#) (*sanic.blueprints.FutureStatic* property), 94
- ## L
- [listener\(\)](#) (*sanic.app.Sanic* method), 84  
[listener\(\)](#) (*sanic.Blueprint* method), 126  
[listener\(\)](#) (*sanic.blueprints.Blueprint* method), 91  
[listener\(\)](#) (*sanic.Sanic* method), 120  
[load\\_environment\\_vars\(\)](#) (*sanic.config.Config* method), 95  
[load\\_json\(\)](#) (*sanic.request.Request* method), 101  
[log\(\)](#) (*sanic.handlers.ErrorHandler* method), 99  
[log\\_response\(\)](#) (*sanic.server.HttpProtocol* method), 110  
[lookup\(\)](#) (*sanic.handlers.ErrorHandler* method), 99  
[loop](#) (*sanic.server.AsyncioServer* attribute), 109  
[loop](#) (*sanic.server.HttpProtocol* attribute), 110  
[loop](#) (*sanic.websocket.WebSocketProtocol* attribute), 117  
[loop\(\)](#) (*sanic.app.Sanic* property), 84  
[loop\(\)](#) (*sanic.Sanic* property), 121
- ## M
- [match\\_info\(\)](#) (*sanic.request.Request* property), 101

merge\_environment\_settings() (sanic.testing.SanicASGITestClient method), 114

method (sanic.request.Request attribute), 102

MethodNotSupported, 96

methods () (sanic.blueprints.FutureListener property), 93

methods () (sanic.blueprints.FutureRoute property), 93

methods () (sanic.router.Route property), 107

middleware () (sanic.app.Sanic method), 84

middleware () (sanic.Blueprint method), 127

middleware () (sanic.blueprint\_group.BlueprintGroup method), 94

middleware () (sanic.blueprints.Blueprint method), 91

middleware () (sanic.blueprints.FutureMiddleware property), 93

middleware () (sanic.Sanic method), 121

## N

name () (sanic.blueprints.FutureRoute property), 93

name () (sanic.request.File property), 100

name () (sanic.router.Parameter property), 106

name () (sanic.router.Route property), 107

NotFound, 96

## O

on\_body () (sanic.server.HttpProtocol method), 111

on\_header () (sanic.server.HttpProtocol method), 111

on\_headers\_complete () (sanic.server.HttpProtocol method), 111

on\_message\_complete () (sanic.server.HttpProtocol method), 111

on\_url () (sanic.server.HttpProtocol method), 111

options () (sanic.app.Sanic method), 85

options () (sanic.Blueprint method), 127

options () (sanic.blueprints.Blueprint method), 91

options () (sanic.Sanic method), 121

options () (sanic.testing.SanicTestClient method), 115

output () (sanic.response.HTTPResponse method), 104

## P

Parameter (class in sanic.router), 106

parameter\_pattern (sanic.router.Router attribute), 108

ParameterNameConflicts, 106

parameters () (sanic.router.Route property), 107

parse\_multipart\_form () (in module sanic.request), 103

parse\_parameter\_string () (sanic.router.Router class method), 108

parsed\_args (sanic.request.Request attribute), 102

parsed\_files (sanic.request.Request attribute), 102

parsed\_form (sanic.request.Request attribute), 102

parsed\_forwarded (sanic.request.Request attribute), 102

parsed\_json (sanic.request.Request attribute), 102

parsed\_not\_grouped\_args (sanic.request.Request attribute), 102

parser (sanic.server.HttpProtocol attribute), 111

parser (sanic.websocket.WebSocketProtocol attribute), 117

patch () (sanic.app.Sanic method), 85

patch () (sanic.Blueprint method), 127

patch () (sanic.blueprints.Blueprint method), 91

patch () (sanic.Sanic method), 121

patch () (sanic.testing.SanicTestClient method), 115

path () (sanic.request.Request property), 102

pattern () (sanic.router.Route property), 107

pause\_writing () (sanic.server.HttpProtocol method), 111

PayloadTooLarge, 96

port () (sanic.request.Request property), 102

post () (sanic.app.Sanic method), 85

post () (sanic.Blueprint method), 127

post () (sanic.blueprints.Blueprint method), 91

post () (sanic.Sanic method), 121

post () (sanic.testing.SanicTestClient method), 115

protocol (sanic.response.StreamingHTTPResponse attribute), 104

push\_data () (sanic.server.HttpProtocol method), 111

put () (sanic.app.Sanic method), 85

put () (sanic.Blueprint method), 127

put () (sanic.blueprints.Blueprint method), 92

put () (sanic.request.StreamBuffer method), 103

put () (sanic.Sanic method), 121

put () (sanic.testing.SanicTestClient method), 115

PyFileError, 97

## Q

query\_args () (sanic.request.Request property), 102

query\_string () (sanic.request.Request property), 102

## R

raw () (in module sanic.response), 105

raw\_args () (sanic.request.Request property), 102

raw\_url (sanic.request.Request attribute), 102

read () (sanic.request.StreamBuffer method), 103

receive () (sanic.websocket.WebSocketConnection method), 118

recv () (sanic.websocket.WebSocketConnection method), 118

redirect () (in module sanic.response), 105

register () (in module sanic.static), 113

register () (sanic.Blueprint method), 128

register () (sanic.blueprints.Blueprint method), 92



- register\_blueprint() (*sanic.app.Sanic method*), 86  
 register\_blueprint() (*sanic.Sanic method*), 122  
 register\_listener() (*sanic.app.Sanic method*), 86  
 register\_listener() (*sanic.Sanic method*), 122  
 register\_middleware() (*sanic.app.Sanic method*), 86  
 register\_middleware() (*sanic.Sanic method*), 122  
 remote\_addr() (*sanic.request.Request property*), 102  
 remove() (*sanic.router.Router method*), 108  
 remove\_route() (*sanic.app.Sanic method*), 86  
 remove\_route() (*sanic.Sanic method*), 122  
 Request (*class in sancic.request*), 100  
 request (*sanic.server.HttpProtocol attribute*), 111  
 request (*sanic.websocket.WebSocketProtocol attribute*), 117  
 request() (*sanic.testing.SanicASGITestClient method*), 114  
 request\_buffer\_queue\_size (*sanic.server.HttpProtocol attribute*), 111  
 request\_buffer\_queue\_size (*sanic.websocket.WebSocketProtocol attribute*), 117  
 request\_class (*sanic.server.HttpProtocol attribute*), 111  
 request\_class (*sanic.websocket.WebSocketProtocol attribute*), 117  
 request\_handler (*sanic.server.HttpProtocol attribute*), 111  
 request\_handler (*sanic.websocket.WebSocketProtocol attribute*), 117  
 request\_max\_size (*sanic.server.HttpProtocol attribute*), 111  
 request\_max\_size (*sanic.websocket.WebSocketProtocol attribute*), 117  
 request\_timeout (*sanic.server.HttpProtocol attribute*), 111  
 request\_timeout (*sanic.websocket.WebSocketProtocol attribute*), 117  
 request\_timeout\_callback() (*sanic.server.HttpProtocol method*), 111  
 request\_timeout\_callback() (*sanic.websocket.WebSocketProtocol method*), 117  
 RequestParameters (*class in sancic.request*), 103  
 RequestTimeout, 97  
 response() (*sanic.handlers.ErrorHandler method*), 99  
 response\_timeout (*sanic.server.HttpProtocol attribute*), 111  
 response\_timeout (*sanic.websocket.WebSocketProtocol attribute*), 117  
 response\_timeout\_callback() (*sanic.server.HttpProtocol method*), 111  
 response\_timeout\_callback() (*sanic.websocket.WebSocketProtocol method*), 117  
 resume\_writing() (*sanic.server.HttpProtocol method*), 111  
 Route (*class in sancic.router*), 106  
 route() (*sanic.app.Sanic method*), 87  
 route() (*sanic.Blueprint method*), 128  
 route() (*sanic.blueprints.Blueprint method*), 92  
 route() (*sanic.Sanic method*), 123  
 RouteDoesNotExist, 107  
 RouteExists, 107  
 Router (*class in sancic.router*), 107  
 router (*sanic.server.HttpProtocol attribute*), 111  
 router (*sanic.websocket.WebSocketProtocol attribute*), 117  
 routes\_always\_check (*sanic.router.Router attribute*), 108  
 routes\_dynamic (*sanic.router.Router attribute*), 108  
 routes\_static (*sanic.router.Router attribute*), 108  
 run() (*sanic.app.Sanic method*), 87  
 run() (*sanic.Sanic method*), 123
- ## S
- Sanic (*class in sancic*), 118  
 Sanic (*class in sancic.app*), 82  
 sancic (*module*), 118  
 sancic.app (*module*), 82  
 sancic.blueprint\_group (*module*), 94  
 sancic.blueprints (*module*), 89  
 sancic.config (*module*), 95  
 sancic.constants (*module*), 95  
 sancic.cookies (*module*), 95  
 sancic.exceptions (*module*), 96  
 sancic.handlers (*module*), 98  
 sancic.log (*module*), 100  
 sancic.request (*module*), 100  
 sancic.response (*module*), 104  
 sancic.router (*module*), 106  
 sancic.server (*module*), 109  
 sancic.static (*module*), 113  
 sancic.testing (*module*), 114  
 sancic.views (*module*), 115  
 sancic.websocket (*module*), 116  
 SanicASGIAdapter (*class in sancic.testing*), 114  
 SanicASGITestClient (*class in sancic.testing*), 114  
 SanicException, 97  
 SanicTestClient (*class in sancic.testing*), 115  
 scheme() (*sanic.request.Request property*), 102  
 send() (*sanic.testing.SanicASGIAdapter method*), 114  
 send() (*sanic.websocket.WebSocketConnection method*), 118

- serve() (in module *sanic.server*), 112  
 serve\_coro (*sanic.server.AsyncioServer* attribute), 109  
 serve\_multiple() (in module *sanic.server*), 113  
 server (*sanic.server.AsyncioServer* attribute), 109  
 server\_name() (*sanic.request.Request* property), 102  
 server\_port() (*sanic.request.Request* property), 103  
 ServerError, 97  
 ServiceUnavailable, 97  
 Signal (class in *sanic.server*), 112  
 signal (*sanic.server.HttpProtocol* attribute), 111  
 signal (*sanic.websocket.WebSocketProtocol* attribute), 117  
 size (*sanic.handlers.ContentRangeHandler* attribute), 98  
 socket() (*sanic.request.Request* property), 103  
 start (*sanic.handlers.ContentRangeHandler* attribute), 98  
 state (*sanic.server.HttpProtocol* attribute), 111  
 state (*sanic.websocket.WebSocketProtocol* attribute), 117  
 static() (*sanic.app.Sanic* method), 87  
 static() (*sanic.Blueprint* method), 128  
 static() (*sanic.blueprints.Blueprint* method), 92  
 static() (*sanic.Sanic* method), 124  
 status (*sanic.response.HTTPResponse* attribute), 104  
 status (*sanic.response.StreamingHTTPResponse* attribute), 104  
 status\_code (*sanic.exceptions.ContentRangeError* attribute), 96  
 status\_code (*sanic.exceptions.Forbidden* attribute), 96  
 status\_code (*sanic.exceptions.HeaderExpectationFailed* attribute), 96  
 status\_code (*sanic.exceptions.InvalidUsage* attribute), 96  
 status\_code (*sanic.exceptions.MethodNotSupported* attribute), 96  
 status\_code (*sanic.exceptions.NotFound* attribute), 96  
 status\_code (*sanic.exceptions.PayloadTooLarge* attribute), 96  
 status\_code (*sanic.exceptions.RequestTimeout* attribute), 97  
 status\_code (*sanic.exceptions.ServerError* attribute), 97  
 status\_code (*sanic.exceptions.ServiceUnavailable* attribute), 97  
 status\_code (*sanic.exceptions.Unauthorized* attribute), 98  
 stop() (*sanic.app.Sanic* method), 88  
 stop() (*sanic.Sanic* method), 124  
 stopped (*sanic.server.Signal* attribute), 112  
 stream (*sanic.request.Request* attribute), 103  
 stream() (in module *sanic.response*), 106  
 stream() (in module *sanic.views*), 116  
 stream() (*sanic.blueprints.FutureRoute* property), 94  
 stream() (*sanic.response.StreamingHTTPResponse* method), 104  
 stream\_response() (*sanic.server.HttpProtocol* method), 111  
 StreamBuffer (class in *sanic.request*), 103  
 streaming\_fn (*sanic.response.StreamingHTTPResponse* attribute), 104  
 StreamingHTTPResponse (class in *sanic.response*), 104  
 strict\_slashes() (*sanic.blueprints.FutureRoute* property), 94  
 strtobool() (in module *sanic.config*), 95
- ## T
- test\_client() (*sanic.app.Sanic* property), 88  
 test\_client() (*sanic.Sanic* property), 124  
 TestASGIApp (class in *sanic.testing*), 115  
 text() (in module *sanic.response*), 106  
 token() (*sanic.request.Request* property), 103  
 total (*sanic.handlers.ContentRangeHandler* attribute), 98  
 transport (*sanic.request.Request* attribute), 103  
 transport (*sanic.server.HttpProtocol* attribute), 111  
 transport (*sanic.websocket.WebSocketProtocol* attribute), 117  
 trigger\_events() (in module *sanic.server*), 113  
 trigger\_events() (*sanic.app.Sanic* method), 88  
 trigger\_events() (*sanic.Sanic* method), 124  
 type() (*sanic.request.File* property), 100
- ## U
- Unauthorized, 97  
 uri() (*sanic.blueprints.FutureListener* property), 93  
 uri() (*sanic.blueprints.FutureRoute* property), 94  
 uri() (*sanic.blueprints.FutureStatic* property), 94  
 uri() (*sanic.router.Route* property), 107  
 uri\_template (*sanic.request.Request* attribute), 103  
 url (*sanic.server.HttpProtocol* attribute), 111  
 url (*sanic.websocket.WebSocketProtocol* attribute), 117  
 url() (*sanic.request.Request* property), 103  
 url\_for() (*sanic.app.Sanic* method), 88  
 url\_for() (*sanic.request.Request* method), 103  
 url\_for() (*sanic.Sanic* method), 124  
 url\_hash() (in module *sanic.router*), 108  
 url\_prefix() (*sanic.blueprint\_group.BlueprintGroup* property), 95  
 URLBuildError, 97
- ## V
- version (*sanic.request.Request* attribute), 103  
 version() (*sanic.blueprints.FutureRoute* property), 94



## W

- `wait_closed()` (*sanic.server.AsyncioServer method*), 109
- `websocket()` (*sanic.app.Sanic method*), 88
- `websocket()` (*sanic.Blueprint method*), 128
- `websocket()` (*sanic.blueprints.Blueprint method*), 92
- `websocket()` (*sanic.Sanic method*), 125
- `websocket()` (*sanic.testing.SanicASGITestClient method*), 115
- `websocket()` (*sanic.testing.SanicTestClient method*), 115
- `websocket_handshake()` (*sanic.websocket.WebSocketProtocol method*), 117
- `WebSocketConnection` (*class in sanc.websocket*), 117
- `WebSocketProtocol` (*class in sanc.websocket*), 116
- `write()` (*sanic.response.StreamingHTTPResponse method*), 104
- `write_error()` (*sanic.server.HttpProtocol method*), 111
- `write_response()` (*sanic.server.HttpProtocol method*), 112
- `write_response()` (*sanic.websocket.WebSocketProtocol method*), 117